

# Object-Oriented KRR with Flora-2 – Access Control and Privacy Control Example

CSE 505 – Computing with Logic

Stony Brook University

<http://www.cs.stonybrook.edu/~cse505>

# Knowledge Representation and Reasoning with Flora-2

- Example: Social networks have complex information access and privacy policies.
  - In this example, we model such a network and use it to create various views based on these policies for friends, public, private and groups
- A user has several properties with various access policies:

```
User [|  
    // String_Object, Gender_Object,  
    // Location, and others are subclasses of  
    // Access_Controlled and can have access  
    // permissions  
    first_name           => String_Object,  
    last_name            => String_Object,  
    profile              => Profile_Object,
```

# Knowledge Representation and Reasoning with Flora-2

```
cover                => Cover_Object,  
gender      {0..1}  => Gender_Object,  
email                => String_Object,  
birthday    {0..1}  => Birthday_Object,  
userid       {1..1} => String_Object,  
user_name                => String_Object,  
education_history => School_Attendance,  
job_history             => Job_Held,  
relationship           => Relationship,  
location               => Location,  
content                => Content,  
// created objects: Page, Event, Group  
creates                => Created_Objects,  
likes                  => LikeContent,  
timeline               => Timeline_Object  
transaction            => Transaction,
```

```
] ].
```

# Knowledge Representation and Reasoning with Flora-2

- A class of all objects to which access can be controlled:

```
Access_Controlled[|  
    read(Access_Entity)    => \boolean,  
    write(Access_Entity) => \boolean,  
    find(Access_Entity, Access_Entity) => \boolean,  
    default values inherited by all objects unless overwritten:  
    read(?)                -> \false,  
    write(?)               -> \false,  
    find(?, ?)             -> \false  
|].
```

# Knowledge Representation and Reasoning with Flora-2

- Entities that can have access control privacy control:

```
{male,female}:Gender_Object.  
Gender_Object::Access_Controlled[|  
    value => Gender_Type  
|].
```

```
Birthday_Object::Access_Controlled[|  
    value => \date  
|].
```

```
{spouse,friend,girlfriend,parent,child} :  
    Relationship.  
Relationship::Access_Controlled[|  
    type    => Relationship_Type,  
    person => User  
|].
```

# Knowledge Representation and Reasoning with Flora-2

```
Attendance::Access_Controlled[|  
    institution {1..1} => \string,  
    start       {0..1} => \date,  
    end         {0..1} => \date,  
    address                               => Address  
|].  
{School_Attendance, Job_Held} :: Attendance.
```

```
School_Attendance[|  
    status => \string,  
    level  => \string  
|].
```

```
Job_Held[|  
    position => \string  
|].
```

# Knowledge Representation and Reasoning with Flora-2

```
Location::Access_Controlled[|  
    country      => \string,  
    region       => \string,  
    city         => \string,  
    latitude     => \decimal,  
    longitude    => \decimal  
|].
```

```
// general address  
Address :: Location[|  
    street       {0..1} => \string,  
    number       {0..1} => \string,  
    apartment    {0..1} => \string,  
    zipcode      {0..1} => \string  
|].
```

# Knowledge Representation and Reasoning with Flora-2

```
{Photo,Video,Comment,Note,Group,Event,Link,  
  StatusPost,Message} :: Content.
```

```
Content::Access_Controlled[|  
  author          {1..1} => User,  
  creation_time {1..1} => \datetime,  
  description      => \string,  
  comment          => Comment,  
  tags             => Tag,  
  audience         => Audience  
|].
```

```
Timeline[|  
  content => Content
```

```
|].
```

```
{Public, Friends, FriendsofFriends, OnlyMe} :  
  Audience.
```



# Knowledge Representation and Reasoning with Flora-2

- Social networks also provide access to purchasing products and store information about login and transactions:

```
Product [|  
    name      {1..1} => \string,  
    owner           => \string,  
    price   {1..1} => \decimal,  
    description      => \string  
|].
```

```
Transaction::Access_Controlled [|  
    account => Account,  
    time    => \datetime,  
    product => Product,  
    amount  => \decimal  
|].
```

# Knowledge Representation and Reasoning with Flora-2

```
Account[|  
    bank_name      {1..1} => \string,  
    account_number {1..1} => \string,  
    created        {1..1} => \date,  
    owner          {1..*} => User  
|].
```

```
Cookie[|  
    device      => \string,  
    browser     => \string,  
    os          => \string,  
    location    => Location,  
    IP_address  => \string,  
    login       => \string,  
    time        => \datetime  
|].
```

# Knowledge Representation and Reasoning with Flora-2

```
paul:User[
    relationship -> paul_mary_relationship,
    relationship -> paul_john_relationship,
    relationship -> paul_mike_relationship,
    relationship -> paul_jack_relationship,
    timeline -> paul_timeline
].
paul_mary_relationship:Relationship[
    type -> spouse,
    person -> mary
].
paul_john_relationship:Relationship[
    type -> child,
    person -> john
].
```

# Knowledge Representation and Reasoning with Flora-2

```
paul_jack_relationship:Relationship[
  type -> friend,
  person -> jack
].
paul_timeline:Timeline[
  content -> post1,
  content -> photo1
].
post1:Post[
  value -> "I am in Berlin",
  audience -> Family
].
photo1:Photo[
  imageName -> "Berlin 1",
  audience -> Friends
].
```

# Knowledge Representation and Reasoning with Flora-2

```
mary:User[
    relationship -> mary_paul_relationship,
    relationship -> mary_john_relationship,
    relationship -> mary_mike_relationship,
    relationship -> mary_jack_relationship,
    relationship -> mary_jane_relationship,
    timeline -> mary_timeline
].
mary_paul_relationship:Relationship[
    type -> spouse,
    person -> paul
].
mary_john_relationship:Relationship[
    type -> child,
    person -> john
].
```

# Knowledge Representation and Reasoning with Flora-2

```
mary_jack_relationship:Relationship[
    type -> friend,
    person -> jack
].
mary_jane_relationship:Relationship[
    type -> friend,
    person -> jane
].
mary_timeline:Timeline[
    content -> post2,
    content -> photo2
].
```

# Knowledge Representation and Reasoning with Flora-2

```
post2:Post[
  value -> "I am in Berlin",
  audience -> Family
].
photo2:Photo[
  imageName -> "Berlin 1",
  audience -> Friends
].
john:User[
  relationship -> john_paul_relationship,
  relationship -> john_mary_relationship,
  relationship -> john_mike_relationship,
  relationship -> john_jasmine_relationship,
  relationship -> john_sun_relationship,
  timeline -> john_timeline
]. ...
```

# Knowledge Representation and Reasoning with Flora-2

```
// a user's timeline
timeLine(?User, ?ListContent):-
    ?User:User[
        timeline -> ?UserTimeline
    ],
    ?ListContent = setof( ?Content |
        ?UserTimeline[ content -> ?Content ] ).
```

- We will filter it for a viewer depending on the relationship with the current user.



# Knowledge Representation and Reasoning with Flora-2

```
filter_only_family(?User,?User2,?ListContent):-
    ?User:User[
        relationship -> ?Relationship
    ],
    (?Relationship[type->spouse,person->?User2];
    ?Relationship[type->child, person->?User2];
    ?Relationship[type->parent, person->?User2];
    ?Relationship[type->grandparent,person->?User2]
    ),
    ?ListContent = setof( ?Content |
        ?UserTimeline[ content -> ?Content[
            audience -> Family ] ] ).
```

# Knowledge Representation and Reasoning with Flora-2

```
filter_only_friends(?User,?User2,?ListContent):-  
    ?User:User[  
        relationship -> ?Relationship  
    ],  
    ?Relationship[type->friend,person->?User2],  
    ?ListContent = setof( ?Content |  
        ?UserTimeline[ content -> ?Content[  
            audience -> Friends ] ] ).
```

# Knowledge Representation and Reasoning with Flora-2

```
filter_only_friends_of_friends ...
```