

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT

on

COURSE TITLE

Submitted by

NISHCHAL NANDAGOPAL (1BM19CS105)

in partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

May-2022 to July-2022

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “MACHINE LEARNING” carried out by **NISHCHAL NANDAGOPAL(1BM19CS105)**, who is bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2022. The Lab report has been approved as it satisfies the academic requirements in respect of a **Course Title - (Course code)** work prescribed for the said degree.

Name of the Lab-Incharge
Designation
Department of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index Sheet

SL NO	EXPERIMENT	PAGE NO
1	FIND S ALGORITHM	3
2	CANDIDATE ELIMINATION ALGORITHM	4
3	DECISION TREE USING ID3 ALGORITHM	6
4	LINEAR REGRESSION	10
5	NAÏVE BAYES NETWORK	12

WEEK 1

FIND S ALGORITHM

```
import pandas as pd
import numpy as np

#to read the data in the csv file
print("USN:1BM19CS095")
data = pd.read_csv(r"C:\Users\admin\Downloads\data.csv")
print(data,"\n")

#making an array of all the attributes
d = np.array(data)[:,:-1]
print("The attributes are: ",d)

#segragating the target that has positive and negative examples
target = np.array(data)[:,-1]
print("The target is: ",target)

#training function to implement find-s algorithm
def train(c,t):
    for i, val in enumerate(t):
```

```

    if val == "Yes":
        specific_hypothesis = c[i].copy()
        break

for i, val in enumerate(c):
    if t[i] == "Yes":
        for x in range(len(specific_hypothesis)):
            if val[x] != specific_hypothesis[x]:
                specific_hypothesis[x] = '?'
            else:
                pass

return specific_hypothesis

#obtaining the final hypothesis
print("\n The final hypothesis is:",train(d,target))

```

OUTPUT

	Time	Weather	Temperature	Company	Humidity	Wind	Goes
0	Morning	Sunny	Warm	Yes	Mild	Strong	Yes
1	Evening	Rainy	Cold	No	Mild	Normal	No
2	Morning	Sunny	Moderate	Yes	Normal	Normal	Yes
3	Evening	Sunny	Cold	Yes	High	Strong	Yes

The attributes are: [['Morning' 'Sunny' 'Warm' 'Yes' 'Mild' 'Strong']
['Evening' 'Rainy' 'Cold' 'No' 'Mild' 'Normal']
['Morning' 'Sunny' 'Moderate' 'Yes' 'Normal' 'Normal']
['Evening' 'Sunny' 'Cold' 'Yes' 'High' 'Strong']]

WEEK 2

CANDIDATE ELIMINATION ALGORITHM

```

Import
numpy
as np

import pandas as pd

data = pd.read_csv(r'C:\Users\admin\Downloads\enjoysport.csv')
concepts = np.array(data.iloc[:,0:-1])
print("\nInstances are:\n",concepts)
target = np.array(data.iloc[:,-1])

```

```

print("\nTarget Values are: ",target)

def learn(concepts, target):
    specific_h = concepts[0].copy()
    print("\nInitialization of specific_h and general_h")
    print("\nSpecific Boundary: ", specific_h)
    general_h = [["?" for i in range(len(specific_h))] for i in
range(len(specific_h))]
    print("\nGeneric Boundary: ",general_h)

    for i, h in enumerate(concepts):
        print("\nInstance", i+1 , "is ", h)
        if target[i] == "yes":
            print("Instance is Positive ")
            for x in range(len(specific_h)):
                if h[x] != specific_h[x]:
                    specific_h[x] = '?'
                    general_h[x][x] = '?'

        if target[i] == "no":
            print("Instance is Negative ")
            for x in range(len(specific_h)):
                if h[x] != specific_h[x]:
                    general_h[x][x] = specific_h[x]
                else:
                    general_h[x][x] = '?'

        print("Specific Boundary after ", i+1, "Instance is ", specific_h)
        print("Generic Boundary after ", i+1, "Instance is ", general_h)
        print("\n")

    indices = [i for i, val in enumerate(general_h) if val == ['?', '?', '?', '?',
'?', '?']]
    for i in indices:
        general_h.remove(['?', '?', '?', '?', '?', '?'])
    return specific_h, general_h

s_final, g_final = learn(concepts, target)

print("Final Specific_h: ", s_final, sep="\n")
print("Final General_h: ", g_final, sep="\n")

```

OUTPUT

```

Instances are:
[['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
 ['sunny' 'warm' 'high' 'strong' 'warm' 'same']
 ['rainy' 'cold' 'high' 'strong' 'warm' 'change']
 ['sunny' 'warm' 'high' 'strong' 'cool' 'change']]

Target Values are: ['yes' 'yes' 'no' 'yes']

Initialization of specific_h and general_h

Specific Boundary: ['sunny' 'warm' 'normal' 'strong' 'warm' 'same']

Generic Boundary: [['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?',
'?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Instance 1 is ['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
Instance is Positive
Specific Boundary after 1 Instance is ['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
Generic Boundary after 1 Instance is [['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?',
'?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Instance 2 is ['sunny' 'warm' 'high' 'strong' 'warm' 'same']
Instance is Positive
Specific Boundary after 2 Instance is ['sunny' 'warm' '?' 'strong' 'warm' 'same']
Generic Boundary after 2 Instance is [['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?',
'?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Instance 3 is ['rainy' 'cold' 'high' 'strong' 'warm' 'change']
Instance is Negative
Specific Boundary after 3 Instance is ['sunny' 'warm' '?' 'strong' 'warm' 'same']
Generic Boundary after 3 Instance is [['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?',
'?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', 'same']]

Instance 4 is ['sunny' 'warm' 'high' 'strong' 'cool' 'change']
Instance is Positive
Specific Boundary after 4 Instance is ['sunny' 'warm' '?' 'strong' '?' '?']
Generic Boundary after 4 Instance is [['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?',
'?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Final Specific_h:
['sunny' 'warm' '?' 'strong' '?' '?']
Final General_h:
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?']]

```

WEEK 3

DECISION TREE USING ID3 ALGORITHM

```

import
math

import csv
def load_csv(filename):
    lines=csv.reader(open(filename,"r"))
    dataset = list(lines)
    headers = dataset.pop(0)
    return dataset,headers

class Node:
    def __init__(self,attribute):
        self.attribute=attribute

```

```

        self.children=[]
        self.answer=""

def subtables(data,col,delete):
    dic={}
    coldata=[row[col] for row in data]
    attr=list(set(coldata))

    counts=[0]*len(attr)
    r=len(data)
    c=len(data[0])
    for x in range(len(attr)):
        for y in range(r):
            if data[y][col]==attr[x]:
                counts[x]+=1

    for x in range(len(attr)):
        dic[attr[x]]=[[0 for i in range(c)] for j in range(counts[x])]
        pos=0
        for y in range(r):
            if data[y][col]==attr[x]:
                if delete:
                    del data[y][col]
                dic[attr[x]][pos]=data[y]
                pos+=1
    return attr,dic

def entropy(S):
    attr=list(set(S))
    if len(attr)==1:
        return 0

    counts=[0,0]
    for i in range(2):
        counts[i]=sum([1 for x in S if attr[i]==x])/(len(S)*1.0)

    sums=0
    for cnt in counts:
        sums+=-1*cnt*math.log(cnt,2)
    return sums

def compute_gain(data,col):
    attr,dic = subtables(data,col,delete=False)

    total_size=len(data)
    entropies=[0]*len(attr)
    ratio=[0]*len(attr)

    total_entropy=entropy([row[-1] for row in data])
    for x in range(len(attr)):
        ratio[x]=len(dic[attr[x]])/(total_size*1.0)
        entropies[x]=entropy([row[-1] for row in dic[attr[x]]])
        total_entropy-=ratio[x]*entropies[x]
    return total_entropy

```

```

def build_tree(data, features):
    lastcol=[row[-1] for row in data]
    if(len(set(lastcol))==1):
        node=Node("")
        node.answer=lastcol[0]
        return node

    n=len(data[0])-1
    gains=[0]*n
    for col in range(n):
        gains[col]=compute_gain(data,col)
    split=gains.index(max(gains))
    node=Node(features[split])
    fea = features[:split]+features[split+1:]

    attr,dic=subtables(data,split,delete=True)

    for x in range(len(attr)):
        child=build_tree(dic[attr[x]],fea)
        node.children.append((attr[x],child))
    return node

def print_tree(node,level):
    if node.answer!="":
        print("  "*level,node.answer)
        return

    print("  "*level,node.attribute)
    for value,n in node.children:
        print("  "*(level+1),value)
        print_tree(n,level+2)

def classify(node,x_test,features):
    if node.answer!="":
        print(node.answer)
        return
    pos=features.index(node.attribute)
    for value, n in node.children:
        if x_test[pos]==value:
            classify(n,x_test,features)

'''Main program'''
dataset,features=load_csv(r"C:\Users\admin\Downloads\id3.csv")
node1=build_tree(dataset,features)

print("The decision tree for the dataset using ID3 algorithm is")
print_tree(node1,0)
testdata,features=load_csv(r"C:\Users\admin\Downloads\id3_test.csv")

```



```

for xtest in testdata:
    print("The test instance:",xtest)
    print("The label for test instance:")
    classify(node1,xtest,features)

```

OUTPUT

```

The decision tree for the dataset using ID3 algorithm is
Outlook
  overcast
    yes
  rain
    Wind
      strong
        no
      weak
        yes
  sunny
    Humidity
      high
        no
      normal
        yes
The test instance: ['rain', 'cool', 'normal', 'strong']
The label for test instance:
no
The test instance: ['sunny', 'mild', 'normal', 'strong']
The label for test instance:
yes

```

WEEK 4

LINEAR REGRESSION

```

import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

dataset = pd.read_csv('salary_data.csv')
X = dataset.iloc[:, :-1].values
y = dataset.iloc[:, 1].values

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=1/3,
random_state=0)

```

```

# Fitting Simple Linear Regression to the Training set
from sklearn.linear_model import LinearRegression
regressor = LinearRegression()
regressor.fit(X_train, y_train)

# Predicting the Test set results
y_pred = regressor.predict(X_test)

# Visualizing the Training set results
viz_train = plt
viz_train.scatter(X_train, y_train, color='red')
viz_train.plot(X_train, regressor.predict(X_train), color='blue')
viz_train.title('Salary VS Experience (Training set)')
viz_train.xlabel('Year of Experience')
viz_train.ylabel('Salary')
viz_train.show()

# Visualizing the Test set results
viz_test = plt
viz_test.scatter(X_test, y_test, color='red')
viz_test.plot(X_train, regressor.predict(X_train), color='blue')
viz_test.title('Salary VS Experience (Test set)')
viz_test.xlabel('Year of Experience')
viz_test.ylabel('Salary')
viz_test.show()

```

OUTPUT





LAB 5

NAÏVE BAYES NETWORK

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.naive_bayes import GaussianNB
from sklearn import metrics

df = pd.read_csv(r"C:\Users\admin\Downloads\data5.csv")
col_names = ['num_preg', 'glucose_conc', 'diastolic_bp', 'thickness',
             'insulin', 'bmi', 'diab_pred', 'age']
predicted_class = ['diabetes']

X = df[col_names].values
y = df[predicted_class].values

print(df.head)
xtrain,xtest,ytrain,ytest=train_test_split(X,y,test_size=0.4)

print ('\n the total number of Training Data :',ytrain.shape)
print ('\n the total number of Test Data :',ytest.shape)

clf = GaussianNB().fit(xtrain,ytrain.ravel())
predicted = clf.predict(xtest)
predictTestData= clf.predict([[6,148,72,35,0,33.6,0.627,50]])
```

```

print('\n Confusion matrix')
print(metrics.confusion_matrix(ytest,predicted))

print('\n Accuracy of the classifier
is',metrics.accuracy_score(ytest,predicted))

print('\n The value of Precision', metrics.precision_score(ytest,predicted))

print('\n The value of Recall', metrics.recall_score(ytest,predicted))

print("Predicted Value for individual Test Data:", predictTestData)

```

<bound	method	NDFrame.head of	num_preg	glucose_conc	diastolic_bp	thickness	insulin	bmi \
0	6	148	72	35	0	33.6		
1	1	85	66	29	0	26.6		
2	8	183	64	0	0	23.3		
3	1	89	66	23	94	28.1		
4	0	137	40	35	168	43.1		
..		
763	10	101	76	48	180	32.9		
764	2	122	70	27	0	36.8		
765	5	121	72	23	112	26.2		
766	1	126	60	0	0	30.1		
767	1	93	70	31	0	30.4		

	diab_pred	age	diabetes
0	0.627	50	1
1	0.351	31	0
2	0.672	32	1
3	0.167	21	0
4	2.288	33	1
..
763	0.171	63	0
764	0.340	27	0
765	0.245	30	0
766	0.349	47	1
767	0.315	23	0

[768 rows x 9 columns]>

the total number of Training Data : (460, 1)

the total number of Test Data : (308, 1)

```

Confusion matrix
[[176  29]
 [ 40  63]]

```

Accuracy of the classifier is 0.775974025974026

The value of Precision 0.6847826086956522

The value of Recall 0.6116504854368932

Predicted Value for individual Test Data: [1]

