

# MOTOMAN MH24

Handling & General Applications with the MH-series



The 6-axis MOTOMAN MH24 high-speed robot from YASKAWA offers outstanding performance in a wide range of applications, e.g. handling or machine tending. The hollow structure of the upper arm (diameter 50 mm) of this universal robot allows internal routing of supply lines, thereby reducing interference contours and increasing the service life of the hose package. Despite the hollow design, the outer contour of the upper arm has only been slightly modified.

With its high payload capacity of 24 kg and streamlined design, the MOTOMAN MH24 only has a small footprint. Maintenance is simplified by means of a preventive maintenance function for gearmotors and hardware.


New safety functions, such as position monitoring of the robot and accessories for motion limitation, and an external media package for field bus cables are optionally available.


#### **KEY BENEFITS**

- Fast, compact and powerful (max. payload capacity 24 kg)
- Universally deployable
- Hollow front arm:
  - Diameter 50 mm
  - Additional payload 12 kg
  - Minimized interference contours
- Simple servicing/maintenance
- Advanced safety functions




## **MOTOMAN MH24**









# Please note wall mounting option: ±30° S-axis limit


# Please note ceiling mounting option:

Depends on B-axis position


# Please note

tilted robot: 0°-90° limitation of S-axis, details on request

# Allowable wrist load




#### View A



#### View B




#### View C



Mounting options: Floor, ceiling, wall Protection class: IP54/67

## View D



Specifications MH24						
Axes	Maximum motion range [°]	Maximum speed [°/sec.]	Allowable moment [Nm]	Allowable moment of inertia [kg · m²]	Controlled axes	6
					Max. payload [kg]	24
S	±180	197	-	-	Repeatability [mm]	±0.06
L	+155/-105	190	-	-	Max. working range R [mm]	1730
U	+240/-170	210	-	-	Temperature [°C]	0 to +45
R	±200	410	50.0	2.1	Humidity [%]	20 – 80
В	±150	410	50.0	2.1	Weight [kg]	268
Т	±455	620	30.4	1.1	Power supply, average [KVA]	2.0



### YASKAWA Europe GmbH

Robotics Yaskawastraße 1 85391 Allershausen, Germany Tel. +49 (0) 8166 90-0 robotics@yaskawa.eu.com All dimensions in mm

Technical data may be subject to change without previous notice | Please request detailed drawings at robotics@yaskawa.eu.com

YR-MH00024-A00 A-03-2017, A-Nr. 167089