# JavaScript Test Day 10_Feb 20

Q.1

What is printed in the console?

```
var foo = function foo()
{
   console.log(foo === foo);
};
foo();
```

a) **True** b) False c) ReferanceError

Q.2

```
function aaa()
{
   return
   {
      test: 1
   };
}
alert(typeof aaa());
```

What does the above alert?

a) function b) number c) object d) **undefined**

Q.3

What is the result?

```
Number("1") - 1 == 0;
```

a) **True** b) False c) TypeError

Q.4

(true + false) > 2 + true;

What is the result?

a) True b) **False** c) Type Erroe d) NaN

Q.5

```
function bar()
{
   return foo;
   foo = 10;
   function foo() {}
   var foo = '11';
}
alert(typeof bar());
```

What is alerted?

a) number b) **function** c) undefined d) string e) Error

Q.6

"1" - - "1";

What is the result?

a) 0 b) **2** c) 11 d) “11”

Q.7

```
var x = 3;
var foo =
{
   x: 2,
   baz:
  {
      x: 1,
      bar: function()
    {
        return this.x;
      }
   }
}
var go = foo.baz.bar;
alert(go());
alert(foo.baz.bar());
```

What is the order of values alerted?

a) 1,2 b) 1,3 c) 2,1 d) 2,3 e) **3,1** f) 3,2

Q.8

```
new String("This is a string") instanceof String;
```

What is the result?

a) **True** b) False c) TypeError

Q.9

[] + [] + 'foo'.split('');

What is the result?

a) **“f, o, o,”** b) TypeError c) [“f”, “o”, “o”] d) [] [] [“f”, “o”, “o”]

Q.10

new Array(5).toString();

What is the result?

a) **“,,,,”** b) [] c) “[]”

Q.11

```
var myArr = ['foo', 'bar', 'baz'];
myArr.length = 0;
myArr.push('bin');
console.log(myArr);
```

What is printed in the console?

a) [‘foo’, ‘bar’, ‘baz’] b) [‘foo’, ‘bar’, ‘baz’, ‘bin’]

c) [‘bin’, ‘foo’, ‘bar’, ‘baz’] d) **[‘bin’]**

Q.12

String('Hello') === 'Hello';

What is the result?

a) **True** b) False c) TypeError

Q.13

```
var x = 0;
function foo()
{
   x++;
   this.x = x;
   return foo;
}
var bar = new new foo;
console.log(bar.x);
```

What is printed on the console?

a) ReferrenceError b) TypeError c) **undefined** d) 0 e) 1

Q.14

```
"This is a string" instanceof String;
```

What is the result?

a) True b) **False** c) TypeError

Q.15

```
var bar = 1,
   foo = {};
foo:
{
   bar: 2;
   baz: ++bar;
};
foo.baz + foo.bar + bar;
```

What is the result?

a) ReferenceError b) TypeError c) undefined d) **NaN** d) 4 e) 5

Q.16

```
var myArr = ['foo', 'bar', 'baz'];
myArr[2];
console.log('2' in myArr);
```

What is the result of console.log?

a) **True** b) False c) ReferenceError

Q.17

```
var arr = [];
arr[0]  = 'a';
arr[1]  = 'b';
arr.foo = 'c';
alert(arr.length);
```

What value is alerted?

a) 1 b) **2** c) 3 d) undefined

Q.18

```
10 > 9 > 8 === true;
```

What is the result?

a) True b) **False**

Q.19

```
function foo(a, b)
{
   arguments[1] = 2;
   alert(b);
}
foo(1);
```

What value is alerted?

a) 2 b) **undefined** c) ReferenceError

Q.20

```
NaN === NaN;
```

What is the result?

a) True b) **False** c) TypeError