

Cheat Sheet: Python Data Structures Part-2

Dictionaries

Package/Method	Description	Code Example
Creating a Dictionary	A dictionary is a built-in data type that represents a collection of key-value pairs. Dictionaries are enclosed in curly braces {}.	<div>Example:</div> <pre>1. 1 2. 2 1. dict_name = {} #Creates an empty dictionary 2. person = { "name": "John", "age": 30, "city": "New York"}</pre> <div>Copied!</div> <div>Syntax:</div> <pre>1. 1 1. Value = dict_name["key_name"]</pre> <div>Copied!</div>
Accessing Values	You can access the values in a dictionary using their corresponding keys.	<div>Example:</div> <pre>1. 1 2. 2 1. name = person["name"] 2. age = person["age"]</pre> <div>Copied!</div> <div>Syntax:</div> <pre>1. 1 1. dict_name[key] = value</pre> <div>Copied!</div>
Add or modify	Inserts a new key-value pair into the dictionary. If the key already exists, the value will be updated; otherwise, a new entry is created.	<div>Example:</div> <pre>1. 1 2. 2 1. person["Country"] = "USA" # A new entry will be created. 2. person["city"] = "Chicago" # Update the existing value for the same key</pre> <div>Copied!</div> <div>Syntax:</div> <pre>1. 1 1. del dict_name[key]</pre> <div>Copied!</div>
del	Removes the specified key-value pair from the dictionary. Raises a KeyError if the key does not exist.	<div>Example:</div> <pre>1. 1 1. del person["Country"]</pre> <div>Copied!</div> <div>Syntax:</div> <pre>1. 1 1. dict_name.update({key: value})</pre> <div>Copied!</div>
update()	The update() method merges the provided dictionary into the existing dictionary, adding or updating key-value pairs.	<div>Example:</div> <pre>1. 1 1. person.update({"Profession": "Doctor"})</pre> <div>Copied!</div>
clear()	The clear() method empties the dictionary, removing all key-value pairs within it. After this operation, the dictionary is still accessible and can be used further.	<div>Syntax:</div> <pre>1. 1 1. dict_name.clear()</pre> <div>Copied!</div> <div>Example:</div> <pre>1. 1 1. grades.clear()</pre>

Copied!

Example:

```
1. 1
2. 2

1. if "name" in person:
2.     print("Name exists in the dictionary.")
```

Copied!

Syntax:

```
1. 1

1. new_dict = dict_name.copy()
```

Copied!

Example:

```
1. 1
2. 2

1. new_person = person.copy()
2. new_person = dict(person) # another way to create a copy of dictionary
```

Copied!

Syntax:

```
1. 1

1. keys_list = list(dict_name.keys())
```

Copied!

Example:

```
1. 1

1. person_keys = list(person.keys())
```

Copied!

Syntax:

```
1. 1

1. values_list = list(dict_name.values())
```

Copied!

Example:

```
1. 1

1. person_values = list(person.values())
```

Copied!

Syntax:

```
1. 1

1. items_list = list(dict_name.items())
```

Copied!

Example:

```
1. 1

1. info = list(person.items())
```

Copied!

key existence You can check for the existence of a key in a dictionary using the `in` keyword

copy() Creates a shallow copy of the dictionary. The new dictionary contains the same key-value pairs as the original, but they remain distinct objects in memory.

keys() Retrieves all keys from the dictionary and converts them into a list. Useful for iterating or processing keys using list methods.

values() Extracts all values from the dictionary and converts them into a list. This list can be used for further processing or analysis.

items() Retrieves all key-value pairs as tuples and converts them into a list of tuples. Each tuple consists of a key and its corresponding value.

Sets

Package/Method	Description	Code Example
		Syntax:
		1. 1
		1. set_name.add(element)
add()	Elements can be added to a set using the <code>`add()`</code> method. Duplicates are automatically removed, as sets only store unique values.	Example:
		1. 1
		1. fruits.add("mango")
clear()	The <code>`clear()`</code> method removes all elements from the set, resulting in an empty set. It updates the set in-place.	Syntax:
		1. 1
		1. set_name.clear()

		<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. fruits.clear()</td></div></div>
		<div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. new_set = set_name.copy()</div></div>
copy()	The `copy()` method creates a shallow copy of the set. Any modifications to the copy won't affect the original set.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. new_fruits = fruits.copy()</div></div>
Defining Sets	A set is an unordered collection of unique elements. Sets are enclosed in curly braces `{}`. They are useful for storing distinct values and performing set operations.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>2. 2</div><div>1. empty_set = set() #Creating an Empty</div><div>2. Set fruits = {"apple", "banana", "orange"}</div></div>
		<div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. set_name.discard(element)</div></div>
discard()	Use the `discard()` method to remove a specific element from the set. Ignores if the element is not found.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. fruits.discard("apple")</div></div>
		<div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. is_subset = set1.issubset(set2)</div></div>
issubset()	The `issubset()` method checks if the current set is a subset of another set. It returns True if all elements of the current set are present in the other set, otherwise False.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. is_subset = fruits.issubset(colors)</div></div>
		<div>Copied!</div> <div>Syntax:</div> <div><div>is_superset = set1.issuperset(set2)</div></div>
issuperset()	The `issuperset()` method checks if the current set is a superset of another set. It returns True if all elements of the other set are present in the current set, otherwise False.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. is_superset = colors.issuperset(fruits)</div></div>
		<div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. removed_element = set_name.pop()</div></div>
pop()	The `pop()` method removes and returns an arbitrary element from the set. It raises a `KeyError` if the set is empty. Use this method to remove elements when the order doesn't matter.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. removed_fruit = fruits.pop()</div></div>
		<div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. set_name.remove(element)</div></div>
remove()	Use the `remove()` method to remove a specific element from the set. Raises a `KeyError` if the element is not found.	<div>Copied!</div>

Set Operations Perform various operations on sets: `union`, `intersection`, `difference`, `symmetric difference` .

update() The `update()` method adds elements from another iterable into the set. It maintains the uniqueness of elements.



© IBM Corporation. All rights reserved.

Example:

```
1. 1
1. fruits.remove("banana")
```

Copied!

Syntax:

```
1. 1
2. 2
3. 3
4. 4

1. union_set = set1.union(set2)
2. intersection_set = set1.intersection(set2)
3. difference_set = set1.difference(set2)
4. sym_diff_set = set1.symmetric_difference(set2)
```

Copied!

Example:

```
1. 1
2. 2
3. 3
4. 4

1. combined = fruits.union(colors)
2. common = fruits.intersection(colors)
3. unique_to_fruits = fruits.difference(colors)
4. sym_diff = fruits.symmetric_difference(colors)
```

Copied!

Syntax:

```
1. 1
1. set_name.update(iterable)
```

Copied!

Example:

```
1. 1
1. fruits.update(["kiwi", "grape"])
```

Copied!