UPTOSKILLS INTERNSHIP-2026

Intern Name: Nitesh Sharma

Course: MCA

Enrollment NO. : 25MCAN0280

Internship Duration: 3 Months

Start Date: 13 Jan 2026

End Date: 13 Apr 2026

Interview Date: 10 Jan 2026

Offer Latter Date: 13 Jan 2026

Reporting Manager: Shivam Agarwal

Project Handler: Chandan Nayak

Assistant Project Handler: Vanshika Jadaun

Project Name: Cyber Security


UPTOSKILLS INTERNSHIP-2026

Task-1: Install Kali Linux & Burp-Suite Pro

Date of Allotment: 15 Jan 2026


Date of Completion: 17 Jan2026

1. Download VMware Workstation: https://www.vmware.com/products/desktop-hypervisor/workstation-and-fusion
2. Download Kali ISO Image file: **https://www.kali.org**




VMware Workstation PRO Home Screen:- Create Virtual Machine For kali

Click on Create a New Virtual Machine



Setup Virtual Machine Wizard


Select: **Typical(recommended)**



In Installer disk image file: **Browse Kali ISO image file**


GO: **NEXT**

UPTOSKILLS INTERNSHIP-2026




Setup Machine name: **KALI 2025-4**

Go : **NEXT**




Give ROM: 80GB Go: **NEXT**



Allocate Hardware Requirements:


RAM: 8GB, Processor: 4,

Click: **Close**




Check All Information & confirm that

Click on **Finish**




Start Kali Machine & Select **Graphical Install**




Select a Language: Bydefault Select (English-English),

Click **Continue**




Select Your Location: Select (india) If you Belongs to


Click **Continue**



Configure the Keyboard: By default (American English)


Click **Continue**






Give Hostname: cyber(Choose any)


Click **Continue**



Click **Continue**




Click **continue**




Set-up Username of account: kali


Click **Continue**



Setup Password for Linux: ****


Click **Continue**







Partition Disks: Guided entire disk (By default Selected)


Click **Continue**






Click Continue






Write the changes to disks: Select **Yes**


Click **Continue**







Click **Continue** & Install Xfce (Default desktop environment)

For easy to use required less memory.










Install GRUB Boot loader Select **YES,** Click **Continue**

Its help to chouse OS, its firstly start when system is ON, its helps to start OS.




Select **/dev/sda** for using store OS or data.






After installation system need reboot than click **Continue**




Finally Kali look like after installation.

UPTOSKILLS INTERNSHIP-2026




Now we have to need update all packages.


Using **sudo apt update**




Upgrade all packages using **sudo apt upgrade**

UPTOSKILLS INTERNSHIP-2026





3. **Install Burp-Suite Pro :-**



In kali Linux's Browser(Firefox) search "Burp-suite Professional git hub".

Copy link address.


Open terminal change directory **cd /opt** &

" git clone <Paste copied Link>" + Enter download Burp-suite Pro


Give executable permission using command **chmod +x install.sh**

And start installation using command **./install.sh**


UPTOSKILLS INTERNSHIP-2026




Edit license text “licensed to root” & setup for root user...




UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026




All process same just edit License text “licensed to kali” for normal user .




UPTOSKILLS INTERNSHIP-2026






UPTOSKILLS INTERNSHIP-2026




Add Foxy-Proxy extension on browser Click **options** than **Proxies**

And **add** Enter Details in Hostname= 127.0.0.1 & Port= 8080


In Title = Burp and last **Save**






In search bar “http://burpsuite” + Enter and download CA certificate


Gor capturing web requests.



in Browser’s Setting find certificate and CA certificate Import in it.

UPTOSKILLS INTERNSHIP-2026





Now successfully burp-suite Pro and CA certificate Configuration Process Completed.

Conclusion:-

The successful installation of Kali Linux and Burp Suite Pro ensured a fully functional penetration testing environment. This task improved practical skills in tool setup, system configuration, and understanding real-world cybersecurity testing requirements.

UPTOSKILLS INTERNSHIP-2026


Task: 2 => SQL Injection (Flipkart)

Date Of Allotment: 16 Jan 2026

Date of Completion: 20 Jan 2026


Objective :-

The objective of this task is to understand and analyze SQL Injection vulnerabilities in a web application by performing controlled security testing. This assessment aims to identify improper input validation and insecure database interaction that could lead to unauthorized access or data leakage, and to recommend appropriate mitigation measures.




Flipkart is Task Project where try to some SQL Injection.

UPTOSKILLS INTERNSHIP-2026




Successfully Captured a GET request using Burp-Suite.



The captured GET request parameter was tested for SQL Injection using Burp Suite Repeater by manipulating input values. **1-- -** (Comment based), **--** after all think are ignore by the sql.


Result: The server returned a *400 Bad Request* response, indicating proper input validation and no SQL Injection vulnerability was observed.

UPTOSKILLS INTERNSHIP-2026



SQL Injection payload **‘ OR '1'='1** was manually injected into a GET request parameter using Burp Suite Repeater.

Result: The application responded with *400 Bad Request*, indicating effective server-side input validation and no SQL Injection vulnerability detected.



A SQL Injection payload was injected into a JSON-based POST parameter using Burp Suite Repeater during authorized security testing.

Result: The server returned a *400 Bad Request* response, confirming proper input validation and no SQL Injection vulnerability was identified.

Conclusion:-

SQL Injection testing was conducted on identified GET and POST parameters using Burp Suite in an authorized testing environment. Multiple payloads, including Boolean-based (OR 1=1) and string-based(‘ OR ‘1’=’1) injections, were tested.

All tested inputs were properly validated by the server, resulting in controlled responses such as *400 Bad Request*.

No SQL Injection vulnerability was detected, indicating effective input validation and secure backend implementation.


UPTOSKILLS INTERNSHIP-2026


Task: 3 => Port Swigger Lab

Date Of Allotment: 21 JAN 2026


Date Of Completion: 2 FEB 2026


SQL LAB: -







UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026






UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026


Cross Site Scripting(XSS):-







UPTOSKILLS INTERNSHIP-2026






UPTOSKILLS INTERNSHIP-2026







Conclusion:-

During the testing phase, a basic XSS payload

<script>alert(1)</script> , "><svg onload=alert(1)> ,


<img src=1 onerror=alert(1)> , javascript:alert(document.cookie) ,


<iframe src="https://YOUR-LAB-ID.web-security-academy.net/#" onload="this.src+='<img src=x onerror=print()>'"></iframe>

was injected into the vulnerable input field. The successful execution of the script confirmed the presence of a Cross-Site Scripting vulnerability.


UPTOSKILLS INTERNSHIP-2026


Cross-site request forgery (CSRF):-







UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026






UPTOSKILLS INTERNSHIP-2026









Conclusion:-

This lab demonstrated a Cross-Site Request Forgery (CSRF) vulnerability where unauthorized actions were performed using a victim's active session. The application failed to verify the authenticity of user requests. This allowed an attacker to execute malicious requests without the user's knowledge. The lab emphasizes the need for proper CSRF tokens and request validation to prevent such attacks.


UPTOSKILLS INTERNSHIP-2026


Server- Side Request Forgery(SSRF):-







UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026









Conclusion:-

In this lab, I identified and exploited a Server-Side Request Forgery (SSRF) vulnerability in the application.


The server was making backend requests based on user-controlled input without proper validation.


By manipulating the request, I was able to access internal resources that were not intended to be publicly reachable.

This lab highlights the risk of SSRF and the need for strict input validation and restricted server-side network access.


UPTOSKILLS INTERNSHIP-2026


Access Control Vulnerabilities (IDOR) :-






UPTOSKILLS INTERNSHIP-2026









Conclusion:-

In this task, I identified access control vulnerabilities where authorization checks were not properly enforced.
I was able to access restricted functions or data by manipulating user roles or request parameters.
This showed that the application failed to ensure users could only perform actions permitted to their privileges.
The lab highlights the importance of proper authorization checks on the server side to prevent unauthorized access.


UPTOSKILLS INTERNSHIP-2026


Business Logic:-






UPTOSKILLS INTERNSHIP-2026









Conclusion:-

In this task, I identified a **business logic vulnerability** in the application.
By manipulating the product quantity, I was able to place an order with a total cost of **₹0**.
I also reused the same coupon code multiple times to continuously reduce the product price.
This lab highlights how improper validation of business rules can lead to financial loss and abuse of discounts.


UPTOSKILLS INTERNSHIP-2026


Path Traversal, IDOR:-







UPTOSKILLS INTERNSHIP-2026







UPTOSKILLS INTERNSHIP-2026






UPTOSKILLS INTERNSHIP-2026







Conclusion:-

In this task, I identified **Path Traversal and IDOR vulnerabilities** in the application.

By manipulating the image file path, I was able to access sensitive system files.

This allowed me to retrieve the **password file list**, which should not be accessible to users.

The lab highlights the importance of proper access control and secure file path validation.


Leave From	Leave To	Reason
19 Jan 2026	19 Jan 2026	Fever
28 Jan 2026	31 Jan 2026	Job assessment

UPTOSKILLS INTERNSHIP-2026


Task = NMAP (UpToSkills)

Date Of Allotment: 3 Feb 2026

Date of Completion: 10 Feb 2026




Gather Information about UpToSkills like(Domain Name, Register_ID,etc.)




Before Scanning send ping packets for checking host is up or not

ping -v uptoskills.com with the help to this command get IP Address of target.

UPTOSKILLS INTERNSHIP-2026




Get 19 sub-domain.




On target website try no-ping scan using NMAP

nmap -v 172.67.211.113 -Pn for trying to using for bypass firewall. And find 4 open ports 80,443,8080,8443.


UPTOSKILLS INTERNSHIP-2026






OS detection commands try which help to get info about OS


Nmap -O 172.67.211.113 -v -Pn Getting full details also using verbose flag.






Aggressive scan using **nmap -A -v -Pn 172.67.211.113**


UPTOSKILLS INTERNSHIP-2026




Syn, and version detection using nmap

Nmap -Pn -sS 172.67.211.113, nmap -Pn -sV 172.67.211.113 but high security so no detect version






Nmap --script vuln 172.67.211.113 this command using for vulnerability check





UPTOSKILLS INTERNSHIP-2026

Nmap 172.67.211.113 -v -D RND:10 this is decoy scan and attack to 10 random ip for help to beware with firewall.





Nmap 172.67.211.113 -v -source -port 80 data-length 24, this command using for firewall bypass & trying to manipulate target.





UPTOSKILLS INTERNSHIP-2026





Nmap -p 80 --script=http* 172.67.211.113 -v , this command using for run script on particular port no-80 and http* working all http script run and test all types of vulnerabilities.

Conclusion:-

During the Nmap scan, http* scripts were used to identify web services and potential vulnerabilities.
The -v and -Pn options improved scan visibility and allowed host discovery to be bypassed for accurate results.
The -O and -A flags successfully identified the target operating system, running services, and their versions.
The -D decoy technique helped make the scan more stealthy by masking the real scanning source.


UPTOSKILLS INTERNSHIP-2026

Task = NetCat (UpToSkills)

Date Of Allotment: 11 Feb 2026


Date of Completion: 18 Feb 2026

Netcat is a versatile command-line utility for reading and writing data across network connections using TCP or UDP protocols, acting as a "Swiss Army knife" for network tasks like port scanning, file transfers, debugging, and creating simple network listeners or backdoors, often used by system administrators and security professionals.




First I used “nc -h” command for the options I can used with netcat.

IP address of target website and selected IP=172.67.211.113



We can use netcat for communication between two system one system has to listen on port eg:-4545 and other has to send request to same port. For this we use command “nc -lvnp 4444”.

Then I performed TCP port scan to cheack ports.



After TCP I performed a UDP scan using -u.


UPTOSKILLS INTERNSHIP-2026

Task = Burp-Suite (UpToSkills)


Date Of Allotment: 18 Feb 2026

Date of Completion: 20 Feb 2026


Burp Suite is a web application security testing tool that intercepts, inspects, and modifies HTTP requests and responses to identify vulnerabilities like SQL injection and XSS during penetration testing activities.



UPTOSKILLS INTERNSHIP-2026




During website inspection, the search bar was found to have identical background and text colors (black), which negatively impacts readability and user experience.




The screenshot shows the HTTP History section of Burp Suite Community Edition, where multiple HTTP and HTTPS requests captured through the proxy are visible. It includes details such as host, request method (GET/POST), URL endpoints, status codes (200, 401, 403), MIME types, and response lengths. This indicates that traffic interception was successfully configured, allowing analysis of client–server communication during website interaction.

UPTOSKILLS INTERNSHIP-2026



An API key was identified within the client-side JavaScript file. Client-side exposure of API keys is a security concern, as attackers may extract and misuse the key for unauthorized API access, leading to data leakage or service abuse.



While attempting to place an order through the payment option, the system displayed an error message stating ‘Failed to create order. Please try again.’ This indicates a failure in the order creation or payment initiation process

This issue prevents users from successfully completing transactions, negatively affecting user experience and business operations

UPTOSKILLS INTERNSHIP-2026

Task = Wapiti3 (UpToSkills)

Date Of Allotment: 20 Feb 2026

Date of Completion: 26 Feb 2026

Wapiti3 tool is a web vulnerability scanner. It is used to find security flaws in web applications/websites.

- SQL Injection
- Cross Site Scripting
- File Inclusion(LFI/RFI)
- Command Execution
- Directory Traversal
- Weak Credential


Wapiti3 -h :- (Help command) command use for showing for all flags.

Wapiti3 -version :- use for show version (3.2.10)




Wapiti –list-modules :- this command use for show vulnerability module list.

UPTOSKILLS INTERNSHIP-2026




Wapiti -u https://uptoskills.com/ --verify-ssl 0 :- this command using for verifying ssl.




UPTOSKILLS INTERNSHIP-2026


Wapiti -u https://uptoskills.com/ -m sql,xss :- this command use for specific vulnerability check of SQL and XSS.



Wapiti -u https://uptoskills.com/ --max-scan-time 5 :- this command check vulnerability on target for 5 sec.



UPTOSKILLS INTERNSHIP-2026




```
Warning: you are using the root account. You may h
                                                    Vulnerable software :   0
*******************************************************************************

Content Security Policy Configuration
-------------------------------------
CSP "object-src" value is not safe for URL: https://uptoskills.com/
WSTG code: ['WSTG-CONF-12', 'OSHP-Content-Security-Policy']
Evil request:
    GET / HTTP/1.1
    host: uptoskills.com
    connection: keep-alive
    user-agent: Mozilla/5.0 (Windows NT 6.1; rv:45.0) Gecko/20100101 Firefox/45.0
    accept-language: en-US
    accept-encoding: gzip, deflate, br
    accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
cURL command PoC : "curl "https://uptoskills.com/""

                                  *   *   *

*******************************************************************************
```



```
/root/.wapiti/generated_report/wapiti.t
File  Edit  Search  View  Document  Help
Warning: you are using the root account. Y


*******************************************************************************

TLS/SSL misconfigurations
-------------------------
Certificate doesn't use Extended Validation
WSTG code: ['WSTG-CRYP-01']
Evil request:
    GET / HTTP/1.1
    host: uptoskills.com
    connection: keep-alive
    user-agent: Mozilla/5.0 (Windows NT 6.1; rv:45.0) Gecko/20100101 Firefox/45.0
    accept-language: en-US
    accept-encoding: gzip, deflate, br
    accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
cURL command PoC : "curl "https://uptoskills.com/""

                                  *   *   *

OCSP Must-Staple extension is missing
WSTG code: ['WSTG-CRYP-01']
Evil request:
    GET / HTTP/1.1
    host: uptoskills.com
    connection: keep-alive
    user-agent: Mozilla/5.0 (Windows NT 6.1; rv:45.0) Gecko/20100101 Firefox/45.0
    accept-language: en-US
    accept-encoding: gzip, deflate, br
    accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
cURL command PoC : "curl "https://uptoskills.com/""

                                  *   *   *
```



```
/root/.wapiti/generated_report/wapiti.txt - Mousepad
File  Edit  Search  View  Document  Help
Warning: you are using the root account. You may harm your system.
Evil request:
    GET / HTTP/1.1
    host: uptoskills.com
    connection: keep-alive
    user-agent: Mozilla/5.0 (Windows NT 6.1; rv:45.0) Gecko/20100101 Firefox/45.0
    accept-language: en-US
    accept-encoding: gzip, deflate, br
    accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
cURL command PoC : "curl "https://uptoskills.com/""

                  *   *   *

Server doesn't support secure renegotiations
WSTG code: ['WSTG-CRYP-01']
Evil request:
    GET / HTTP/1.1
    host: uptoskills.com
    connection: keep-alive
    user-agent: Mozilla/5.0 (Windows NT 6.1; rv:45.0) Gecko/20100101 Firefox/45.0
    accept-language: en-US
    accept-encoding: gzip, deflate, br
    accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
cURL command PoC : "curl "https://uptoskills.com/""

                  *   *   *

The following ciphers are acceptable for TLSv1.2: TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA, TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256, TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA, TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA384,
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA, TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256, TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA, TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384, TLS_RSA_WITH_AES_128_CBC_SHA,
TLS_RSA_WITH_AES_128_CBC_SHA256, TLS_RSA_WITH_AES_128_GCM_SHA256, TLS_RSA_WITH_AES_256_CBC_SHA, TLS_RSA_WITH_AES_256_CBC_SHA256, TLS_RSA_WITH_AES_256_GCM_SHA384
WSTG code: ['WSTG-CRYP-01']
Evil request:
    GET / HTTP/1.1
    host: uptoskills.com
    connection: keep-alive
    user-agent: Mozilla/5.0 (Windows NT 6.1; rv:45.0) Gecko/20100101 Firefox/45.0
    accept-language: en-US
    accept-encoding: gzip, deflate, br
    accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
cURL command PoC : "curl "https://uptoskills.com/""
```

UPTOSKILLS INTERNSHIP-2026

And finally got it some vulnerability in uptoskills 1 Content security policy configuration and 5 SSL/TLS Misconfiguration. **Below vulnerability Explanation.**

1. Certificate does not use Extended Validation (EV)

Vulnerability

The SSL certificate used by the website is not an **Extended Validation (EV)** certificate. This means the website does not provide strong identity verification to users.

Impact:

- Users cannot fully trust the website
- Phishing or fake websites can be created more easily
- Less assurance during sensitive activities like login or payment

Solution

- Use an **Extended Validation (EV) SSL certificate**
- Purchase certificates from a trusted Certificate Authority (CA)
- Regularly review and audit SSL certificates

2. OCSP Must-Staple Extension is Missing

Vulnerability

The SSL certificate does not have the **OCSP Must-Staple** extension enabled.
Because of this, the browser may not properly verify whether the certificate has been revoked.

Impact:

- Increases the risk of **Man-in-the-Middle (MITM) attacks**
- Revoked or compromised certificates may still be accepted

Solution

- Enable **OCSP Must-Staple** in the SSL certificate
- Configure OCSP stapling on the server
- Ensure certificates are renewed and monitored regularly

3. Server Vulnerable to OpenSSL CCS (CVE-2014-0224)

Vulnerability

The server is running a vulnerable version of **OpenSSL** that is affected by the **CCS Injection vulnerability (CVE-2014-0224)**.

Impact:

- Attackers can intercept encrypted communication
- Sensitive data such as usernames and passwords may be exposed

Solution

- Update OpenSSL to the **latest secure version**
- Disable outdated SSL/TLS protocols
- Apply security patches regularly

4. Support for Weak Cipher Suites

Vulnerability

The server supports **weak or outdated cipher suites**, which reduces encryption strength.

Impact:

- Encrypted data can be broken
- Secure communication can be compromised

Solution

- Disable weak cipher suites
- Allow only strong encryption algorithms such as:
    - AES-GCM
    - ECDHE-based cipher suites
- Enable only **TLS 1.2 and TLS 1.3**

UPTOSKILLS INTERNSHIP-2026

Task = theHarvester (UpToSkills)


Date Of Allotment: 26 Feb 2026

Date of Completion: 4 Mar 2026

theHarvester is an OSINT(Open Source INTelligence) reconnaissance tool that collects information from public sources without directly attacking the target.


What is collect:-

- E-mails
- Subdomains
- Hosts/IPs
- Employee Names etc....




Firstly starting theHarvester with help command **theHarvester -h** with the help of this command I learn about all flags and some important commands.

UPTOSKILLS INTERNSHIP-2026





theHarvester -d uptoskills.com -b bing, **theHarvester -d uptoskills.com -b Shodan** I tried some commands but they are not working with theHarvester and in result show me not supported or invalid source.




UPTOSKILLS INTERNSHIP-2026


theHarvester -d uptoskills.com -b all -f report finally I tried all command which is help for get information about subdomains, emails, and hosts&IPs. And Harvested some information given Bellow.






UPTOSKILLS INTERNSHIP-2026







Conclusion:-

TheHarvester collected a lot of useful public information about the target domain. It found several subdomains, email addresses, IP addresses, and their connections. This helps understand the company's servers, mail systems, and web services. Overall, it is very helpful during the reconnaissance stage of penetration testing.


UPTOSKILLS INTERNSHIP-2026

Task = Masscan(1.3.2) (UpToSkills)


Date Of Allotment: 05 Mar 2026

Date of Completion: 12 Mar 2026


Masscan is an open-source TCP port scanner that scans IP addresses and ports very quickly to identify which ports are open on a system.




Masscan 172.67.211.113 -p80 scan single port and it discovered open port.




Masscan 172.67.211.113 -p22,443 scan dual port and Discovered open port 443



Masscan 172.67.211.113 -p1-1000 --rate=1000 scan ports 1 to 1000 and send 1000 packets each time and it discovered two open port 80/443.



Masscan 172.67.211.113 -p1-65535 --rate=1000 scan ports 1 to 65535 and send 1000 packets each time.



Masscan 172.67.211.113 -p1-65535 --rate=500 --open scan port 1 to 65535 each time send 500 data packets and find open port(2082,2087,443).

Conclusion:-

After using different **Masscan commands**, we successfully scanned target systems and networks to identify open ports quickly. Masscan proved to be a very fast and efficient port scanning tool, useful in the reconnaissance phase of penetration testing to discover potential entry points in a network.


UPTOSKILLS INTERNSHIP-2026

Task = FFUF (UpToSkills)

Date Of Allotment: 13 Mar 2026

Date of Completion: 19 Mar 2026


FFUF is a powerful and fast web fuzzing tool used in penetration testing to discover hidden directories, files, parameters, and credentials. By using wordlists like rockyou.txt, it automates testing and improves efficiency. With proper filtering options and techniques, FFUF helps identify vulnerabilities accurately, making it an essential tool for ethical hackers and bug bounty hunters.




At first start with **ffuf -h** command which is help to guide about the tool. And how to use it.

UPTOSKILLS INTERNSHIP-2026

Directory fuzzing:-




UPTOSKILLS INTERNSHIP-2026



ffuf -u https://uptoskills.com/FUZZ /usr/share/wordlists/dirb/common.txt FUZZ is replaced with words from common.txt

- I found many **hidden directories/files**, like:
    - .git, .ssh, .history, .bashrc, .htaccess, _assets


UPTOSKILLS INTERNSHIP-2026



ffuf -u http://uptoskills.com/login -X POST -d "username=admin&password=FUZZ" -w /usr/share/wordlists/rockyou.txt -mc 200

I am trying brute-forcing login using FFUF, Tool is working correctly, But result is incomplete and unclear, No confirmed password found yet.


UPTOSKILLS INTERNSHIP-2026



ffuf -u http://uptoskills.com/login -X POST -d "username=admin&password=FUZZ" -w /usr/share/wordlists/rockyou.txt -fc 401

You are trying to **guess admin password**, Using rockyou.txt wordlist, FUZZ = password field, -fc 401 = **hide all 401 (unauthorized) responses**

UPTOSKILLS INTERNSHIP-2026




ffuf -u http://uptoskills.com/page.php?user=FUZZ -w /usr/share/wordlists/rockyou.txt

I am testing a **URL parameter (user),**FFUF is replacing FUZZ with values from rockyou.txt .

Trying to find:

- valid usernames
- hidden behavior
- possible vulnerabilities

UPTOSKILLS INTERNSHIP-2026



ffuf -u http://FUZZ.uptoskills.com -w /usr/share/wordlists/dirb/common.txt

I am trying **subdomain fuzzing**


FUZZ will be replaced with words like:

- admin
- test
- dev

Target becomes:

- admin.uptoskills.com
- test.uptoskills.com

UPTOSKILLS INTERNSHIP-2026



ffuf -u http://uptoskills.com/login -X POST -d "username=admin&password=FUZZ" -w /usr/share/wordlists/dirb/common.txt -rate 5


I am trying **login password testing**

Username = admin

Passwords = from common.txt (small list)

-rate 5 = slow speed (5 requests per second)

UPTOSKILLS INTERNSHIP-2026




ffuf -u http://uptoskills.com -H "User-Agent: FUZZ" -w /usr/share/wordlists/rockyou.txt

I am testing **User-Agent header fuzzing,**FUZZ is replaced with values from rockyou.txt and

Trying different **browser identities .**

UPTOSKILLS INTERNSHIP-2026



ffuf -u http://uptoskills.com/api/login -X POST -H "Content-Type: application/json" -d '{"username":"admin","password":"FUZZ"}' -w /usr/share/wordlists/rockyou.txt

I am testing **API login (JSON request),** Username = admin,Passwords = from rockyou.txt

Sending data in **JSON format.**

Conclusion:-

FFUF is a powerful tool for testing logins, APIs, parameters, and directories using wordlists. In these tests, most responses were identical, indicating no successful findings and many false positives. Proper filtering (status, size, words) and correct wordlists are essential to identify real results and detect vulnerabilities accurately during penetration testing.


UPTOSKILLS INTERNSHIP-2026


Task = SQLMap (UpToSkills)

Date Of Allotment: 20 Mar 2026

Date of Completion: 22 Mar 2026

SQLmap is an open-source **penetration testing tool** used to detect and exploit **SQL injection vulnerabilities** in web applications.





UPTOSKILLS INTERNSHIP-2026

The **sqlmap -h** command is essential for beginners to understand all functionalities of SQLMap. It provides a complete overview of how to perform SQL Injection testing and customize attacks effectively.




sqlmap -u http://uptoskills.com/api/auth/login --data="username=test&password=test"

This command is used to test **SQL Injection on a login API (POST request)**.

- -u → Target URL (login endpoint)
- --data → Sends POST data (username & password)
- SQLMap treats this as a **POST request instead of GET**
- It tries different SQL Injection techniques on:
    - username
    - password

UPTOSKILLS INTERNSHIP-2026




sqlmap -u "https://uptoskills.com/page?id=1"

This command tests a **GET parameter (id)** for SQL Injection.

- -u → Target URL
- ?id=1 → Input parameter to test
- SQLMap automatically:
    - Checks if parameter is dynamic
    - Tries multiple SQL Injection techniques:
        - Boolean-based
        - Error-based
        - Time-based
        - UNION-based

The test shows that the id parameter is not vulnerable to SQL Injection. The server also uses security mechanisms (like WAF), which block repeated requests and may affect testing results.

UPTOSKILLS INTERNSHIP-2026




sqlmap -u "https://uptoskills.com/page?id=1" –dbs

This command is used to **extract database names** from the target if it is vulnerable to SQL Injection.

- -u → Target URL with GET parameter
- --dbs → Enumerates (lists) all available databases
- SQLMap first checks:
    - Whether parameter is injectable
    - Then tries multiple SQL Injection techniques
- If vulnerability is found → it fetches database names

The attempt to extract databases failed because the target parameter is not vulnerable to SQL Injection. Security protections on the server also restrict testing, preventing further enumeration.

UPTOSKILLS INTERNSHIP-2026



sqlmap -u "https://uptoskills.com/page?id=1" --dbs --level=5 --risk=3 --random-agent

This command performs **advanced SQL Injection testing and database enumeration**.


- -u → Target URL with GET parameter
- --dbs → Attempt to extract database names
- --level=5 → Maximum testing depth (more payloads)
- --risk=3 → High-risk tests (more aggressive techniques)
- --random-agent → Uses random User-Agent to bypass basic security

SQLMap tries multiple advanced techniques like:

- Boolean-based
- Error-based
- Time-based
- UNION-based

Even with advanced settings, no SQL Injection vulnerability was found. This indicates that the target is either secure or protected by strong filtering mechanisms, preventing successful database enumeration.

UPTOSKILLS INTERNSHIP-2026




sqlmap -u "http://uptoskills.com/api/auth/login" --data="username=test&password=test"

This command is used to test **SQL Injection on a login API using POST request**.

- -u → Target login URL
- --data → Sends POST parameters (username & password)
- SQLMap tests both parameters for injection using:
    - Boolean-based
    - Error-based
    - Time-based
    - UNION-based techniques

The login API is not vulnerable to SQL Injection. Both parameters are non-dynamic, and security mechanisms prevent successful injection attempts.

UPTOSKILLS INTERNSHIP-2026



sqlmap -u "http://uptoskills.com" --crawl=2 --threads=5 –batch

This command is used to **automatically crawl the website and find injectable URLs**.


- -u → Target website
- --crawl=2 → Crawl website up to depth level 2
- --threads=5 → Use 5 threads (faster scanning)
- --batch → Auto-confirm all prompts

SQLMap scans pages and looks for:

- URLs with parameters (?id=1)
- Possible injection points

The crawling process did not find any usable URLs with parameters, so SQL Injection testing could not proceed. This indicates either the site does not expose parameters or uses modern routing methods.

UPTOSKILLS INTERNSHIP-2026



sqlmap -u "https://www.studylms.uptoskills.com" --crawl=2 --threads=5 --batch --banner

sqlmap -u "https://www.studylms.uptoskills.com" --forms --crawl=2 --batch --level=2


These commands are used to **crawl the website and detect SQL Injection points including forms**.

- --crawl=2 → Crawl website up to depth 2
- --threads=5 → Faster scanning using multiple threads
- --batch → Auto-confirm prompts
- --banner → Try to fetch database banner
- --forms → Detect and test input forms
- --level=2 → Moderate testing level

SQLMap tries to:

- Find URLs with parameters
- Detect forms (login/search)
- Test them for SQL Injection

The scan failed due to SSL connection issues and absence of usable parameters or forms. As a result, SQLMap could not perform SQL Injection testing on the target.



sqlmap -u "https://www.studylms.uptoskills.com" --crawl=2 --level=3 --risk=2 --random-agent --batch

sqlmap -u "https://www.studylms.uptoskills.com" --crawl=2 --tamper=space2comment,between --random-agent --batch


These commands perform **advanced crawling and injection testing with evasion techniques**.

- --crawl=2 → Crawl website up to depth 2
- --level=3 → Medium-deep testing
- --risk=2 → Moderate risk payloads
- --random-agent → Random User-Agent to bypass filters
- --tamper → Modify payloads to bypass WAF
    - space2comment → replaces spaces with comments
    - between → alters SQL queries

SQLMap attempts to:

- Discover injectable URLs
- Bypass security filters
- Perform injection testing

Even with advanced evasion techniques, the scan failed due to SSL connection issues and absence of injectable parameters. Therefore, no SQL Injection vulnerability could be tested or identified.



sqlmap -u "https://cpcalendars.uptoskills.com" --batch --banner --random-agent

sqlmap -u "https://cpcalendars.uptoskills.com" --crawl=3 --threads=5 --batch --level=3

These commands are used to:

- Test the target for **SQL Injection**
- Extract **database banner information**

- Perform **deep crawling (depth 3)** to find parameters
- --banner → Fetch database version info
- --crawl=3 → Deep crawling
- --threads=5 → Faster scanning
- --level=3 → Moderate testing depth
- --random-agent → Avoid detection

The scan failed because the target host does not exist or is not reachable. Even after attempting crawling, no usable links or parameters were found, so SQL Injection testing could not be performed.

Conclusion:-

SQLMap testing was performed on multiple endpoints using GET, POST, crawling, and advanced options. Most parameters were non-dynamic or non-injectable, while several requests were blocked by WAF (403 errors). Some targets had DNS or SSL issues. No usable links or forms were found. Overall, no SQL Injection vulnerability was detected, indicating secure configuration or strong protection mechanisms.

UPTOSKILLS INTERNSHIP-2026

Task = Metasploit (UpToSkills)

Date Of Allotment: 23 Mar 2026

Date of Completion: 30 Mar 2026


Metasploit Framework is a popular open-source tool used in cybersecurity for **penetration testing and ethical hacking**. It helps security professionals find and exploit vulnerabilities in systems, networks, and applications. It contains a large database of **exploits (known vulnerabilities)**, **payloads (malicious code like reverse shells)**, and tools for testing security.

How it works:


Metasploit follows a simple process—first, you gather information about the target, then choose an appropriate exploit based on a vulnerability, attach a payload, and execute it on the target system. If successful, it gives access (like a command shell or control over the system).

What it can do:

It can scan for vulnerabilities, exploit systems, maintain access, and generate reports. It is widely used by security experts to **test defenses and improve system security**, not for illegal hacking.



UPTOSKILLS INTERNSHIP-2026



 I opened the terminal in **Kali Linux** and typed the command **msfconsole**.

 This command starts the **Metasploit Framework**.

 After running it, Metasploit loaded successfully and showed:

- Version info (v6.4.116-dev)
- Number of **exploits, payloads, encoders, etc.**


 I used the command **help**, which displayed all available commands in Metasploit (like connect, set, sessions, etc.).

UPTOSKILLS INTERNSHIP-2026




- I typed the command **banner** inside **Metasploit Framework**.
- This command displays a **random ASCII art banner**.
- In my case, it shows a **duck with "HONK" text** 🦆.
- Below that, Metasploit shows:
  - Version: **v6.4.116-dev**
  - Number of modules:
    - Exploits: 2,623
    - Auxiliary: 1,326
    - Payloads: 1,710
    - Encoders, nops, evasion tools

UPTOSKILLS INTERNSHIP-2026



- I am using **Metasploit Framework** inside **Kali Linux**.
- I selected the module:
  auxiliary/scanner/portscan/tcp → used for **TCP port scanning**.
- Then I ran:
  - show options → to see required settings
  - set RHOSTS 172.67.211.113 → target IP set
  - set PORTS 1-1000 (correct command)
  - run → started scanning

UPTOSKILLS INTERNSHIP-2026




- I am using **Metasploit Framework** in **Kali Linux**.

- i selected the module:
auxiliary/scanner/ftp/ftp_version → used to check **FTP service version**.

- Then i ran:

  - set RHOSTS 172.67.211.113 → set target IP
  - run → executed the scan



 I am using **Metasploit Framework** in **Kali Linux**.

 I selected the module:
auxiliary/scanner/http/http_version → used to detect **web server (HTTP) version**.

 Then you ran:

- set RHOSTS 172.67.211.113 → set target IP
- run → executed the scan

403 Forbidden means:

- Access is **blocked or restricted**
- Server is not allowing your request

Some targets use **security layers (WAF/CDN)** to hide real server details

Direct scanning may not reveal full information

Conclusion:-

I successfully explored the basics of **Metasploit Framework** in **Kali Linux**. I learned how to start Metasploit (msfconsole), use commands like help and banner, and understand its interface. I performed different scanning techniques such as TCP port scanning, FTP version detection, and HTTP version scanning.

UPTOSKILLS INTERNSHIP-2026


Task = HashCat

Date Of Allotment: 30 Mar 2026

Date of Completion: 6 Apr 2026

Hashcat is a tool that takes hashed passwords (like MD5, SHA1, etc.) and tries to find the original plaintext password using different attack methods.

ALGORITHM	CODE
MD5	0
SHA1	100
HMAC-SHA1	160
NTLM	1000
SHA256	1400
HMAC-SHA256	1450



UPTOSKILLS INTERNSHIP-2026

Hashcat --help

Device Types


- CPU / GPU → where cracking runs

Workload Profiles

- Low → slow, less system load
- High → fast, more power usage

Basic Examples


- Ready-made commands for different attacks




I am start hashcat with tryhackme lab “Crack the hash”.


There is many types of hash values MD4,MD5,SHA1,SHA256,NTLM.

UPTOSKILLS INTERNSHIP-2026






SHA1 hash stored in hash.h file and try to crack with rockyou.txt and try to getting result in result.txt.





And I try again with another type for MD5 dictionary attack with rockyou.txt

And I got flag **“easy”.**



And make work easy, all hashes stored in single file and using hashid for algorithm type.


[+] Skein-512(160)
Analyzing '1C8BFE8F801D79745C4631D09FFF36C82AA37FC4CCE4FC946683D7B336B63032'
[+] Snefru-256
[+] SHA-256
[+] RIPEMD-256
[+] Haval-256
[+] GOST R 34.11-94
[+] GOST CryptoPro S-Box
[+] SHA3-256
[+] Skein-256
[+] Skein-512(256)
Analyzing '$2y$12$Dwt1BZj6pcyc3Dy1FWZ5ieeUznr71EeNkJkUlypTsgbX1H68wsRom'
[+] Blowfish(OpenBSD)
[+] Woltlab Burning Board 4.x
[+] bcrypt
Analyzing '279412f945939ba78ce0758d3fd83daa'
[+] MD2
[+] MD5
[+] MD4
[+] Double MD5
[+] LM
[+] RIPEMD-128
[+] Haval-128
[+] Tiger-128
[+] Skein-256(128)
[+] Skein-512(128)
[+] Lotus Notes/Domino 5
[+] Skype
[+] Snefru-128
[+] NTLM
[+] Domain Cached Credentials
[+] Domain Cached Credentials 2
[+] DNSSEC(NSEC3)
[+] RAdmin v2.x
--End of file '/home/kali/Desktop/hash.h'--
(kali㉿cyber)-[~]
$


$2y$12$Dwt1BZj6pcyc3Dy1FWZ5ieeUznr71EeNkJkUlypTsgbX1H68wsRom
Answer format: ****
279412f945939ba78ce0758d3fd83daa
Search the hashcat examples page (https://hashcat.net/wiki/doku.php?id=example_hashes) for $2y$. This type of hash can take a very long time to crack, so either filter rockyou for four character words, or use a mask for four lower case alphabetical characters.

```
The wordlist or mask that you are using is too small.
This means that hashcat cannot use the full parallel power of your device(s).
Hashcat is expecting at least 16 base words but only got 6.2% of that.
Unless you supply more work, your cracking speed will drop.
For tips on supplying more work, see: https://hashcat.net/faq/morework


Approaching final keyspace - workload adjusted.

$2y$12$Dwt1BZj6pcyc3Dy1FWZ5ieeUznr71EeNkJkUlypTsgbX1H68wsRom:bleh

Session..........: hashcat
Status...........: Cracked
Hash.Mode........: 3200 (bcrypt $2*$, Blowfish (Unix))
Hash.Target......: $2y$12$Dwt1BZj6pcyc3Dy1FWZ5ieeUznr71EeNkJkUlypTsgbX ... 8wsRom
Time.Started.....: Mon Apr  6 01:58:25 2026, (1 sec)
Time.Estimated...: Mon Apr  6 01:58:26 2026, (0 secs)
Kernel.Feature...: Pure Kernel (password length 0-72 bytes)
Guess.Mask.......: bleh [4]
Guess.Queue......: 12/130857 (0.01%)
Speed.#01........:        4 H/s (1.99ms) @ Accel:4 Loops:32 Thr:1 Vec:1
Recovered........: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)
Progress.........: 1/1 (100.00%)
Rejected.........: 0/1 (0.00%)
Restore.Point....: 0/1 (0.00%)
Restore.Sub.#01..: Salt:0 Amplifier:0-1 Iteration:4064-4096
Candidate.Engine.: Device Generator
Candidates.#01...: bleh → bleh
Hardware.Mon.#01.: Util: 23%

Started: Mon Apr  6 01:58:17 2026
Stopped: Mon Apr  6 01:58:28 2026
```

In this hash CPU take much more time and become overheat. Than I sort password list according to given hint. And I got flag **“bleh” for algorithm bcrypt(3200).**



Perform all task and I got Correct Answer.

UPTOSKILLS INTERNSHIP-2026

```
┌──(kali㉿cyber)-[~]
└─$ hashid hash2
--File 'hash2'--
Analyzing 'F09EDCB1FCEFC6DFB23DC3505A882655FF77375ED8AA2D1C13F640FCCC2D0C85'
[+] Snefru-256
[+] SHA-256
[+] RIPEMD-256
[+] Haval-256
[+] GOST R 34.11-94
[+] GOST CryptoPro S-Box
[+] SHA3-256
[+] Skein-256
[+] Skein-512(256)
Analyzing '1DFECA0C002AE40B8619ECF94819CC1B'
[+] MD2
[+] MD5
[+] MD4
[+] Double MD5
[+] LM
[+] RIPEMD-128
[+] Haval-128
[+] Tiger-128
[+] Skein-256(128)
[+] Skein-512(128)
[+] Lotus Notes/Domino 5
[+] Skype
[+] Snefru-128
[+] NTLM
[+] Domain Cached Credentials
[+] Domain Cached Credentials 2
[+] DNSSEC(NSEC3)
[+] RAdmin v2.x
Analyzing '$6$aReallyHardSalt$6WKUTqzq.UQQmrm0p/T7MPpMbGNnzXPMAXi4bJMl9be.cfi3/qxIf.hsGpS41BqMhSrHVXgMpdjS6xeKZAs02'
[+] Unknown hash
Analyzing 'e5d8870e5bdd26602cab8dbe07a942c8669e56d6'
[+] SHA-1
[+] Double SHA-1
[+] RIPEMD-160
[+] Haval-160
[+] Tiger-160
[+] HAS-160
[+] LinkedIn
[+] Skein-256(160)
[+] Skein-512(160)
--End of file 'hash2'--
```

Than perform same task for “Task-2” tryhackme lab. Starting all hashes stored in single file and check hash formate.

UPTOSKILLS INTERNSHIP-2026

```
┌──(root㉿cyber)-[/home/kali]
└─# hashcat -m 1400 -a 0 F09EDCB1FCEFC6DFB23DC3505A882655FF77375ED8AA2D1C13F640FCCC2D0C85 /home/kali/Desktop/rockyou.txt
hashcat (v7.1.2) starting

OpenCL API (OpenCL 3.0 PoCL 6.0+debian  Linux, None+Asserts, RELOC, SPIR-V, LLVM 18.1.8, SLEEF, DISTRO, POCL_DEBUG) - Platform #1 [The pocl project]
====================================================================================================================================================

* Device #01: cpu-haswell-12th Gen Intel(R) Core(TM) i7-1255U, 2930/5861 MB (1024 MB allocatable), 4MCU

Minimum password length supported by kernel: 0
Maximum password length supported by kernel: 256

Hashes: 1 digests; 1 unique digests, 1 unique salts
Bitmaps: 16 bits, 65536 entries, 0x0000ffff mask, 262144 bytes, 5/13 rotates
Rules: 1

Optimizers applied:
* Zero-Byte
* Early-Skip
* Not-Salted
* Not-Iterated
* Single-Hash
* Single-Salt
* Raw-Hash

ATTENTION! Pure (unoptimized) backend kernels selected.
Pure kernels can crack longer passwords, but drastically reduce performance.
If you want to switch to optimized kernels, append -O to your commandline.
See the above message to find out about the exact limits.

Watchdog: Temperature abort trigger set to 90c

Host memory allocated for this attack: 513 MB (6261 MB free)

Dictionary cache hit:
* Filename..: /home/kali/Desktop/rockyou.txt
* Passwords.: 14344385
* Bytes.....: 139921507
* Keyspace..: 14344385

f09edcb1fcefc6dfb23dc3505a882655ff77375ed8aa2d1c13f640fccc2d0c85:paule

Session..........: hashcat
Status...........: Cracked
Hash.Mode........: 1400 (SHA2-256)
Hash.Target......: f09edcb1fcefc6dfb23dc3505a882655ff77375ed8aa2d1c13f ... 2d0c85
```

And I solve hash for algorithm SHA256(1400) and try “Rockyou.txt” Password list.

Successfully got correct answer **“paule”**

```
┌──(root㉿cyber)-[/home/kali]
└─# hashcat -m 1000 -a 0 1DFECA0C002AE40B8619ECF94819CC1B /home/kali/Desktop/rockyou.txt
hashcat (v7.1.2) starting

OpenCL API (OpenCL 3.0 PoCL 6.0+debian  Linux, None+Asserts, RELOC, SPIR-V, LLVM 18.1.8, SLEEF, DISTRO, POCL_DEBUG) - Platform #1 [The pocl project]
====================================================================================================================================================

* Device #01: cpu-haswell-12th Gen Intel(R) Core(TM) i7-1255U, 2930/5861 MB (1024 MB allocatable), 4MCU

Minimum password length supported by kernel: 0
Maximum password length supported by kernel: 256

Hashes: 1 digests; 1 unique digests, 1 unique salts
Bitmaps: 16 bits, 65536 entries, 0x0000ffff mask, 262144 bytes, 5/13 rotates
Rules: 1

Optimizers applied:
* Zero-Byte
* Early-Skip
* Not-Salted
* Not-Iterated
* Single-Hash
* Single-Salt
* Raw-Hash

ATTENTION! Pure (unoptimized) backend kernels selected.
Pure kernels can crack longer passwords, but drastically reduce performance.
If you want to switch to optimized kernels, append -O to your commandline.
See the above message to find out about the exact limits.

Watchdog: Temperature abort trigger set to 90c

Host memory allocated for this attack: 513 MB (5996 MB free)

Dictionary cache hit:
* Filename..: /home/kali/Desktop/rockyou.txt
* Passwords.: 14344385
* Bytes.....: 139921507
* Keyspace..: 14344385

1dfeca0c002ae40b8619ecf94819cc1b:n63umy8lkf4i

Session..........: hashcat
Status...........: Cracked
Hash.Mode........: 1000 (NTLM)
```

I solve hash for algorithm NTLM(1000) and try “Rockyou.txt” Password list.

Successfully got correct answer **“n63umy8lkf4i”.**

Conclusion:-

Finally I successfully used Hashcat to perform practical **password cracking** .

- I understood different **hash types** (MD5, MD4, HMAC-SHA1, bcrypt) and their numeric codes
- Used the correct **attack mode (-a 0, dictionary attack)**
- Applied a wordlist (**rockyou.txt**) to crack hashes
- Learned how to **analyze output and identify cracked passwords**

UPTOSKILLS INTERNSHIP-2026


Task = Nuclei

Date Of Allotment: 7 Apr 2026

Date of Completion: 14 Apr 2026


Nuclei is a fast and powerful **vulnerability scanning tool** used in cybersecurity to find security issues in websites, servers, and APIs.

- Nuclei uses **templates (YAML files)**
- Each template = one vulnerability check
- It sends requests to the target (website/IP)
- Then checks response for vulnerabilities




Nuclei tool start with set and download all templates and updated version.

UPTOSKILLS INTERNSHIP-2026




For trying all domain using subfinder tool and get all domains list and saved in Domain.txt file.




Starting all testing on target site:uptoskills.com & trying all possibilities.

UPTOSKILLS INTERNSHIP-2026



Now its testing on all domain.




Due to security no vulnerabilities show.

UPTOSKILLS INTERNSHIP-2026





With the help of nuclei finding high and critical securityflows but there is high security than we did not get vulnerability on target.



Trying to all domain testing and save output in Result.txt.


UPTOSKILLS INTERNSHIP-2026







Trying on rate limiting 10 using advanced method.

UPTOSKILLS INTERNSHIP-2026







Firstly I tried nuclei with assetfinder but that not pre install so that show error, than I install “sudo apt install assetfinder” that again try and due to security did’not find any security flow.




“amass enum -d uptoskills.com | httpx | nuclei” this command using for information gathering along with nuclei and help to find vulnerabilities at that poit. In this nuclei load 17 templates

UPTOSKILLS INTERNSHIP-2026









UPTOSKILLS INTERNSHIP-2026

In enumeration process scan all domains and tring to detect vulnerabilities and during the scanning process https://mautic.uptoskill.com/.env which high level vulnerabilities than I looed on this location . and download .env file




But at this point there is no any type type of API keys, or passwords. So at this time its looking safe.

UPTOSKILLS INTERNSHIP-2026




And robots.txt file also accessible and I am adding what type of content having in this file.




UPTOSKILLS INTERNSHIP-2026

Using naabu tool and scanning network but did not find result.



“nmap -p 80,443 uptoskills.com” scan with nuclei but also no results found.



“nmap -iL /Desktop/Domains.txt | nuclei “ nmap start for scanning the all subdomain (Domains.txt), -iL flag using for input List (Domains.txt) along with nuclei tool. But stay no result found.

- Tools list:- Subfinder
- Amass
- Assetfinder
- httpx
- gau
- Naabu
- Nmap

These tools use with nuclei which is help me for finding Subdomains + Network Scanning.

Conclusion:-

Nuclei is a fast, template-based vulnerability scanner that automates security testing of websites and systems. It helps identify common flaws efficiently, making it valuable for penetration testers, bug bounty hunters, and cybersecurity professionals.

learned Nuclei basics, important flags, and how to integrate it with other tools to build a complete reconnaissance and vulnerability scanning workflow. This knowledge helps you move from beginner to intermediate level in practical cybersecurity and bug bounty hunting.