ŀ	Here, we will discuss :
•	What an exception is and how it differs from a syntax error Anatomy of Error Some built in Exceptions
\	 What Is an Error in Python? An error is an action that is incorrect or inaccurate. Due to which the program fails to execute. The errors can be broadly classified into two types:
	 Syntax errors Logical errors (Exception)
	Syntax Exceptions multiples
•	Syntax Error: As the name suggests this error is caused by the wrong structure or syntax in the code. A syntax error is also known as a parsing error.
[4]:	<pre>Putting keywords in the wrong place. #Syntax Error print("syntax error") for i in range(10) print(i) File "<ipython-input-4-0368748bca5f>", line 3 for i in range(10)</ipython-input-4-0368748bca5f></pre>
ī	SyntaxError: invalid syntax The arrow indicates where the parser ran into the syntax error Logical errors (Exception):
• F	Even if code is syntactically correct, the error that occurs at the runtime is known as a Logical error or Exception. An event that occurs during the execution of programs that disrupt the flow of execution are called EXCEPTIONS. Runtime exceptions, generally a result of programming errors, such as: Indenting a block to the wrong level.
•	
[3]:	<pre>a = 10 b = 20 print("Addition:", a + c) NameError</pre>
1	3 b = 20> 4 print("Addition:", a + c) NameError: name 'c' is not defined Anatomy of an Exception: • An exception is an object derives from the BaseException class that contains information about an error.
	 Exception object contains: Error type (exception name) The state of the program when the error occurred An error message describes the error event.
	Line that raised the exception Traceback (most recent call last): File " <py: hell#0="">", line 1, in <module> a - 5/0 NameError: name 'a' is not defined</module></py:>
	Exception Descriptive message If the line that raised the exception belongs to a function, module is replaced by the name of the function. A traceback is basically a list detailing the function calls that were made before the exception was raised.
•	Default Exception Handing in Python: There are many different types of exceptions, and they are all raised in particular situations For every exception, a corresponding class is available and every exception is object to its corresponding class
•	Whenever an exception occurs, PVM will create the corresponding exception object and check for handling code. If handling code is not available, then interpreter terminates the program and prints exception info to the console exception Hierarchy:
	The BaseException class is the root class for all exception classes in python exception hierarchy The below image shows different built-in exceptions:
	Exception KeyboardInterrupt
	Attribute Error Error Name Error Stop OS Type Error Er
E	Base exception classes in Python : BaseException
	GeneratorExit KeyboardInterrupt SystemExit Exception
	BaseException - is the base class for all the built-in exceptions. We should not directly inherit this class to define any custom exception classes GeneratorExit - Python throws this exception when a coroutine or generator is closed.
•	KeyboardInterrupt - When a user hits the interrupt key such as Delete or Control+C, this error exception is raised. SystemExit - When the sys.exit() function is called, this exception is raised. Exception - is a base class for all built-in non-system-exiting exceptions and user-defined exceptions #keyboard Interrupt import time
	<pre>while True: print("Stop the kernel") time.sleep(5) Stop the kernel Stop the kernel Stop the kernel </pre>
:	<pre>"Time.sleep(5) KeyboardInterrupt: #GeneratorExit def sample(): arr = [1, 2, 3, 4, 5] for i in arr: yield i print("From Function: ", i) print("Reached the end!!!")</pre>
	<pre>for num in sample(): print("Output: ", num) if(num >= 3): break print("Generatorexit is called") #so the print statements after last yield is not excuted - it is not an error. Output: 1 From Function: 1 Reached the end!!!</pre>
T	Output: 2 From Function: 2 Reached the end!!! Output: 3 Generatorexit is called TO DO: Excute a function with sys.exit() Arithmetic Error classes in Python:
	Exception Exception ArithmeticError
•	OverflowError FloatingPointError ZeroDivisionError ArithmeticError - is the base exception class for arithmetic errors such as
• F	FloatingPointError, ZeroDivisionError, and OverflowError. FloatingPointError - you can catch this exception when the operation of a floating-point value fails. However, this exception is always defined and handled internally ZeroDivisionError -happens when second argument of the division or modulo operation equals zero.
[14]:	OverflowError - this exception happens when the results from an arithmetic operation are out of range and also if integers are out of a required range. #Zero Division Error print(10/0) ZeroDivisionError Traceback (most recent call last) <ipython-input-14-f76ff30294c8> in <module> 1 #Zero Division Error</module></ipython-input-14-f76ff30294c8>
[13]:	> 2 print(10/0) ZeroDivisionError: division by zero #Simple program for showing overflow error import math print(math.exp(1000)) OverflowError Traceback (most recent call last) <ipython-input-13-872eldaed7c7> in <module></module></ipython-input-13-872eldaed7c7>
	1 #Simple program for showing overflow error 2 import math> 3 print(math.exp(1000)) OverflowError: math range error Lookup Error classes in Python:
	Exception LookupError
	IndexError KeyError
v •	LookupError - Base class for IndexError and KeyError exceptionswhich are raised when we try to manipulate non-existing or invalid index or key values at sequence or mapping. IndexError - exception happens when a referenced sequence is out of range KeyError - We can catch this exception if a mapping key not found in the set of existing keys. #IndexError
	<pre>num = [1, 2, 6, 5] num[5] IndexError</pre>
	<pre>#KeyError students = {"Sirisha": 15, "Vinay": 30} students["Nitheesh"] KeyError</pre>
C	Concrete exceptions in Python: Concrete exceptions in Python: Concrete exceptions in Python are build-in exceptions that inherited directly from the Exception class.
	BaseException
	Exception -
	AttributeError EOFError NameError StopIteration OSError TypeError ValueError
v	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data.
• v	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found. StopIteration - to indicate that all items are produced by the iterator. OSError([arg]) - Whenever a system function returns a system-related error such as I/O failures
• v	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found.
• v	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found. StopIteration - to indicate that all items are produced by the iterator. OSError([arg]) - Whenever a system function returns a system-related error such as I/O failures including "disk full" or "file not found" errors.
	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found. StopIteration - to indicate that all items are produced by the iterator. OSError([arg]) - Whenever a system function returns a system-related error such as I/O failures including "disk full" or "file not found" errors.
	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition vithout reading any data. NameError - The exception is raised when a global or local name is not found. Stopiteration - to indicate that all items are produced by the iterator. OSError([arg]) - Whenever a system function returns a system-related error such as I/O failures including "disk full" or "file not found" errors.
v v i	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found. Stopteration - to indicate that all items are produced by the iterator. OSError(largi) - Whenever a system function returns a system-related error such as I/O failures including "disk full" or "file not found" errors. TypeError - Raised when we apply an inappropriate type object to a function or an operation. ValueError - when a built-in function or operation receives the correct type of argument but with an invalid value RecursionError - Derived from RuntimeError and raised when maximum recursion depth has been exceeded. ImportError - ModuleNotFoundError - Raised when the import statement fails to load a module **Transaction** Transaction** Trans
[21]:	AttributeError - This can happen because the referred attribute does not exist. EOFError - raised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found. Stopiteration - to indicate that all items are produced by the iterator. OSError([arg]) - Whenever a system function returns a system-related error such as I/O failures neckding 'disk full' or 'file not found' errors. TypeError - Raised when we apply an inappropriate type object to a function or an operation. ValueError - when a built-in function or operation receives the correct type of argument but with an invalid value RecursionError - Derived from RuntimeError and raised when maximum recursion depth has been exceeded. ImportError - ModuleNotFoundError - Raised when the import statement falls to load a module **ManaError** **Traceback** (most recent call last) **Craceback** (most recent call last)
[21]: [18]:	Attribute from - This can happen because the referred attribute does not exist. EDFord - raised if the built-in functions such as input() encounters an end-of-file (EDF) condition without reading any data. Name from - The exception is raised when a global or local name is not found. Stopiteration - to indicate that all items are produced by the Iterator. OStroot([avg]) - Whenever a system function returns a system-related error such as I/O failures including "disk full" or "file not found" errors. Type from - Raised when we apply an inappropriate type object to a function or an operation. Value from - when a built-in function or operation receives the correct type of argument but with an invalid value Recursion from - Derived from Runtime From and raised when maximum recursion depth has been exceeded. ImportError - Module Not found from - Raised when the import statement falls to load a module **Manager row - Stroot Additional - Stroot
[21]: [18]:	AttributeError - This can happen because the referred attribute does not exist. EOPError - naised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NameError - The exception is raised when a global or local name is not found. Stopteration - to indicate that all items are produced by the iterator. OSError(Jug)) - Whenever a system function returns a system-related error such as I/O failures including "disk full" or "file not found" errors. TypeError - Raised when we apply an inappropriate type object to a function or an operation. ValueTror - when a built-in function or operation receives the correct type of argument but with an invalid value Recursion/for - Derived from RuntimeError and raised when maximum recursion depth has been exceeded. ImportFore - ModuleNetFoundError - Raised when the import statement fails to load a module PhaseError - Tracelabole (next exceed cell last) Application - T
[21]: [28]:	AttributeFror - This can happen because the referred attribute does not exist. EOfferor - naised if the built-in functions such as input() encounters an end-of-file (EOF) condition without reading any data. NumeError - The exception is raised when a global or local name is not found. Stoptteration - to indicate that all items are produced by the iterator. Oostron(jarg) - Whenever a system function returns a system related error such as I/O failures including "disk full" or "file not found" errors. TypeFrore - Raised when we apply an inappropriate type object to a function or an operation. ValueFror - when a built-in function or operation receives the correct type of argument but with an invalid value RecursionError - Derived from RuntimeError and raised when maximum recursion depth has been exceeded. ImportError - ModulationFoundError - Raised when the import statement fails to load a modula Phonostrore - a but the control of th
[21]: [21]: [28]:	Altribute fores - This can happen because the referred attribute does not exist. **Cofferor - calcied If the built-in functions such as input() encounters an end-of-file (IOF) condition without reading any data. **NameError - The exception is raised when a global or local name is not found. **Stepheration - to indicate that all terms are produced by the Recardor. **OSError(long) - Whenever a system function returns a system-related error such as I/O failures noted ling "disk full" or "file not found" error. **OSError(long) - Whenever a system function returns a system-related error such as I/O failures noted ling "disk full" or "file not found" error. **TypeError - Raised when we apply an inappropriate type object to a function or an operation. **Valuations - when a built in function or operation receives the correct type of argument but with an invalid value importance - ModulabioFoundations - Raised when the import statement falls to local a module **Commissions - Oserical from RuntimeError and mised when maximum recursion depth has been succeeded. **Importance - ModulabioFoundations - Raised when the import statement falls to local a module **Commissions - Oserical from RuntimeError and mised when maximum recursion depth has been succeeded. **Importance - ModulabioFoundations - Raised when the import statement falls to local a module **Commissions - Oserical from RuntimeError - Raised when the import statement falls to local a module **Commissions - Oserical from RuntimeError - Raised when the import statement fall is also local a module **Commissions - Oserical from RuntimeError - Raised when the import statement falls to local a module **Commissions - Oserical from RuntimeError - Raised when the import statement fall is also local a module **Commissions - Oserical from RuntimeError - Raised when the import statement fall is local a module **Commissions - Oserical from Functions - Raised whenever - Oserical falls - Oserical
[21]: [21]: [28]:	Attribute/firer - This can happen because the referred attribute does not exist. **Coloror - raised if the bush in functions such as inpot() encounters an end of-file (EOF) condition villunit reading any data. **Raiseforer - The exception is raised when a global or local name is not found. **Supplieration - to indicate that all items are produced by the function. **Coloror(facy) - Wheever a system function returns a system related error such as (xx foliates enclosing) - fish full or "Tile not found" errors. **Typeform - Raised when we apply an inappropriate type object to a function or an operation. **What firer - where a built is function or operation receives the correct type of argument but with an invatid valuar flavor - Derived from Raistinus Fror and calcular when maximum recorded depth has been exceeded. **Importance - Medical hold conditions - Raised when the import statement fails to local a modular flavor - Derived from Raistinus Fror and calcular when the import statement fails to local a modular flavor - Derived from Raistinus Fror and calcular when the import statement fails to local a modular flavor - Derived from Raistinus Fror and calcular when the import statement fails to local a modular flavor - Derived from Raistinus Fror and calcular when the import statement fails to local a modular flavor - Derived flavor - Derive
[21]: [28]:	Additional form - This can happen became the referred attribute does not wint. (Of form - nieded if the built-in functions such as input!) encounters an end-of-file (EOF) condition influent reading any data. (Nameforer - The exception is raised where a global or local name is not found. Southerstion - to indicate that all items are produced by the iterator. OScreen(pag) - Whenever a system function returns a system related error such as I/O failures relating in the system of the control of th
[21]: [28]:	Additional form - This can happen because the referred attribute does not exist. **Efform - raised If the both in functions such as lapart, encounters an each of the (COT) condition without certain gray date. **Remarkers** The complaints instead when a global or local name in not found. **Complements** The complaints instead when a global or local name in not found. **Complements** The complaints instead when a global or local name in not found. **Complements** The complaints instead when a global or local name in not found. **Complements** The complaints** The complaints