

i

S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S1

Section 1

Q1

Q2

Palindromic Integer

Flag Question

Problem Description

You are given an **integer A** as input and you need to determine whether it is a **palindrome** or **not**. A **palindrome integer** is one whose digits, when reversed, result in the same number. For **example**, 121 is a palindrome because its reverse is also 121, but 123 is not a palindrome because its reverse is 321.

Note: The given integer will not have any leading zeros.

Problem Constraints

1 <= A <= 10⁶

Input Format

First and the only line contains a single integer **A**.

Output Format

Print **Yes** if it is palindromic, else print **No**.

Example Input

Input 1:

120

Input 2:

1001

Input 3:

131

Output 1:

No

Output 2:

Yes

Output 3:

Yes

Example Explanation

Explanation 1:

For A = 120, reverse(A) = reverse(120) = 021 = 21 (removing leading zeroes). 120 is not equal to 21

Explanation 2:

For A = 1001, reverse(A) = reverse(1001) = 1001, which is same as A.

Explanation 3:

For A = 131, reverse(A) = reverse(131) = 131, which is same as A.

See Expected Output

HINTS



Video Explanation

New

Hint 1

Hint 2

Solution Approach

Complete Solution



Editor Mode - Normal



Java 8 (oracle-jdk-1.8)



```
1 import java.lang.*;
2 import java.util.*;
3
4 public class Main {
5     public static void main(String[] args) {
6         // YOUR CODE GOES HERE
7         // Please take input and print output to standard input/output (stdin/stdout)
8         // DO NOT USE ARGUMENTS FOR INPUTS
9         // E.g. 'Scanner' for input & 'System.out' for output
10        Scanner sc = new Scanner(System.in);
11        int n = sc.nextInt();
12        int m = n;
13        int np = 0;
14        while(m>0){
15            np = np*10 +(m%10);
16            m/=10;
17        }
18        if(np == n){
19            System.out.println("Yes");
20        }else{
21            System.out.println("No");
22        }
23    }
24 }
25 }
```

Reset

Test

Test with Custom Input

Submit

i

S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S1

Section 1

Q1

>

Q2

Which triangle?

Flag Question

Problem Description

Write a program to input from user three numbers(**A, B & C**) representing side lengths of a triangle.
You have to print if the traingle is "equilateral", "scalene" or "isosceles".

Problem Constraints

1 <= A <= 100000
1 <= B <= 100000
1 <= C <= 100000

Note: It is guaranteed that the given sides form a valid triangle.

Input Format

One line containing three space separated integers **A, B & C**.

Output Format

One string either "equilateral", "scalene" or "isosceles".

Example Input

Input 1:

5 6 7

Input 2:

30 30 30

Example Output

Output 1:

scalene

Output 2:

equilateral

Example Explanation

Explanation 1:

Since all sides are different, hence it's a scalene triangle.

Explanation 2:

Since all sides are same, hence it's a equilateral triangle.

See Expected Output

HINTS	Video Explanation New	Hint 1	Solution Approach	Complete Solution	
-------	------------------------------------	--------	-------------------	-------------------	--

Editor Mode - Normal Java 8 (oracle-jdk-1.8)

```
1 import java.lang.*;
2 import java.util.*;
3
4 public class Main {
5     public static void main(String[] args) {
6         // YOUR CODE GOES HERE
7         // Please take input and print output to standard input/output (stdin/stdout)
8         // DO NOT USE ARGUMENTS FOR INPUTS
9         // E.g. 'Scanner' for input & 'System.out' for output
10        Scanner sc = new Scanner(System.in);
11        int a = sc.nextInt();
12        int b = sc.nextInt();
13        int c = sc.nextInt();
14        if(a==b && a==c){
15            System.out.println("equilateral");
16        }else if((a==b) || (a==c) || (b==c)){
17            System.out.println("isosceles");
18        }else{
19            System.out.println("scalene");
20        }
21    }
22 }
23 }
```

Reset

Test

Test with Custom Input

Submit

✔ Correct Answer.

S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

Cashback Message

Flag Question

Problem Description

There is a cashback scheme on a shopping platform.

The Cashback amount depends on the price of the product. You need to display a message for the product containing cashback amount according to below rules.

If the price falls between 100 to 500 then cashback amount is 20.

If the price falls between 501 to 1000 then cashback amount is 50.

If the price falls between 1001 to 2000 then cashback amount is 100.

If the price falls between 2001 to 5000 then cashback amount is 200.

If the price is greater than 5000 then cashback amount is 500.

For any product with price other than the above ranges, there is no cashback.

Problem Constraints

0 <= price <= 100000

Input Format

In first line take price as integer input.

Output Format

Output is going to be single line answer based on the price of product.

If price falls in any valid ranges then print "Cashback amount for this product is **cashback**".

Print "No cashback on this product" if not in any valid range.

Example Input

Input 1 :
80

Input 2 :
150

Example Output

Output 1 :
No cashback on this product

Output 2 :
Cashback amount for this product is 20

Example Explanation

Explanation 1 :
Since price is 80, So there is no cashback

Explanation 2 :
Since price is between 100 to 500, so cashback amount is 20

See Expected Output

HINTS	Hint 1	Solution Approach	Complete Solution	
-------	--------	-------------------	-------------------	--

Editor Mode - Normal

Java 8 (oracle-jdk-1.8)

```
1 import java.lang.*;
2 import java.util.*;
3
4 public class Main {
5     public static void main(String[] args) {
6         // YOUR CODE GOES HERE
7         // Please take input and print output to standard input/output (stdin/stdout)
8         // DO NOT USE ARGUMENTS FOR INPUTS
9         // E.g. 'Scanner' for input & 'System.out' for output
10        Scanner sc = new Scanner(System.in);
11        int amount = sc.nextInt();
12        if(amount>5000){
13            System.out.println("Cashback amount for this product is 500");
14        }else if(amount>2000){
15            System.out.println("Cashback amount for this product is 200");
16        }else if(amount>1000){
17            System.out.println("Cashback amount for this product is 100");
18        }else if(amount>500){
19            System.out.println("Cashback amount for this product is 50");
20        }else if(amount>99){
21            System.out.println("Cashback amount for this product is 20");
22        }else{
23            System.out.println("No cashback on this product");
24        }
25    }
26 }
```

Reset

Test

Test with Custom Input

Submit

Correct Answer.



S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3](#) > [Q4](#) > [Q5](#) > [Q6](#) > [Q7](#) > [Q8](#) > [Q9](#) > [Q10](#) > [Q11](#) > [Q12](#) > [Q13](#)

TypeCasting - 2

[Flag Question](#)

What will happen with the following code?

```
double x = 10.5;
int y = (int) x;    // Line 1
long z = y;        // Line 2
long big = 9876543210L;
int small = (int) big; // Line 3
```

HINTS

[Complete Solution](#)

- ☐ Line 2 works without explicit cast (widening conversion).
- ☐ Line 3 gives a compile-time error.
- ☐ Line 2 requires explicit cast.
- ☐ Line 1 compiles with explicit cast (fractional part lost).

Expected Answer: Line 1 compiles with explicit cast (fractional part lost),Line 2 works without explicit cast (widening conversion).

✓ Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.

[Re-Submit](#)



S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3](#) > [Q4](#) > [Q5](#) > [Q6](#) > [Q7](#) > [Q8](#) > [Q9](#) > [Q10](#) > [Q11](#) > [Q12](#) > [Q13](#)

Unary Operator -1

[Flag Question](#)Which statements about pre-increment (`++x`) are correct? HINTS[Complete Solution](#)

- ☐ `int y = ++x;` means `y` gets the updated value of `x`.
- ☐ The value of `x` is incremented first, then returned.
- ☐ The old value of `x` is returned before increment.
- ☐ It cannot be used in an assignment statement.

Expected Answer: The value of `x` is incremented first, then returned.,`int y = ++x;` means `y` gets the updated value of `x`. Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.

Re-Submit





S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3](#) > [Q4](#) > [Q5](#) > [Q6](#) > [Q7](#) > [Q8](#) > [Q9](#) > [Q10](#) > [Q11](#) > [Q12](#) > [Q13](#)

Linux - 2

[Flag Question](#)

Which of the following ls options will show file details along with hidden files?

 HINTS[Complete Solution](#)☐ ls -s☐ ls --version☐ ls -la☐ ls -alh

Expected Answer: ls -la,ls -alh

 Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.

Re-Submit





Output 2 :

34

Example Explanation

Explanation 1 :

The Squares of 1, 2, 3, 5, 6 are: $1 + 4 + 9 + 25 + 36$.

So total is 75

Explanation 2 :

The Squares of 2, 1, 3, 4, 2 are: $4 + 1 + 9 + 16 + 4$.

So total is 34

[See Expected Output](#)

HINTS

[Hint 1](#)[Solution Approach](#)[Complete Solution](#)

Editor Mode - Normal



Java 8 (oracle-jdk-1.8)



```
1 import java.lang.*;
2 import java.util.*;
3
4 public class Main {
5     public static void main(String[] args) {
6         // YOUR CODE GOES HERE
7         // Please take input and print output to standard input/output (stdin/stdout)
8         // DO NOT USE ARGUMENTS FOR INPUTS
9         // E.g. 'Scanner' for input & 'System.out' for output
10        Scanner sc = new Scanner(System.in);
11        long answer = 0 ;
12        for(int i = 0;i<5;i++){
13            long temp = sc.nextLong();
14            answer+= temp*temp;
15        }
16        System.out.println(answer);
17    }
18 }
19
20 }
```

[Reset](#)[Test](#)[Test with Custom Input](#)[Submit](#)

✓ Correct Answer.



S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3](#) > [Q4](#) > [Q5](#) > [Q6](#) > [Q7](#) > [Q8](#) > [Q9](#) > [Q10](#) > [Q11](#) > [Q12](#) > [Q13](#)

TypeCasting - 1

[Flag Question](#)

Which of the following statements about typecasting between **double** and **int** are correct in Java?

 HINTS[Complete Solution](#)

- ☐ Implicit casting from int to double is allowed (widening conversion).
- ☐ int can directly store decimal values without casting.
- ☐ Explicit casting is required from double to int (narrowing conversion).
- ☐ Casting from double to int may cause data loss (fractional part is truncated).

Expected Answer: Implicit casting from int to double is allowed (widening conversion), Explicit casting is required from double to int (narrowing conversion), Casting from double to int may cause data loss (fractional part is truncated).

✓ Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.



Re-Submit





S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

Q3 > Q4 > Q5 > Q6 > Q7 > Q8 > Q9 > Q10 > Q11 > Q12 > Q13

IfElse + Loops

Flag Question

What is the output for following Code?

```
1 int a = 1;
2 int y = 0;
3 int s = 1;
4
5 while (y <= 20) {
6     y = a++ + ++a;
7     s = y * s;
8 }
9
10 // After loop, check condition
11 if (s % 2 == 0) {
12     System.out.println(y);
13 } else {
14     System.out.println(s);
15 }
```

HINTS



Complete Solution

24

Expected Answer: ["24"]



Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.



Re-Submit



CORRECT ANSWER

Your answer has been evaluated.





S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3 >](#) [Q4 >](#) [Q5 >](#) [Q6 >](#) [Q7 >](#) [Q8 >](#) [Q9 >](#) [Q10 >](#) [Q11 >](#) [Q12 >](#) [Q13](#)

Loops - 2

[Flag Question](#)

What is the output for following Code?

```
1 import java.util.*;
2 class Main {
3     public static void main(String args[]) {
4         int n = 34562;
5         int sum = 0;
6         while(n > 0) {
7             int ld = n % 10;
8             sum += 1;
9             System.out.print(ld + " ");
10            n = n / 10;
11        }
12        System.out.print(sum);
13    }
14 }
```

HINTS

[Complete Solution](#)

2 6 5 4 3 5

Expected Answer: ["2 6 5 4 3 5"]



Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.



Re-Submit



CORRECT ANSWER

Your answer has been evaluated.





S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3](#) > [Q4](#) > [Q5](#) > [Q6](#) > [Q7](#) > [Q8](#) > [Q9](#) > [Q10](#) > [Q11](#) > [Q12](#) > [Q13](#)

Linux - 1

[Flag Question](#)

Which cat commands are valid?

HINTS

[Complete Solution](#)☐ cat file1.txt file2.txt >> combined.txt☐ cat notes.txt☐ cat >> diary.txt☐ cat --remove file.txt

Expected Answer: cat notes.txt,cat file1.txt file2.txt >> combined.txt,cat >> diary.txt

Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.

[Re-Submit](#)



S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

S2 Section 2

[Q3](#) > [Q4](#) > [Q5](#) > [Q6](#) > [Q7](#) > [Q8](#) > [Q9](#) > [Q10](#) > [Q11](#) > [Q12](#) > [Q13](#)

If Else - 1

[Flag Question](#)

What is the output for following Code?

```
1  if (true) {  
2      if (true) {  
3          if (false) {  
4              System.out.println(5 / 0);  
5          } else {  
6              System.out.println("Hey there");  
7          }  
8      } else {  
9          System.out.println("Hello");  
10     }  
11 } else {  
12     System.out.println("Hi");  
13 }  
14
```

 HINTS[Complete Solution](#)

Hey there

Expected Answer: ["Hey there"]



Your answer to this question has been recorded. It will be evaluated after the end of the contest. If you change your answer, kindly re-submit.



Re-Submit



CORRECT ANSWER

Your answer has been evaluated.



i

S1

Q 1

Q 2

S2

Q 3

Q 4

Q 5

Q 6

Q 7

Q 8

Q 9

Q 10

Q 11

Q 12

Q 13

Primes Count Between A to B

Flag Question

Problem Description

Given two numbers **A** and **B**. Return the count of prime numbers available between A to B in which A and B both are inclusive.

Problem Constraints

1 <= **A** < **B** <= 1000

Input Format

Given Integer Arguments A and B

Output Format

Return An Integer Count [i.e. count of prime numbers]

Example Input

Input 1 :

10

20

Input 2 :

5

25

Example Output

Output 1 :

4

Output 2 :

7

Example Explanation

Explanation 1 :

Prime Numbers Between 10 20 are : 11, 13, 17, 19

So count is 4

Explanation 2 :

Prime Numbers Between 5 25 are : 5, 7, 11, 13, 17, 19, 23

So count is 7

See Expected Output

HINTS ? Hint 1 Solution Approach Complete Solution

Editor Mode - Normal Java 8 (oracle-jdk-1.8)

```
1 import java.lang.*;
2 import java.util.*;
3
4 public class Main {
5     public static void main(String[] args) {
6         // YOUR CODE GOES HERE
7         // Please take input and print output to standard input/output (stdin/stdout)
8         // DO NOT USE ARGUMENTS FOR INPUTS
9         // E.g. 'Scanner' for input & 'System.out' for output
10        Scanner sc = new Scanner(System.in);
11        int A = sc.nextInt();
12        int B = sc.nextInt();
13        int count=0;
14        for(int i=A;i<=B;i++){
15            boolean check = true;
16            for(int j= 2; j*j<=i;j++){
17                if(i%j==0){
18                    check = false;
19                    break;
20                }
21            }
22            if(check && i!=1){
23                count++;
24            }
25        }
26        System.out.println(count);
27    }
28 }
29 }
```

Reset Test Test with Custom Input Submit

Correct Answer.