Express

A Node.js web application framework that helps us to make web applications

It is used for server side programming.

- Listen for incoming request
- parse input request
- match response with routes
- response

Getting Started with Express

```
const express = require("express");
const app = express();

let port = 8080;

app.listen(port, () => {
  console.log(`app listening on port ${port}`);
});
```

*Ports are the logical endpoints of a network connection that is used to exchange information between a web server and a web client.

app.use

```
app.use((req, res) => {
  console.log("new incoming request");
});
```

hoppscotch/hoppscotch

#2051 **How can i work with localhost APIs?**

Answered Q&A 21 comments

juaiglesias opened on December 30, 2021

GitHub

How can i work with localhost APIs? · hoppscotch hoppscotch · Discus...

Hello everyone! First of all, thanks for this space. I wanted to ask how it's possible to work with localhost APIs, I couldn't find enought doc about this...

```
app.use((req, res) => {
  //   console.log(req);
  console.log("request received");
  res.send("this is a basic response");
});
```

```
app.use((req, res) => {
  console.log("request received");
  res.send({
    name: "apple",
    color: "red",
  });
});
```

```
app.use((req, res) => {
  console.log("request received");
  let code = "<h1>Fruits</h1> <ul><li>apple</li><li>orange
  res.send(code);
});
```

Routing

it is process of selecting a path for traffic in a network or between or across multiple networks.

```
app.get("/apple", (req, res) => {
  res.send({
    name: "apple",
    color: "red",
  });
});
```

Nodemon

To **automatically restart server** with code changes

Path Parameters

req.params

```
app.get("/ig/:username", (req, res) => {
  let { username } = req.params;
  res.send(`This account belongs to @${username}`);
});
```

Path parameters are variable parts of a URL path used to identify a specific resource within a collection. They are embedded directly into the endpoint and are essential for locating a unique item. Swagger +3

Query Strings

req.query

```
app.get("/search", (req, res) => {
  let { q } = req.query;
  if (!q) {
    res.send("No search query");
  }
  res.send(`These are the results for: ${q}`);
});
```

Templating

EJS (Embedded JavaScript templates)

EJS is a simple templating language that lets you generate HTML markup with plain JavaScrip