Creating the Model

Chat will have : (_id, from, to, message, created_at)

MongoDB by default runs without authentication enabled. When you install MongoDB locally, it starts in **unauthenticated mode**, so any local connection can access it without credentials.

The connection string format with credentials would be:

```
mongodb://username:password@127.0.0.1:27017/whatsapp
```

But since your local MongoDB instance has no auth configured, the simple form works fine:

```
mongodb://127.0.0.1:27017/whatsapp
```

Index Route

GET /chats → show all chats

Chats

New & Create Route

new chat

button

GET /chats/new → form render (message/chat)

POST /chats

↓

DB insert chat

Yes, **big problem.** `res.redirect('/chats')` is **outside** the `.then()`, so it runs immediately without waiting for the save to finish:

```
newChat
    .save()
    .then((res) => {          // ← 'res' here shadows th
        console.log("chat was saved");
    })
    .catch((err) => {
        console.log(err);
    });

res.redirect("/chats");  // ❌ runs BEFORE save complete
```

Two bugs:

1. `res.redirect` **fires before DB save** — user gets redirected before chat is stored
2. `res` **in** `.then((res) =>` **shadows the Express** `res` — if you tried to use `res` inside `.then`, it would be the DB result, not the response object

Using Date

```
<%= chat.created_at.toString().split(" ")[4] %> <br />
<%= chat.created_at.toString().split(" ").slice(0, 4).join(" ") %> <br />
```

1) edit

2) Edit

Chats

Edit & Update Route

GET /chats/:id/edit → edit form display → msg edit

PUT /chats/:id

Chats

Destroy Route

DELETE /chats/:id