EJS

Embedded JavaScript Templating — dynamic HTML, powered by JS.

Templating

EJS (Embedded JavaScript templates)

EJS is a simple templating language that lets you generate HTML markup with plain JavaScript.

ejs.co

EJS -- Embedded JavaScript templates

'E' is for 'effective'. EJS is a simple templating language that lets you generate HTML markup with plain JavaScript. No religiousness about how to organize things. No reinvention of iteration and control-flow. It's just plain JavaScript.

Using EJS

```
app.set("view engine", "ejs");

app.get("/", (req, res) => {
  res.render("home.ejs");
});
```

Views Directory

```
const path = require("path");

app.set("views", path.join(__dirname, "/views"));
```

Interpolation Syntax

Interpolation refers to **embedding expressions** into marked up text.

Passing data to EJS

```
app.get("/rolldice", (req, res) => {
  let num = Math.floor(Math.random() * 6) + 1;
  res.render("rollDice.ejs", { diceVal: num });
});
```

```
<h1>Your dice gave value : <%= diceVal %></h1>
```

Instagram EJS

Create a basic template for instagram page based on following route :

*/igl:*username

Conditional Statements in EJS

Adding conditions inside EJS

```
<% if(diceVal == 6) { %>
<h2>Nice! Roll dice again.</h2>
<% } %>
```

Loops in EJS

```
<% for(user of followers) { %>
<li><%= user %></li>
<% } %>
```

Serving Static Files

app.use(express.static(folder_name))

```
app.use(express.static(path.join(__dirname, "public")));
```

```
You visit /ig/cats
    |
    ├── 1. Express sends follow_disp.ejs HTML
    |
    └── Browser reads HTML, finds <link>, <img> tags
            |
            ├── 2. GET /style.css  → express.static serves public/style.css
            └── 3. GET /image.jpg  → express.static serves public/image.jpg
```

This tells Express:

> "Treat the 🗀 `public` folder as if it lives at `/` on the server."

So:

```
public/style.css   →   accessible at   /style.css
public/logo.png    →   accessible at   /logo.png
public/js/app.js   →   accessible at   /js/app.js
```

It becomes a **relative URL**, so the browser resolves it relative to the **current page's URL path**.

If you're on `/ig/cats` and you write just `style.css`:

```
Current URL:  http://localhost:3000/ig/cats
              http://localhost:3000/ig/   ← browser takes this base
              + style.css
              = http://localhost:3000/ig/style.css  ❌
```

Includes

```
<%- include("includes/head.ejs"); %>
```