IT252 Database Systems Mid Sem Lab Exam Questions and Solution

Q: Consider the schema for Movie Database:

```
ACTOR (<u>Act_id</u>, Act_Name, Act_Gender)

DIRECTOR (<u>Dir_id</u>, Dir_Name, Dir_Phone)

MOVIES (<u>Mov_id</u>, Mov_Title, Mov_Year, Mov_Lang, Dir_id)

MOVIE_CAST (<u>Act_id</u>, Mov_id, Role)

RATING (<u>Mov_id</u>, Rev_Stars)
```

Write SQL queries to

- 1. List the titles of all movies directed by 'Hitchcock'.
- 2. Find the movie names where one or more actors acted in two or more movies.
- 3. List all actors who acted in a movie before 2000 and also in a movie after 2015 (use JOIN operation).
- 4. Find the title of movies and number of stars for each movie that has at least one rating and find the highest number of stars that movie received. Sort the result by movie title.
- 5. Update rating of all movies directed by 'Steven Spielberg' to 5.

Table Creation

CREATE TABLE ACTOR (

```
ACT ID NUMBER (3),
ACT_NAME VARCHAR (20),
ACT_GENDER CHAR (1),
PRIMARY KEY (ACT ID));
CREATE TABLE DIRECTOR (
DIR ID NUMBER (3),
DIR_NAME VARCHAR (20),
DIR PHONE NUMBER (10),
PRIMARY KEY (DIR_ID));
CREATE TABLE MOVIES (
MOV_ID NUMBER (4),
MOV TITLE VARCHAR (25),
MOV_YEAR NUMBER (4),
MOV_LANG VARCHAR (12),
DIR ID NUMBER (3),
PRIMARY KEY (MOV_ID),
FOREIGN KEY (DIR ID) REFERENCES DIRECTOR (DIR ID));
```

```
CREATE TABLE MOVIE_CAST (
ACT_ID NUMBER (3),
MOV_ID NUMBER (4),
ROLE VARCHAR (10),
PRIMARY KEY (ACT_ID, MOV_ID),
FOREIGN KEY (ACT_ID) REFERENCES ACTOR (ACT_ID),
FOREIGN KEY (MOV_ID) REFERENCES MOVIES (MOV_ID));
```

CREATE TABLE RATING (
MOV_ID NUMBER (4),
REV_STARS VARCHAR (25),
PRIMARY KEY (MOV_ID),
FOREIGN KEY (MOV_ID) REFERENCES MOVIES (MOV_ID));

Table Descriptions

DESC ACTOR;

SUL> DESC ACTUR;		
Nane	Nu11?	Туре
ACT_ID	NOT HULL	NUMBER(3)
ACT_NAME		UARCHAR2(20)
ACT GENDER		CHAR(1)

DESC DIRECTOR;

Name	Nu113	?	Туре
DIR ID	HOT I	NULL	HUMBER(3)
DIR_NAME			UARCHAR2(20)
DIR_PHONE			NUMBER(18)

DESC MOVIES;

SQL> DESC MOUIES; Name	Nu11?	Туре
MOU_ID	HOT HULL	HUMBER(4)
MOV_TITLE		VARCHAR2(25)
MOU_YEAR		NUNBER(4)
MOV_LANG		VARCHAR2(12)
DIR_ID		NUMBER(3)

DESC MOVIE_CAST;

Name	Nu1	1?	Туре
ACT_ID MOV_ID ROLE	HOT HOT	HULL	
DESC RATING;			
SQL> DESC RATING; Name	Nu11	?	Туре
MOV_ID REU_STARS	HOT	NULL	NUMBER(4) VARCHAR2(25)

Insertion of Values to Tables

```
INSERT INTO ACTOR VALUES (301, 'ANUSHKA', 'F');
INSERT INTO ACTOR VALUES (302, 'PRABHAS', 'M');
INSERT INTO ACTOR VALUES (303, 'PUNITH', 'M');
INSERT INTO ACTOR VALUES (304, 'JERMY', 'M');
```

```
INSERT INTO DIRECTOR VALUES (60, 'RAJAMOULI', 8751611001);
INSERT INTO DIRECTOR VALUES (61, 'HITCHCOCK', 7766138911);
INSERT INTO DIRECTOR VALUES (62, 'FARAN', 9986776531);
INSERT INTO DIRECTOR VALUES (63, 'STEVEN SPIELBERG', 8989776530);
```

INSERT INTO MOVIES VALUES (1001, 'BAHUBALI-2', 2017, 'TELAGU', 60); INSERT INTO MOVIES VALUES (1002, 'BAHUBALI-1', 2015, 'TELAGU', 60); INSERT INTO MOVIES VALUES (1003, 'AKASH', 2008, 'KANNADA', 61); INSERT INTO MOVIES VALUES (1004, 'WAR HORSE', 2011, 'ENGLISH', 63);

```
INSERT INTO MOVIE_CAST VALUES (301, 1002, 'HEROINE'); INSERT INTO MOVIE_CAST VALUES (301, 1001, 'HEROINE'); INSERT INTO MOVIE_CAST VALUES (303, 1003, 'HERO'); INSERT INTO MOVIE_CAST VALUES (303, 1002, 'GUEST'); INSERT INTO MOVIE_CAST VALUES (304, 1004, 'HERO');
```

```
INSERT INTO RATING VALUES (1001, 4);
INSERT INTO RATING VALUES (1002, 2);
```

INSERT INTO RATING VALUES (1003, 5); INSERT INTO RATING VALUES (1004, 4);

SELECT * FROM ACTOR;

SQL> SELECT * FROM ACTOR;

ACT_ID	ACT_NAME	A
		-
301	ANUSHKA	F
302	PRABHAS	М
3 03	PUNITH	M
304	JERMY	М

SELECT * FROM DIRECTOR;

SQL> SELECT * FROM DIRECTOR;

DIR_ID	DIR_NAME	DIR_PHONE
60	RAJAMOULI	8751611001
61	HITCHCOCK	7766138911
62	FARAN	9986776531
63	STEVEN SPIELBERG	8989776530

SELECT * FROM MOVIES;

SQL> SELECT * FROM MOVIES;

MOV_ID	MOV_TITLE	MOV_YEAR	MOV_LANG	DIR_ID
1001	BAHUBAL I-2	2017	TELAGU	60
1002	BAHUBALI-1	2015	TELAGU	60
1003	AKASH	2008	KANNADA	61
1004	WAR HORSE	2011	ENGLISH	63

SELECT * FROM MOVIE_CAST;

SQL> SELECT * FROM MOVIE_CAST;

ACT_ID	MOV_ID	ROLE
301	1002	HEROINE
301	1001	HEROINE
3 0 3	1003	HERO
3 0 3	1002	GUEST
304	1004	HERO

```
SELECT * FROM RATING;

SQL> SELECT * FROM RATING;

MOU_ID REU_STARS

1001 4
1002 2
1003 5
1004 4
```

Queries:

1. List the titles of all movies directed by 'Hitchcock'.

SELECT MOV_TITLE
FROM MOVIES
WHERE DIR_ID IN (SELECT DIR_ID
FROM DIRECTOR
WHERE DIR_NAME = 'HITCHCOCK');

МОЧ	, _	T	T	LE												
					 -	-	-	-	 	-	-	-	-	-	-	-
AK	25	Н														

2. Find the movie names where one or more actors acted in two or more movies.

SELECT MOV_TITLE

FROM MOVIES M, MOVIE_CAST MV

WHERE M.MOV_ID=MV.MOV_ID AND ACT_ID IN (SELECT ACT_ID

FROM MOVIE_CAST GROUP BY

ACT_ID HAVING COUNT (ACT_ID)>1)

GROUP BY MOV_TITLE

HAVING COUNT (*)>1;

```
MOU_TITLE
-----BAHUBALI-1
```

List all actors who acted in a movie before 2000 and also in a movie after 2015 (use JOIN operation).

SELECT ACT_NAME, MOV_TITLE, MOV_YEAR

FROM ACTOR A

JOIN MOVIE_CAST C

ON A.ACT_ID=C.ACT_ID

JOIN MOVIES M

ON C.MOV_ID=M.MOV_ID

WHERE M.MOV_YEAR NOT BETWEEN 2000 AND 2015;

OR

SELECT A.ACT_NAME, A.ACT_NAME, C.MOV_TITLE, C.MOV_YEAR FROM ACTOR A, MOVIE_CAST B, MOVIES C WHERE A.ACT_ID=B.ACT_ID AND B.MOV_ID=C.MOV_ID AND C.MOV_YEAR NOT BETWEEN 2000 AND 2015;

ACT_NAME	MOV_TITLE	MOV_YEAR
ANUSHKA	BAHUBALI-2	2017

4. Find the title of movies and number of stars for each movie that has at least one rating and find the highest number of stars that movie received. Sort the result by movie title.

SELECT MOV_TITLE, MAX (REV_STARS)
FROM MOVIES
INNER JOIN RATING USING (MOV_ID)
GROUP BY MOV_TITLE
HAVING MAX (REV_STARS)>0
ORDER BY MOV_TITLE;

MOV_TITLE	MAX(REU_STARS)
AKASH	5
BAHUBAL I - 1	2
BAHUBAL I - 2	4
WAR HORSE	4

5. Update rating of all movies directed by 'Steven Spielberg' to 5 $\rm KL$

UPDATE RATING

SET REV_STARS=5

WHERE MOV_ID IN (SELECT MOV_ID FROM MOVIES

WHERE DIR_ID IN (SELECT DIR_ID

FROM DIRECTOR

WHERE DIR_NAME = 'STEVEN

SPIELBERG'));

SQL> SELECT * FROM RATING;

##