Is the Judge the Bottleneck?

A Judge-Swap Study of Consistency-Based Detection of Fabricated References in Large Language Models

NAGIREDDY NITHIN KUMAR REDDY, Indian Institute of Information Technology Allahabad, India

Large language models (LLMs) fabricate bibliographic references, and a model's own consistency can reveal them: when asked repeatedly who wrote a reference, models tend to give stable author lists for real works and unstable ones for invented works. Agrawal et al. reported that such consistency checks detect hallucinated references well for GPT-4 but are ineffective for 7B–13B models, where the language model also acts as the judge of its own answers. We ask whether that failure lies in the judge or in the answers. Using the authors' released data (six models, 200 ACM computing topics, 1,000 references per model), we first reproduce all 36 published AUC values to within 0.0005, and in doing so find that one released file duplicates 200 references. We then run a judge-swap ablation: the same three sampled author answers per reference are scored by the original LM judge, by an external natural-language-inference (NLI) judge as used in SelfCheckGPT, and by a model-free name-overlap judge. The external NLI judge does not recover detection: on Llama-2-7B all judges remain near chance (AUROC 0.51–0.56; NLI minus LM judge +0.046, 95% CI $[-0.003, 0.094]$), and on the five larger models NLI is significantly worse than the LM judge (by 0.05–0.14). The model-free overlap judge matches the LM judge everywhere and beats it on two models. This pattern is consistent with the small-model failure lying in the sampled answers rather than in the judge. [TO VERIFY: state whether this holds on database-confirmed labels (post-hoc M2 check)] For research workflows, a cheap name-overlap check is as informative as an LM-based one. A pre-registered familiarity analysis finds a weak, non-significant tendency for fewer fabrications on well-published topics. All code, protocol, logs and an AI-use record are released.

CCS Concepts: • **Computing methodologies** → **Natural language processing**; • **Information systems** → *Information retrieval*.

Additional Key Words and Phrases: hallucination detection, citation fabrication, self-consistency, SelfCheckGPT, reproduction, natural language inference, research integrity

1 INTRODUCTION

Fabricated references are one of the most consequential hallucinations in LLM-assisted research because they create an apparently traceable evidence chain. Audits have documented substantial fabrication across scientific, medical and systematic-review settings [2–4, 19], with rates that depend on model, domain and topic familiarity [12]. The author's earlier review of hallucination types for research applications [18] argued that citation *existence* and citation *support* are separate verification problems and that self-assessment by the model is an unreliable safeguard [5]. This paper takes the first of those problems and studies one detection mechanism experimentally.

Sampling-based consistency checks detect hallucinations without external resources: if a model knows a fact, repeated samples agree; if it invents it, they diverge [13]. Agrawal et al. applied this idea to references [1]. Their *indirect query* (IQ) asks for the authors of a generated title in three independent sessions and lets the same LM judge how much the author lists overlap; their *direct queries* (DQ) ask whether the reference exists. For GPT-4 these checks achieve AUC $\approx$ 0.88, but for Llama-2-7B and -13B they are reported as not effective. In IQ the generator also judges its own answers. SelfCheckGPT instead hands the agreement judgement to a separate NLI model [13]. This suggests a precise, testable question: **is the small-model failure caused by a weak judge, or by answers that carry no consistency signal?**

Contributions.

(1) A verified reproduction of all 36 AUC values reported by Agrawal et al. from their released scores (max. deviation 0.0005), with an explanation of a text–figure discrepancy and the discovery of 200 duplicated references in one released file (§5.1).
(2) A *judge-swap ablation* that keeps the sampled author answers fixed and changes only the judge (LM, external NLI, model-free name overlap) across six models from Llama-2-7B to GPT-4 (§5.2).
(3) A robustness check of the Bing-based ground truth against scholarly databases (OpenAlex, Crossref) and a pre-registered test of topic familiarity (§5.3, §5.4).

The main result is negative for the hypothesis we pre-registered and, we argue, informative: changing the judge does not rescue small models.

2 RELATED WORK

Hallucination taxonomies. Surveys distinguish factuality from faithfulness and intrinsic from extrinsic errors [6, 7]; fabricated references are extrinsic, entity-level factual fabrications in that vocabulary. **Citation audits** measure fabrication by manual or database-backed checking [3, 4, 19] and report topic dependence [12]. **Detection without external knowledge** includes sampling consistency [13], reference-specific consistency queries [1], self-evaluation of correctness [8] and semantic uncertainty [10]; Kalai and Vempala argue that calibrated models must hallucinate rare facts [9]. **Detection with external knowledge** decomposes text into atomic facts [14], uses benchmarks [11, 16], or verifies references against bibliographic sources, recently with retrieval, fuzzy matching and an LLM verifier [15]; at web scale, citation URLs produced by LLMs and deep-research agents have been audited for resolvability [17]. Our study is closest to [1]: we reuse its data and checks and add a controlled change of the judge, which that work did not test.

3 RESEARCH QUESTIONS

RQ1 (judge). Holding the three sampled author answers fixed, does an external NLI judge (J-NLI) detect hallucinated references better than the LM judge (J-LM)? *H1*: AUROC(J-NLI) > AUROC(J-LM). The paired contrast was registered for each of the six models; the hypothesis was motivated by the small models, and Llama-2-7B is the setting closest to the registered 7B target. H1 is supported for a model if the paired 95% CI of the difference lies above 0. Six contrasts are reported without multiplicity correction. **RQ2 (familiarity).** Is fabrication more frequent for topics with fewer publications? *H2*: the logistic slope of $P(\text{hallucinated})$ on $\log_{10}$ topic works is negative; supported for a model if its 95% CI lies below 0. A third question on the number of samples, and a new-generator experiment (Qwen2.5-1.5B), were planned but dropped for time before they produced results; the pipeline is released but unexecuted (§7).

4 METHOD

4.1 Data

We use the results released with [1] (repository `microsoft/hallucinated-references`, commit `bf3ef5f`, MIT licence): for each of GPT-4, GPT-3.5-turbo, text-davinci-003 and Llama-2-Chat 7B/13B/70B, 1,000 generated titles (5 per topic for 200 ACM CCS topics), a Bing exact-title label (no result $\Rightarrow$ hallucinated, $y = 1$), three sampled author answers, and the released IQ and DQ scores. File integrity was checked against the paper's hallucination rates (e.g. GPT-4 468/1,000 = 46.8%, Llama-2-7B 68.3%). The Llama-2-13B file covers only 160 topics: rows 700–899 repeat 200 (topic, title) pairs with identical labels but re-sampled answers; we deduplicate it (800 references) for all new analyses. Ten topics, drawn with a fixed seed, form a *pilot* set used only to set parsing and

matching rules; all reported results use the remaining 190 *main* topics (5,520 references; 770 for 13B).

4.2 Judges

All judges score a reference from its three author answers a_1, a_2, a_3; higher means more likely hallucinated, and the orientation is fixed in advance. **J-LM** is Agrawal et al.'s released judge: the generator rates pairwise author overlap (0–100%), averaged over the three pairs; score = 1−overlap. **J-NLI** uses the SelfCheckGPT NLI checkpoint (`potsawee/deberta-v3-large-mnli`) and averages $P(\text{contradiction})$ over the six ordered pairs, encoded exactly as `SelfCheckNLI`. Agrawal's LM judge is instructed to output 0 if "either of them is not a list of authors"; we apply the same rule, scoring pairs that involve an answer with no parseable name (typically a refusal) as 1. Without the rule two refusals entail each other and look consistent; this variant (J-NLI-raw) is reported as a sensitivity check. **J-STR** needs no model: 1−mean pairwise Jaccard similarity of the sets of normalised name tokens. Token sets (rather than surnames) make "Bishop, Christopher" and "Christopher M. Bishop" agree. The parser was developed on pilot answers from the same six models (pilot topics are excluded from every result) and every rule is covered by a unit test built from real pilot rows; part of J-STR's performance may reflect this tuning.

4.3 Baseline validation

V2 recomputes Agrawal's IQ, DQ1–3, DQ-ensemble and IQ+DQ AUCs from the released scores. Their figures report the mean AUC over 100 bootstrap resamples (`roc-utils`, seed 42) with an automatic flip of below-chance predictors; because that package no longer imports with current SciPy, we reimplemented its procedure. The flip is used for V2 only. **V1** reproduces SelfCheckGPT on its WikiBio benchmark (238 passages, 20 samples each).

4.4 Ground-truth robustness (R1)

Bing labels date from 2023 and match any web page containing the exact phrase. We re-label the Llama-2-7B main-set titles by querying OpenAlex and then Crossref (five candidates each) and calling a title *found* if the best normalised similarity (`rapidfuzz` `ratio`) is ≥ 90, *partial* in $[75, 90)$, else *not found*. Both the threshold and the order-sensitive similarity were chosen on pilot titles: an order-insensitive measure matched a reordered fake title, and the chosen setting reached Cohen's $\kappa = 0.82$ (GPT-4) and 0.80 (Llama-2-7B) with Bing on the pilot.

4.5 Familiarity (RQ2)

Topic familiarity is $\log_{10}(1 + n)$, where n is the OpenAlex works count for the topic's leaf phrase (e.g. "Topology" in "Continuous mathematics: Topology"). Tertiles are defined over topics, so all models share cut points.

4.6 Statistics and protocol

AUROC is the primary metric. CIs are 95% percentile intervals from 2,000 bootstrap resamples of *topics* (references within a topic are not independent); judge differences are paired, using the same resamples. No auto-flip is applied. Settings, hypotheses, decision rules and seeds were frozen before any main-set score was computed (git tag `protocol-v1`); five later changes are logged with their reasons and whether results had been seen. Three preceded all main-set results; E1 was complete when the new-generator experiment was dropped for time and when RQ2 was re-registered on the released data, and both changes record this.

Table 1. V2: published AUCs of Agrawal et al. (figures 5 and 9) vs. our recomputation from the released scores (bootstrap mean). All 36 cells, including DQ1–3, are within 0.0005 (`results/v2_agrawal_auc.csv`).

	IQ		DQ ensemble		IQ+DQ	
Model	published	ours	published	ours	published	ours
GPT-4	0.877	0.8768	0.915	0.9149	0.927	0.9274
GPT-3.5-turbo	0.782	0.7818	0.624	0.6239	0.792	0.7922
text-davinci-003	0.695	0.6947	0.621	0.6211	0.710	0.7104
Llama-2-70B	0.658	0.6577	0.658	0.6583	0.702	0.7020
Llama-2-13B	0.657	0.6568	0.696	0.6961	0.723	0.7235
Llama-2-7B	0.517	0.5172	0.573	0.5729	0.575	0.5747

Table 2. E1: AUROC [95% CI] per judge and paired differences from the LM judge. **Bold** differences have CIs that exclude 0. J-NLI-raw omits the refusal rule.

Model (n, % hall.)	J-LM	J-NLI	J-STR	J-NLI − J-LM	J-STR − J-LM
GPT-4 (950, 48%)	0.881 [.855,.903]	0.834 [.800,.864]	0.876 [.849,.899]	**−0.047** [−.069,−.028]	−0.006 [−.016,.005]
GPT-3.5 (950, 61%)	0.774 [.740,.806]	0.717 [.676,.755]	0.782 [.748,.815]	**−0.057** [−.085,−.029]	+0.008 [−.005,.021]
GPT-3 (950, 74%)	0.694 [.652,.734]	0.580 [.526,.630]	0.722 [.675,.764]	**−0.114** [−.159,−.068]	**+0.027** [.008,.048]
Llama-2-70B (950, 66%)	0.660 [.618,.702]	0.524 [.479,.569]	0.711 [.671,.752]	**−0.136** [−.183,−.088]	**+0.052** [.027,.075]
Llama-2-13B (770, 77%)	0.658 [.604,.708]	0.545 [.487,.598]	0.640 [.584,.691]	**−0.113** [−.187,−.040]	−0.019 [−.069,.032]
Llama-2-7B (950, 69%)	0.513 [.481,.544]	0.559 [.515,.603]	0.546 [.506,.588]	+0.046 [−.003,.094]	+0.033 [−.021,.088]

5 RESULTS

5.1 Baseline validation

V2. All 36 published values were reproduced within the pre-registered tolerance of ±0.005; the maximum deviation is 0.0005. No predictor was auto-flipped, so the V2 values and our unflipped E1 values are on the same scale. Table 1 shows a subset. The paper's text quotes GPT-4 IQ 0.878 and DQ1 0.887 while its figure shows 0.877 and 0.885; our point AUCs (0.8781, 0.8868) and bootstrap means (0.8768, 0.8854) show that the text reports point estimates and the figure bootstrap means. The 13B duplication barely affects the published numbers (deduplicated IQ 0.660 vs. 0.657; IQ+DQ 0.729 vs. 0.724).

V1. SelfCheck-Unigram (max) reproduces the published WikiBio results almost exactly: non-factual AUC-PR 85.64 vs. 85.63, factual 58.50 vs. 58.47, passage-level Pearson correlation 64.72 vs. 64.71 (all 1,908 sentences). The full NLI benchmark (38,160 premise–hypothesis pairs) was not re-run: on the available hardware it would have taken about 40 h. Instead we verified that our batched NLI scorer is numerically identical to the official `SelfCheckNLI` class (maximum difference 2.0×10^{-7} on 25 sentence scores); the published NLI figure (92.50) is therefore not independently re-measured.

5.2 E1: changing the judge

Figure 1 and Table 2 give the results. As a consistency check, J-LM on the 190 main topics gives 0.881 for GPT-4, in line with the 0.877–0.878 reproduced on all 200.

H1 is not supported for any of the six registered contrasts. On Llama-2-7B, J-NLI exceeds J-LM by 0.046 but the CI includes 0, and all three judges remain close to chance (0.51–0.56). On the five larger models J-NLI is significantly *worse* than the LM judge, by 0.047 to 0.136; no multiplicity correction was registered, so these are six separate 95% intervals. The model-free J-STR is




Fig. 1. E1: AUROC of three judges applied to the same sampled author answers (190 main topics; 95% topic-cluster bootstrap CIs). The dashed line marks chance.

never significantly worse than J-LM and is significantly better on GPT-3 (+0.027) and Llama-2-70B (+0.052).

Sensitivity. Without the refusal rule, J-NLI on GPT-4 drops from 0.834 to 0.732, because consistent refusals look like agreement; for the other models the rule changes AUROC by at most 0.023. Using the 13B file with duplicates (V2) or without (E1) changes the 13B IQ AUC by 0.003.

5.3 R1: ground-truth robustness

[TO VERIFY: R1 main-set confusion matrix, partial share and κ for Llama-2-7B; fill from `results/r1_agreemer` and the R1 log.]

5.4 RQ2: topic familiarity

OpenAlex counts for the 190 leaf phrases range from 1,876 to 35.1 million works (median 1.08 million); the largest counts belong to generic words such as "Design" (35.1 million) and "Availability" (32.8 million), which illustrates the crudeness of the proxy. Figure 2 shows the slopes. Five of six are negative (fewer fabrications on better-published topics), but **no model's CI excludes 0**, so H2 is not supported; the pooled slope with model fixed effects is -0.144 $[-0.342, 0.040]$. The clearest monotone pattern is Llama-2-13B (fabrication 81.8%, 76.7%, 72.7% from low to high tertile; slope -0.34 $[-0.76, 0.02]$). Exploratory per-tertile AUROCs show no consistent dependence of detection quality on familiarity.

6 DISCUSSION

The judge is not the bottleneck at small scale. If Llama-2-7B's author answers contained a consistency signal that its own judging failed to read, an independent judge should have exposed it. Neither a large DeBERTa NLI model nor exact token overlap does: all judges stay within 0.06 of chance. The answers themselves therefore appear to vary about as much for real references as for invented ones. This is consistent with the failure reported by [1] lying in what the small model *knows* about authorship rather than in how its consistency is assessed, but it is an inference, not a




Fig. 2. RQ2: logistic slope of $P(\text{hallucinated})$ per $\log_{10}$ OpenAlex works of the topic (95% topic-cluster bootstrap CIs). Negative means fewer fabrications on better-published topics.

measurement of knowledge. Three alternatives remain open: (i) three samples may be too few to estimate consistency for a noisy generator; (ii) the decoding settings used to produce the released answers may suppress or exaggerate variation; (iii) label noise in the Bing ground truth could pull every judge towards chance. We test (iii) in §5.3; (i) and (ii) require new generations, which this study did not run.

Why NLI is the weakest judge. Comparing two author lists is set overlap, not entailment between sentences; an MNLI-trained model sees short name lists far from its training distribution and can call two different lists "neutral" rather than contradictory. The model-free J-STR, which measures overlap directly, matches or beats the LM judge on every model. The more general lesson for consistency-based detection is that the agreement function should fit the answer type: SelfCheckGPT's NLI judge was designed for sentences of a biography, not for structured fields.

Implications for research workflows. A name-overlap check over three sampled author answers costs three short generations and no judge model, and is as informative as the LM judge. It remains a weak signal for small models, which supports the review's recommendation that citation existence be verified against bibliographic databases rather than inferred from the model's self-consistency.

7 LIMITATIONS AND THREATS TO VALIDITY

- **Ground truth.** Labels are Agrawal et al.'s 2023 Bing exact-phrase searches; R1 quantifies their agreement with scholarly databases but does not replace them.
- **Fixed answers.** E1 isolates the judge by design; it cannot say whether different prompts or more samples would produce a usable signal at 7B. The planned new-generator experiment (Qwen2.5-1.5B, with direct, log-probability, verbal-confidence and SelfCheck detectors) was dropped after a measured cost of 334 s per topic on the available hardware; its code is released but was not run on the main set.
- **Baseline scope.** The NLI baseline was validated by showing that our scorer is identical to the official implementation, not by re-measuring its published benchmark score.
- **Familiarity proxy.** Leaf-phrase search counts are crude: generic leaves such as "Design" count works far outside computing. RQ2 also performs six tests without correction.
- **Scope.** Computer-science topics, English, and closed or 2023-era models; J-STR's parser was tuned on pilot answers from these models.

8 REPRODUCIBILITY AND AI USE

The repository contains the frozen protocol, all decision and protocol-change records, the scripts that produce every table and figure from cached data, unit tests, environment logs and exact package versions. V2, E1 and RQ2 run from the released data on a laptop (E1: about one hour on an Apple-silicon GPU); R1 is limited by the OpenAlex and Crossref rate limits, and all API responses are cached so reruns need no network. AI assistance (Claude Code) was used for literature search, code generation, debugging and drafting; every AI-proposed source was checked against its primary page, every number in this paper comes from a logged run, and the AI-assistance log records the cases where verification changed the work, including an overclaimed novelty framing, a name parser that failed on real answer formats, and the auto-flip in the original AUC procedure.

9 CONCLUSION

Replacing the LM judge of a reference-consistency check with an external NLI model does not rescue detection for small models: on Llama-2-7B every judge stays near chance, and on larger models the NLI judge is worse than the LM it replaces. A model-free name-overlap judge is as good as the LM judge throughout. This is consistent with the small-model failure lying in the sampled answers rather than the judge; for practical citation checking, cheap overlap measures and database verification are the more promising combination.

REFERENCES

[1] Ayush Agrawal, Mirac Suzgun, Lester Mackey, and Adam Tauman Kalai. 2023. Do Language Models Know When They're Hallucinating References? *arXiv preprint arXiv:2305.18248* (2023). https://doi.org/10.48550/arXiv.2305.18248 Version 3, 20 March 2024.

[2] S. A. Athaluri, S. V. Manthena, V. S. R. K. M. Kesapragada, V. Yarlagadda, T. Dave, and R. T. S. Duddumpudi. 2023. Exploring the Boundaries of Reality: Investigating the Phenomenon of Artificial Intelligence Hallucination in Scientific Writing Through ChatGPT References. *Cureus* 15, 4 (2023), e37432. https://doi.org/10.7759/cureus.37432

[3] M. Bhattacharyya, V. M. Miller, D. Bhattacharyya, and L. E. Miller. 2023. High Rates of Fabricated and Inaccurate References in ChatGPT-Generated Medical Content. *Cureus* 15, 5 (2023), e39238. https://doi.org/10.7759/cureus.39238

[4] M. Chelli, J. Descamps, V. Lavoué, C. Trojani, M. Azar, M. Deckert, J.-L. Raynier, P. Clavert, J. Ma, B. Beauplet, and C. Denis. 2024. Hallucination Rates and Reference Accuracy of ChatGPT and Bard for Systematic Reviews: Comparative Analysis. *Journal of Medical Internet Research* 26, 1 (2024), e53164. https://doi.org/10.2196/53164

[5] Matthew Dahl, Varun Magesh, Mirac Suzgun, and Daniel E. Ho. 2024. Large Legal Fictions: Profiling Legal Hallucinations in Large Language Models. *Journal of Legal Analysis* 16, 1 (2024), 64–93. https://doi.org/10.1093/jla/laae003

[6] Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qiang Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. 2025. A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions. *ACM Transactions on Information Systems* 43, 2 (2025), Article 3155. https://doi.org/10.1145/3703155

[7] Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of Hallucination in Natural Language Generation. *Comput. Surveys* 55, 12 (2023), Article 248. https://doi.org/10.1145/3571730

[8] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. 2022. Language Models (Mostly) Know What They Know. *arXiv preprint arXiv:2207.05221* (2022). https://doi.org/10.48550/arXiv.2207.05221

[9] Adam Tauman Kalai and Santosh S. Vempala. 2024. Calibrated Language Models Must Hallucinate. *arXiv preprint arXiv:2311.14648* (2024). https://doi.org/10.48550/arXiv.2311.14648

[10] Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. 2023. Semantic Uncertainty: Linguistic Invariances for Uncertainty Estimation in Natural Language Generation. In *International Conference on Learning Representations*. https://doi.org/10.48550/arXiv.2302.09664 arXiv:2302.09664

[11] Junyi Li, Xiaoxue Cheng, Wayne Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. 2023. HaluEval: A Large-Scale Hallucination Evaluation Benchmark for Large Language Models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 6449–6464. arXiv:2305.11747

[12] Jake Linardon, Hannah K. Jarman, Zoe McClure, C. Anderson, C. Liu, and M. Messer. 2025. Influence of Topic Familiarity and Prompt Specificity on Citation Fabrication in Mental Health Research Using Large Language Models:

Experimental Study. *JMIR Mental Health* 12, 1 (2025), e80371. https://doi.org/10.2196/80371

[13] Potsawee Manakul, Adian Liusie, and Mark J. F. Gales. 2023. SelfCheckGPT: Zero-Resource Black-Box Hallucination Detection for Generative Large Language Models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 9004–9017. arXiv:2303.08896

[14] Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. 2023. FActScore: Fine-Grained Atomic Evaluation of Factual Precision in Long Form Text Generation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 12076–12100. arXiv:2305.14251

[15] Nipun Misra and Vikranth Udandarao. 2026. Detecting Citation Hallucinations in Large Language Model Outputs (Student Abstract). In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 40. https://doi.org/10.1609/aaai.v40i48.42257

[16] Cheng Niu, Yifan Wu, Jia Zhu, Shanshan Xu, Kevin Shum, Rita Zhong, J. Song, and Tong Zhang. 2024. RAGTruth: A Hallucination Corpus for Developing Trustworthy Retrieval-Augmented Language Models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics, 10862–10878.

[17] Delip Rao, Eric Wong, and Chris Callison-Burch. 2026. Detecting and Correcting Reference Hallucinations in Commercial LLMs and Deep Research Agents. *arXiv preprint arXiv:2604.03173* (2026). https://doi.org/10.48550/arXiv.2604.03173

[18] Nagireddy Nithin Kumar Reddy. 2026. A Taxonomy of Hallucination Types in Large Language Models for Research Applications. (2026). Review paper, AI Tools for Research mid-semester evaluation, IIIT Allahabad.

[19] William H. Walters and E. I. Wilder. 2023. Fabrication and Errors in the Bibliographic Citations Generated by ChatGPT. *Scientific Reports* 13 (2023), 14045. https://doi.org/10.1038/s41598-023-41032-5