Pot 13

Ping Program.

Aim :

To implement a user-defined Ping Program to Check the reachability of a host and obtain its response time..

Algorithm :-

* Start the program.
* Get the hostname or IP address from the user.
* Execute a ping request to the specified host.
* Wait for the responsed from the host
* If a reply or response from the host
* If a reply is received, displayed the host is reachable and responses details.
* If no reply is received, displayed the host is unreachable.
* stop the program.

Code :-

```
import java.io.*;

Public Class Mpping {.

    Public Static Void main (String [] a) throws Exception {
                                  new Buffer
        BufferedReader b= Reader (new InputStreamReader(system
                                                    in));

        System.out.print ("Enter host");
```

Result :-

```
PS C:\User\Dell\Download\Cn-13 > javac MyPing.java
PSC:\User\Dell\Download\Cn-13 > java MyPing.
```

Enter host : google.com

Pinging google.com [142.251.221.174] with 32 bytes of

Reply from 142.251.221.174: bytes = 32 times = 7ms TTL=118

Reply from 142.251.221.174: bytes = 32 times = 7ms TTL=118

Reply from 142.251.221.174: bytes = 32 time = 32ms TTL=11

Reply from 142.251.221.174: bytes = 32 Time = 8ms TTL = 118

Ping statistics for 142.251.221.174:

Packet : Sent = 4, Received = 4; Lost = 0 (0% Loss)

Approximate round trip times in milli-Second:

Minimum = 7ms, Maximum = 32ms, Average = 13ms.

```
String h = b.readLine();
Process p = Runtime.getRuntime().exec(new String
    [] {"ping", "-n", "4", h});
BufferedReader r = new BufferedReader(new
 InputStreamReader(p.getInputStream()));
String s;
while((s=r.readLine())!=null)
 System.out.println(s);
}
}
```

Result:-

Thus; the Ping-Program was successfully implemented to check the reachability of a host and Obtain its response information.