Status	Finished
Started	Thursday, 8 October 2026, 8:25 PM
Completed	Thursday, 8 October 2026, 8:28 PM
Duration	3 mins 44 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. wb+
b. ab+
c. r
d. rw+ ✓

The correct answer is: rw+

Question **2**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

a. readlines()
b. readchar()
c. readline()
d. read(size) ✓

The correct answer is: read(size)

Question **3**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open("c:\\scores.txt", "w") ✓

b. outfile = open(file = "c:\\scores.txt", "w")

c. outfile = open(file = "c:\scores.txt", "w")

d. outfile = open("c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **4**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

a. file.closed()

b. file.isclosed()

c. file.closed ✓

d. file.is_closed()

The correct answer is: file.closed

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

a. current()

b. locate()

c. position()

d. tell() ✓

The correct answer is: tell()

Question **6**

Correct

Mark 1.00 out of 1.00

What is the difference between r+ and w+ modes in file handling?

- a. r+ is for read and write without truncating, w+ is for read and write with truncating ✓
- b. r+ is for read and write, w+ is for append only
- c. r+ is for read and append, w+ is for read and write
- d. r+ is for binary read and write, w+ is for text read and write

The correct answer is: r+ is for read and write without truncating, w+ is for read and write with truncating

Question **7**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

- a. move the file pointer to beginning of the file
- b. move the file pointer five characters behind from the current position
- c. moves the file pointer to the end of a file
- d. move the file pointer five characters ahead from the current position ✓

The correct answer is:
move the file pointer five characters ahead from the current position

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

- a. truncate() ✓
- b. resize()
- c. shrink()
- d. reduce()

The correct answer is: truncate()

Question **9**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. end()
b. finish()
c. close() ✓
d. terminate()

The correct answer is: close()

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. fseek()
b. ftell()
c. tell()
d. seek() ✓

The correct answer is: seek()

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. An error is raised
b. Hello
c. world
d. Hello, world! ✓

The correct answer is: Hello, world!

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

a. It reads a single line from the file
b. It reads the entire file and returns it as a list of lines ✓
c. It reads the entire file and returns it as a string
d. It reads the file and returns it as a dictionary

The correct answer is: It reads the entire file and returns it as a list of lines

Question **13**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It clears the old data and starts fresh ✓
b. It does nothing
c. It raises an error
d. It appends data to the file

The correct answer is: It clears the old data and starts fresh

Question **14**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readline()
b. readlist()
c. read()
d. readlines() ✓

The correct answer is: readlines()

Question **15**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. 1

b. null

c. 0 ✓

d. 2

e. garbage

The correct answer is:
0