

Assignment-2

Name: Nithyasri P

Roll no: 23BTT029

Team-4

Innovative Hybrid Nano-Smart Barrier Fabrics for Chemical Protection in Textile Industries

INTRODUCTION:

In textile mills and chemical processing units, workers face severe risks from liquid chemical splashes, such as acids, alkalis, and solvents, which can cause rapid skin burns and long-term health issues. Barrier fabrics serve as the primary defense, preventing permeation through physical or chemical mechanisms. Traditional options like polyurethane films or expanded polytetrafluoroethylene (ePTFE) membranes physically block liquids via micropores or chemically resist penetration with fluoropolymers. However, these often compromise comfort and durability. This assignment explores limitations of existing solutions and proposes a quad-smart hybrid nano-fabric stack, inspired by biomimicry (lotus leaf self-cleaning and human skin adaptability), to deliver proactive protection. The design targets real-world mill use, emphasizing breathability $> 5000 \text{ g/m}^2/\text{day}$, self-maintenance, and costs under ₹30/m².

OBJECTIVES:

- Analyze shortcomings of conventional barrier fabrics.
- Develop a multi-layered smart fabric prototype using accessible nano-materials and roll-to-roll processing.
- Evaluate performance via standard tests (e.g., ASTM F903 for permeation, WVTR for breathability).

- Demonstrate 150% breathability gain, 300% service life extension, and 60% cost reduction for mill workers.

EXISTING SOLUTIONS:

Current barrier fabrics rely on dense polymers or microporous membranes:

- **Polyvinyl chloride (PVC) or neoprene laminates:** Provide full impermeability but zero breathability.
- **Microporous ePTFE (e.g., Gore-Tex equivalents):** Allows vapor transmission (3000+ g/m²/day) via 0.2-μm pores, repelling liquids > 140° contact angle.

These are applied via coating, lamination, or dipping on cotton/nylon bases, common in protective suits (EN 14605 standard).

LIMITATIONS OF EXISTING SOLUTIONS:

- Traditional fabrics trap sweat (WVTR < 2000 g/m²/day), leading to heat stress—workers lose 1-2L fluid/hour in humid mills.
- Physical barriers tear easily (service life 10-15 exposures), with no damage detection.
- Chemical resistance fades after 10-20 washes due to hydrolysis or abrasion.
- High costs (₹50+/m²) and lack of adaptability mean frequent replacements, increasing downtime.
- No self-repair or alerts exacerbate risks, with permeation breakthrough times dropping below 1 hour for aggressive solvents.

PROPOSED SOLUTION: Quad-Smart Bio-Responsive Fabric Stack

Proposed a four-layer hybrid on recycled cotton (₹25/m² base), fabricated via low-cost dip-coat/spray on mill roll-to-roll lines (speed 20-50 m/min).

Total add-on: ₹5/m². Layers mimic skin functions:

- **Outer Layer:** Solar-Activated TiO₂ Nanocoat -Sol-gel spray of 20-50nm TiO₂ particles creates superhydrophobicity (contact angle 150°+).

Sunlight/UV generates radicals, degrading oils/acids to CO₂/H₂O in 2-4 hours. Durable 40+ washes (ASTM D543).

• **Sensor Layer:** Color-Shifting pH Indicators (₹0.50/m²) –

Microencapsulated halochromic dyes (e.g., methyl red derivatives) embedded in polymer matrix. Acids turn red (pH < 4), bases blue (pH > 10); detects heavy metals via chelation. Smartphone RGB scan quantifies exposure—no power needed.

• **Middle Layer:** Shape-Memory Polymer (SMP) Sealant (₹2/m²) –

Polyurethane SMP coating swells/stiffens 40-60% on chemical contact (2-5s response), sealing breaches via body heat (37°C) or splash exothermic reaction. Relaxes post-exposure.

• **Inner Layer:** Self-Healing Microcapsules (₹1/m²) – 5-200µm urea-formaldehyde shells with dicyclopentadiene (DCPD) monomer + Grubbs catalyst. Tears rupture capsules, polymerizing to seal holes (< 50µm) and neutralize phosphates/acids.

Processing: Dip base in SMP emulsion → dry → spray TiO₂ → embed sensors/capsules → cure at 80°C. Prototype testable on lab hot-press.

PERFORMANCE COMPARISON:

Metric	Traditional (ePTFE/PVC)	Quad-Smart Hybrid	Gain
Breathability (WVTR g/m ² /day)	1000-2000	3000-5000	+150%
Service Exposures	10-15	40-60	+300%
Permeation Breakthrough (min, 98% H ₂ SO ₄)	60-120	> 480	+400%
Self-Clean/Heal/Alerts	No	Yes	Full
Wash Durability (cycles)	20	40+	+100%

COST ANALYSIS:

- **Fabric Cost:** ₹30/m² (base ₹25 + add-ons ₹5) vs. ₹50-75/m² traditional.
- **Annual/Worker:** 10m² suit × 4/year = ₹1200 (hybrid, quarterly replace) vs. ₹3000 (monthly). This represents a 60% savings. Lifecycle: 4x exposures cut waste by 75%. ROI is achieved in 3 months for a 100-worker mill.

CONCLUSION:

This quad-smart hybrid fabric transforms passive barriers into adaptive shields, addressing chemical splash risks with breathable, self-maintaining intelligence. Feasible with standard nano-coating (TiO₂ from pigment suppliers, SMP from polymer labs), it boosts worker safety, cuts costs, and fits Industry 4.0 textile mills.

References

- [1] ASTM Standards F903, F739; Textile Research Journal (nano-coatings).
- [2] J. Mater. Chem. (SMP/self-healing).