Exp No:15 Experiment to understand the data preprocessing in Data science

AIM:

To understand the importance of Data preprocessing in data science.

PROGRAM:

```
import numpy as np
import pandas as pd
df = pd.read_csv("/content/drive/MyDrive/pre-process_datasample (2).csv")
df
df.info()
df.Country.mode()
df.Country.mode()[0]
type(df.Country.mode())
df.Country.fillna(df.Country.mode()[0], inplace=True)
df.Age.fillna(df.Age.median(), inplace=True)
df.Salary.fillna(round(df.Salary.mean()), inplace=True)
df
pd.get_dummies(df.Country)
updated_dataset = pd.concat([pd.get_dummies(df.Country), df.iloc[:, [1, 2, 3]]], axis=1)
updated_dataset
df.info()
updated_dataset.Purchased.replace(['No', 'Yes'], [0, 1], inplace=True)
updated_dataset
```

OUTPUT:

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes
5	France	35.0	58000.0	Yes
6	Spain	NaN	52000.0	No
7	France	48.0	79000.0	Yes
8	NaN	50.0	83000.0	No
9	France	37.0	67000.0	Yes

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column     Non-Null Count  Dtype
---  ------     --------------  -----
 0   Country    9 non-null      object
 1   Age        9 non-null      float64
 2   Salary     9 non-null      float64
 3   Purchased  10 non-null     object
dtypes: float64(2), object(2)
memory usage: 452.0+ bytes
```

	Country
0	France

dtype: object

```
'France'
```

```
pandas.core.series.Series
def __init__(data=None, index=None, dtype: Dtype |
None=None, name=None, copy: bool | None=None, fastpath:
bool | lib.NoDefault=lib.no_default) -> None
```

```
/usr/local/lib/python3.13/dist-packages/pandas/core/series
One-dimensional ndarray with axis labels (including time s

Labels need not be unique but must be a hashable type. The
supports both integer- and label-based indexing and provic
methods for performing operations involving the index  Sta
```

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	63778.0	Yes
5	France	35.0	58000.0	Yes
6	Spain	38.0	52000.0	No
7	France	48.0	79000.0	Yes
8	France	50.0	83000.0	No
9	France	37.0	67000.0	Yes

	France	Germany	Spain
0	True	False	False
1	False	False	True
2	False	True	False
3	False	False	True
4	False	True	False
5	True	False	False
6	False	False	True
7	True	False	False
8	True	False	False
9	True	False	False

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	No
1	False	False	True	27.0	48000.0	Yes
2	False	True	False	30.0	54000.0	No
3	False	False	True	38.0	61000.0	No
4	False	True	False	40.0	63778.0	Yes
5	True	False	False	35.0	58000.0	Yes
6	False	False	True	38.0	52000.0	No
7	True	False	False	48.0	79000.0	Yes
8	True	False	False	50.0	83000.0	No
9	True	False	False	37.0	67000.0	Yes

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column     Non-Null Count  Dtype
---  ------     --------------  -----
 0   Country    10 non-null     object
 1   Age        10 non-null     float64
 2   Salary     10 non-null     float64
 3   Purchased  10 non-null     object
dtypes: float64(2), object(2)
memory usage: 452.0+ bytes
```

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	0
1	False	False	True	27.0	48000.0	1
2	False	True	False	30.0	54000.0	0
3	False	False	True	38.0	61000.0	0
4	False	True	False	40.0	63778.0	1
5	True	False	False	35.0	58000.0	1
6	False	False	True	38.0	52000.0	0
7	True	False	False	48.0	79000.0	1
8	True	False	False	50.0	83000.0	0
9	True	False	False	37.0	67000.0	1

RESULT:

Thus we have successfully understood the importance of Data preprocessing in data science.