Assignment-3

Name-NITHYASHREE J J

Class-24CS4B

Reg No-732924CSR111

1. Display all records from the Employee table.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.

  CREATE TABLE Employees (EmpID INT PRIMARY KEY,Name VARCHAR(50),Department VARCHAR(50),Salary
INT,City VARCHAR(50));

INSERT INTO Employees VALUES
(101, 'kani', 'IT', 50000, 'Chennai'),
(102, 'karthi', 'HR', 45000, 'Bangalore'),
(103, 'KV', 'IT', 60000, NULL),
(104, 'nithya', 'Finance', 55000, 'Chennai'),
(105, 'paarkavi', 'HR', 40000, 'Coimbatore');

SELECT * FROM Employees;
```

Output

EmpID	Name	Department	Salary	City
101	kani	IT	50000	Chennai
102	karthi	HR	45000	Bangalore
103	KV	IT	60000	
104	nithya	Finance	55000	Chennai
105	paarkavi	HR	40000	Coimbatore

2. Display only the Name and Salary of employees

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT Name, Salary FROM Employees;
```

Output

Name	Salary
kani	50000
karthi	45000
KV	60000
nithya	55000
paarkavi	40000

3. Display employees whose salary is greater than 50,000.

Input

Run SQL

```
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees WHERE Salary > 50000;
```

Output

EmpID	Name	Department	Salary	City
103	KV	IT	60000	
104	nithya	Finance	55000	Chennai

4. Display employees who belong to the IT department.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE Department = 'IT';
```

Output

EmpID	Name	Department	Salary	City
101	kani	IT	50000	Chennai
103	KV	IT	60000	

5. Display employees whose city is Chennai.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE City = 'Chennai';
```

Output

EmpID	Name	Department	Salary	City
101	kani	IT	50000	Chennai
104	nithya	Finance	55000	Chennai

6. Display employees whose salary is between 40,000 and 60,000.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE Salary BETWEEN 40000 AND 60000;
```

Output

EmpID	Name	Department	Salary	City
101	kani	IT	50000	Chennai
102	karthi	HR	45000	Bangalore
103	KV	IT	60000	
104	nithya	Finance	55000	Chennai
105	paarkavi	HR	40000	Coimbatore

7. Display distinct departments from the Employee table.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT DISTINCT Department FROM Employees;
```

Output

Department
IT
HR
Finance

8. Display employees whose City value is NULL

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE City IS NULL;
```

Output

EmpID	Name	Department	Salary	City
103	KV	IT	60000	

9. Find the total salary paid to all employees.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT SUM(Salary) FROM Employees;
```

Output

SUM(Salary)
250000

10. Find the average salary of employees in the IT department

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT AVG(Salary)
FROM Employees
WHERE Department = 'IT';
```

Output

AVG(Salary)
55000

11. Count the number of employees in each department using GROUP BY.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT AVG(Salary)
FROM Employees
WHERE Department = 'IT';
```

Output

AVG(Salary)
55000

12. Display employees whose salary is greater than the average salary (nested subquery).

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT Department, COUNT(*)
FROM Employees
GROUP BY Department;
```

Output

Department	COUNT(*)
Finance	1
HR	2
IT	2

13. Write an SQL statement to insert a new employee record.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT Department, COUNT(*)
FROM Employees
GROUP BY Department;
```

Output

Department	COUNT(*)
Finance	1
HR	2
IT	2

14. Write an SQL query to update the salary of employee with EmpID = 105 to 48000.

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE Salary > (SELECT AVG(Salary) FROM Employees);
```

Output

EmpID	Name	Department	Salary	City
103	KV	IT	60000	
104	nithya	Finance	55000	Chennai

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.

INSERT INTO Employee VALUES(106, 'divya', 'IT', 52000, 'Madurai');
SELECT * FROM Employee;
```

Output

Employee

EmpID	Name	Department	Salary	City
101	kani	IT	50000	Chennai
102	karthi	HR	45000	Bangalore
103	KV	IT	60000	
104	nithya	Finance	55000	Chennai
105	paarkavi	HR	40000	Coimbatore
106	divya	IT	52000	Madurai

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.

UPDATE Employee
SET Salary = 48000
WHERE EmpID = 105;
select * from Employee;
```

Output

EmpID	Name	Department	Salary	City
101	kani	IT	50000	Chennai
102	karthi	HR	45000	Bangalore
103	KV	IT	60000	
104	nithya	Finance	55000	Chennai
105	paarkavi	HR	48000	Coimbatore
106	divya	IT	52000	Madurai