

## Configuring add-ons in Istio:

There are many add-ons available for Istio. For example:

1. [Prometheus](#)
2. [Grafana](#)
3. [Zipkin](#)
4. [Jaeger](#)
5. [Service Graph](#)

### Exposing services:

Istio add-on services are deployed by default as **ClusterIP** type services. We can expose the services outside the cluster by either changing the Kubernetes service type to **NodePort** or **LoadBalancer** or by port-forwarding or by configuring Kubernetes Ingress.

Here, we briefly explain the NodePort and port-forwarding ways of exposing services.

#### **Option 1: Expose services with NodePort**

To expose them using NodePort service type, we can edit the services and change the service type from ClusterIP to NodePort:

```
kubectl -n istio-system edit svc prometheus
kubectl -n istio-system edit svc grafana
kubectl -n istio-system edit svc servicegraph
```

For Jaeger, either of tracing or jaeger-query can be exposed.

```
kubectl -n istio-system edit svc tracing
```

Once this is done the services will be assigned dedicated ports on the hosts.

To find the assigned ports for Grafana:

```
kubectl -n istio-system get svc grafana
```

Once this is done the services will be assigned dedicated ports on the hosts.

To find the assigned ports for Grafana:

```
kubectl -n istio-system get svc grafana
```

To find the assigned ports for Prometheus:

```
kubectl -n istio-system get svc prometheus
```

To find the assigned ports for Servicegraph:

```
kubectl -n istio-system get svc servicegraph
```

To find the assigned ports for Jaeger:

```
kubectl -n istio-system get svc tracing
```

## Option 2: Expose services with port-forwarding

To port-forward Grafana:

```
kubectl -n istio-system port-forward $(kubectl -n istio-system get pod  
-l app=grafana \  
-o jsonpath='{.items[0].metadata.name}') 3000:3000 &
```

To port-forward Prometheus:

```
kubectl -n istio-system port-forward \  
$(kubectl -n istio-system get pod -l app=prometheus -o  
jsonpath='{.items[0].metadata.name}') \  
9090:9090 &
```

To port-forward Service Graph:

```
kubectl -n istio-system port-forward \  
  $(kubectl -n istio-system get pod -l app=servicegraph -o  
jsonpath='{.items[0].metadata.name}') \  
  8088:8088 &
```

To port-forward Jaeger:

```
kubectl -n istio-system port-forward \  
  $(kubectl -n istio-system get pod -l app=jaeger -o  
jsonpath='{.items[0].metadata.name}') \  
  16686:16686 &
```

Port-forwarding runs in the foreground. We have appended & to the end of the above 2 commands to run them in the background. If you do not want this behavior, please remove the & from the end.

### **Accessing Exposed Services:**

once a port is exposed, you can access the service from local host:

`http://localhost:<port-number>`