

AI Matches with Odds API Documentation

This document describes the API endpoints for fetching matches with odds data for AI mapping purposes. All endpoints support pagination and return optimized, fast responses.

Table of Contents

- [Overview](#)
 - [Endpoints](#)
 - [Get Bet365 Matches with Odds \(Unmapped\)](#)
 - [Get OddsPortal Matches with Odds \(Unmapped\)](#)
 - [Get Bet365 Matches with Odds \(Mapped\)](#)
 - [Common Features](#)
 - [Response Format](#)
 - [Error Handling](#)
 - [Performance Notes](#)
 - [Examples](#)
-

Overview

These APIs are designed for AI mapping systems to fetch matches with their associated odds data. The endpoints are optimized for performance with:

- **Pagination:** Default 10 matches per page (configurable)
 - **Optimized Queries:** Pagination happens before expensive lookups
 - **Fast Response Times:** Typically 200-500ms depending on dataset size
 - **Filtered Results:** Only returns matches relevant for mapping (unmapped or mapped based on endpoint)
-

Endpoints

1. Get Bet365 Matches with Odds (Unmapped)

Fetches Bet365 matches that are **not mapped** to OddsPortal, along with their odds data.

Endpoint: `GET https://sports-bet-api.allinsports.online/api/matches/get-bet365-matches-with-odds`

Description:

- Returns Bet365 matches that don't have an `oddsportal_mapped_id`
- Excludes live matches(`time_status != "1"`)
- Results sorted by `commence_time` in descending order (newest first)
- Includes full odds data for each match

Query Parameters:

Parameter	Type	Required	Default	Description
<code>page</code>	integer	No	1	Page number for pagination (minimum: 1)
<code>limit</code>	integer	No	10	Number of matches per page (minimum: 1, maximum: 100)

Example Request:

`GET https://sports-bet-api.allinsports.online/api/matches/get-bet365-matc`

Example Response:

```
{
  "status": true,
  "message": "Matches fetched successfully",
  "data": {
    "totalCount": 150,
    "limit": 10,
    "page": 1,
    "totalPages": 15,
    "previousPage": null,
    "nextPage": 2,
    "rows": [
      {
        "id": "12345678",
        "home_team": "Team A",
        "away_team": "Team B",
        "home_team_details": {},
        "away_team_details": {},
        "league": {
          "id": "league123",
```

```

      "name": "Premier League"
    },
    "commence_time": 1704067200,
    "sport_id": "1",
    "sport": "Soccer",
    "platform": "BET365",
    "time_status": "0",
    "odds": [
      {
        "event_id": "12345678",
        "platform": "BET365",
        "key": "moneyline",
        "outcomes": [
          {
            "name": "Team A",
            "price": 2.5
          },
          {
            "name": "Draw",
            "price": 3.2
          },
          {
            "name": "Team B",
            "price": 2.8
          }
        ]
      }
    ]
  }
]
}

```

2. Get OddsPortal Matches with Odds (Unmapped)

Fetches OddsPortal matches that are **not mapped** to Bet365, along with their odds data.

Endpoint: GET <https://sports-bet-api.allinsports.online/api/matches/get-odds-portal-matches-with-odds>

Description:

- Returns OddsPortal matches that don't have a `bet365_mapped_id`

- Excludes live matches(`time_status != "1"`)
- Results sorted by `commence_time` in descending order (newest first)
- Includes full odds data for each match

Query Parameters:

Parameter	Type	Required	Default	Description
<code>page</code>	integer	No	1	Page number for pagination (minimum: 1)
<code>limit</code>	integer	No	10	Number of matches per page (minimum: 1, maximum: 100)

Example Request:

```
GET https://sports-bet-api.allinsports.online/api/matches/get-odds-portal
```

Example Response:

```
{
  "status": true,
  "message": "Matches fetched successfully",
  "data": {
    "totalCount": 200,
    "limit": 10,
    "page": 1,
    "totalPages": 20,
    "previousPage": null,
    "nextPage": 2,
    "rows": [
      {
        "id": "87654321",
        "home_team": "Team C",
        "away_team": "Team D",
        "home_team_details": {},
        "away_team_details": {},
        "league": {
          "id": "league456",
          "name": "La Liga"
        },
        "commence_time": 1704153600,
        "sport_id": "1",
        "sport": "Soccer",
        "platform": "ODDSPORTAL",
```

```
{
  "time_status": "0",
  "odds": [
    {
      "event_id": "87654321",
      "key": "1x2",
      "outcomes": [
        {
          "name": "Team C",
          "price": 1.8
        },
        {
          "name": "Draw",
          "price": 3.5
        },
        {
          "name": "Team D",
          "price": 4.2
        }
      ]
    }
  ]
}
```

3. Get Bet365 Matches with Odds (Mapped)

Fetches Bet365 matches that are **already mapped** to OddsPortal, along with their odds data.

Endpoint: GET <https://sports-bet-api.allinsports.online/api/matches/get-bet365-matches-with-odds-and-mapped>

Description:

- Returns Bet365 matches that have an `oddsportal_mapped_id` (already mapped)
- Excludes live matches(`time_status != "1"`)
- Results sorted by `commence_time` in descending order (newest first)
- Includes full odds data and the mapped OddsPortal match ID

Query Parameters:

Parameter	Type	Required	Default	Description
-----------	------	----------	---------	-------------

Parameter	Type	Required	Default	Description
page	integer	No	1	Page number for pagination (minimum: 1)
limit	integer	No	10	Number of matches per page (minimum: 1, maximum: 100)

Example Request:

GET https://sports-bet-api.allinsports.online/api/matches/get-bet365-matches

Example Response:

```
{
  "status": true,
  "message": "Matches fetched successfully",
  "data": {
    "totalCount": 500,
    "limit": 10,
    "page": 1,
    "totalPages": 50,
    "previousPage": null,
    "nextPage": 2,
    "rows": [
      {
        "id": "12345678",
        "home_team": "Team A",
        "away_team": "Team B",
        "home_team_details": {},
        "away_team_details": {},
        "league": {
          "id": "league123",
          "name": "Premier League"
        },
        "commence_time": 1704067200,
        "sport_id": "1",
        "sport": "Soccer",
        "platform": "BET365",
        "time_status": "0",
        "oddsportal_mapped_id": "87654321",
        "odds": [
          {
            "event_id": "12345678",
            "platform": "BET365",
            "odds": {
              "1": 1.5,
              "2": 2.5,
              "X": 3.5
            }
          }
        ]
      }
    ]
  }
}
```

```
    "key": "moneyline",
    "outcomes": [
      {
        "name": "Team A",
        "price": 2.5
      },
      {
        "name": "Draw",
        "price": 3.2
      },
      {
        "name": "Team B",
        "price": 2.8
      }
    ]
  }
]
}
```

Common Features

Pagination

All endpoints support pagination with the following metadata:

- **totalCount**: Total number of matches available
- **limit**: Number of items per page
- **page**: Current page number
- **totalPages**: Total number of pages
- **previousPage**: Previous page number (null if on first page)
- **nextPage**: Next page number (null if on last page)

Filtering

- **Time Status**: Only returns matches where `time_status != "1"` (excludes live matches)
- **Mapping Status**:
 - Unmapped endpoints: Returns matches without mapping IDs
 - Mapped endpoint: Returns matches with mapping IDs

Sorting

All results are sorted by `commence_time` in **descending order** (newest matches first).

Response Format

Success Response

All endpoints return a consistent response format:

```
{
  "status": true,
  "message": "Matches fetched successfully",
  "data": {
    "totalCount": <integer>,
    "limit": <integer>,
    "page": <integer>,
    "totalPages": <integer>,
    "previousPage": <integer | null>,
    "nextPage": <integer | null>,
    "rows": [
      {
        // Match object with odds
      }
    ]
  }
}
```

Match Object Structure

Each match in the `rows` array contains:

Field	Type	Description
<code>id</code>	string	Match unique identifier
<code>home_team</code>	string	Home team name
<code>away_team</code>	string	Away team name
<code>home_team_details</code>	object	Home team details object

Field	Type	Description
away_team_details	object	Away team details object
league	object	League information object
commence_time	integer	Match start time (Unix timestamp)
sport_id	string	Sport identifier
sport	string	Sport name
platform	string	Platform name (BET365, ODDSPORTAL, etc.)
time_status	string	Match status ("0"=upcoming, "1"=live, "3"=ended)
oddsportal_mapped_id	string	(Mapped endpoint only) Mapped OddsPortal match ID
odds	array	Array of odds data objects

Error Handling

500 Internal Server Error

If an error occurs during processing:

```
{
  "status": false,
  "message": "Internal server error"
}
```

HTTP Status Code: 500

Performance Notes

Optimization Features

- Pagination Before Lookup:** Matches are filtered, sorted, and paginated **before** fetching odds data. This means only 10 matches (or your specified limit) have their odds fetched, not all matches in the database.
- Efficient Queries:** Uses MongoDB aggregation pipelines with:

- Indexed field filtering (`time_status` , `oddsportal_mapped_id` , `bet365_mapped_id`)
- Early sorting on indexed `commence_time` field
- `$facet` for parallel count and data retrieval

3. **Field Projection:** Only necessary fields are returned, reducing data transfer size.

4. **In-Memory Operations:** Uses `allowDiskUse(false)` for faster in-memory operations when possible.

Expected Performance

- **Small datasets** (< 1000 matches): 100-200ms
- **Medium datasets** (1000-10000 matches): 200-400ms
- **Large datasets** (> 10000 matches): 400-800ms

Performance may vary based on:

- Database size
- Network latency
- Server load
- Index availability

Recommended Indexes

For optimal performance, ensure these indexes exist:

```
// Bet365 Matches
{ time_status: 1, oddsportal_mapped_id: 1, commence_time: -1 }
{ time_status: 1, commence_time: -1 }

// OddsPortal Matches
{ time_status: 1, bet365_mapped_id: 1, commence_time: -1 }
{ time_status: 1, commence_time: -1 }

// Odds Collections
{ event_id: 1, platform: 1 }
```

Examples

Example 1: Get First Page of Unmapped Bet365 Matches

```
curl -X GET "https://sports-bet-api.allinsports.online/api/matches/get-be
```

Example 2: Get Second Page with 20 Matches

```
curl -X GET "https://sports-bet-api.allinsports.online/api/matches/get-be
```

Example 3: Get Unmapped OddsPortal Matches

```
curl -X GET "https://sports-bet-api.allinsports.online/api/matches/get-oc
```

Example 4: Get Mapped Bet365 Matches

```
curl -X GET "https://sports-bet-api.allinsports.online/api/matches/get-be
```

Example 5: Using JavaScript/TypeScript

```
// Fetch unmapped Bet365 matches
const response = await fetch(
  'https://sports-bet-api.allinsports.online/api/matches/get-bet365-match
');
const data = await response.json();

console.log(`Total matches: ${data.data.totalCount}`);
console.log(`Current page: ${data.data.page}`);
console.log(`Matches on this page: ${data.data.rows.length}`);

// Process each match
data.data.rows.forEach(match => {
  console.log(`${match.home_team} vs ${match.away_team}`);
  console.log(`Odds count: ${match.odds.length}`);
});
```

Example 6: Pagination Loop

```
async function fetchAllUnmappedMatches() {
  let page = 1;
  let allMatches = [];
  let hasMore = true;

  while (hasMore) {
    const response = await fetch(
      `https://sports-bet-api.allinsports.online/api/matches/get-bet365-n
    );
    const data = await response.json();

    allMatches = allMatches.concat(data.data.rows);
    hasMore = data.data.nextPage !== null;
    page = data.data.nextPage || page + 1;

    // Optional: Add delay to avoid overwhelming the server
    await new Promise(resolve => setTimeout(resolve, 100));
  }

  return allMatches;
}
```

Notes

- All endpoints return matches sorted by `commence_time` in descending order (newest first)
 - Live matches (`time_status = "1"`) are excluded from all results
 - The `limit` parameter has a maximum value of 100 for performance reasons
 - Empty result sets will return `rows: []` with `totalCount: 0`
 - The `odds` array may be empty if no odds data exists for a match
-

Support

For issues or questions, please contact the development team or refer to the main API documentation.