

NScAPICode

Generated by Doxygen 1.7.3

Tue Feb 5 2013 12:26:07

Contents

1	Class Index	1
1.1	Class List	1
2	Class Documentation	3
2.1	apisamplecode.APISampleCode Class Reference	3
2.1.1	Detailed Description	3
2.1.2	Member Function Documentation	3
2.1.2.1	main	3
2.2	apisamplecode.NScAPIWrapper Class Reference	3
2.2.1	Detailed Description	4
2.2.2	Constructor & Destructor Documentation	4
2.2.2.1	NScAPIWrapper	4
2.2.3	Member Function Documentation	4
2.2.3.1	getCustomerDetails	4
2.2.3.2	getShippingAndTax	4
2.2.3.3	getShippingOptions	5
2.2.3.4	getTaxForAnOrder	5
2.2.3.5	getUserID	5
2.2.3.6	insertWebOrders	5

Chapter 1

Class Index

1.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

apisamplecode.APISampleCode	3
apisamplecode.NScAPIWrapper	3

Chapter 2

Class Documentation

2.1 apisamplecode.APISampleCode Class Reference

Static Public Member Functions

- static void [main](#) (String[] args)

2.1.1 Detailed Description

Author

franclin

2.1.2 Member Function Documentation

2.1.2.1 static void apisamplecode.APISampleCode.main (String[] *args*) [static]

Parameters

<i>args</i>	the command line arguments
-------------	----------------------------

The documentation for this class was generated from the following file:

- src/apisamplecode/APISampleCode.java

2.2 apisamplecode.NScAPIWrapper Class Reference

Public Member Functions

- [NScAPIWrapper](#) (String key, String userid, String webstoreUrl)
- String [getUserID](#) ()
- void [getCustomerDetails](#) (String email)

- void [getShippingOptions](#) (HashMap parameters)
- void [getShippingAndTax](#) (HashMap parameters)
- void [getTaxForAnOrder](#) (HashMap parameters)
- void [insertWebOrders](#) (HashMap parameters)

2.2.1 Detailed Description

Author

francin

Date

04/02/2013

2.2.2 Constructor & Destructor Documentation

2.2.2.1 `apisamplecode.NScAPIWrapper.NScAPIWrapper (String key, String userid, String webstoreUrl)`

This is the constructor of the class Three parameters are needed to build an object of this type

Parameters

<i>key</i>	this represents your private. You should contact the NitroSell Support Team to request one.
<i>userid</i>	this represents your User ID as assigned by the retailer to which you would like to query his data
<i>webstoreUrl</i>	this is the URL of the WebStore that you would like to query

2.2.3 Member Function Documentation

2.2.3.1 `void apisamplecode.NScAPIWrapper.getCustomerDetails (String email)`

This method is the endpoint to get the customer details

Parameters

<i>email</i>	
--------------	--

2.2.3.2 `void apisamplecode.NScAPIWrapper.getShippingAndTax (HashMap parameters)`

This method is the endpoint to get the list of shipping options and any applicable tax
The parameters of the request are passed in parameters tables

Parameters

<i>parameters</i>	
-------------------	--

2.2.3.3 void apisamplecode.NScAPIWrapper.getShippingOptions (HashMap *parameters*)

This method is the endpoint to get the list of shipping options The parameters of the request are passed in parameters tables

Parameters

<i>parameters</i>	
-------------------	--

2.2.3.4 void apisamplecode.NScAPIWrapper.getTaxForAnOrder (HashMap *parameters*)

This method is the endpoint to get the tax for a given order The parameters of the request are passed in parameters tables

Parameters

<i>parameters</i>	
-------------------	--

2.2.3.5 String apisamplecode.NScAPIWrapper.getUserID ()

This method returns the user ID

Returns**2.2.3.6 void apisamplecode.NScAPIWrapper.insertWebOrders (HashMap *parameters*)**

This method is the endpoint to insert an order into the WebStore The parameters of the request are passed in parameters tables

Parameters

<i>parameters</i>	
-------------------	--

The documentation for this class was generated from the following file:

- src/apisamplecode/NScAPIWrapper.java

Index

- apisamplecode::APISampleCode, [3](#)
 - main, [3](#)
- apisamplecode::NScAPIWrapper, [3](#)
 - getCustomerDetails, [4](#)
 - getShippingAndTax, [4](#)
 - getShippingOptions, [5](#)
 - getTaxForAnOrder, [5](#)
 - getUserID, [5](#)
 - insertWebOrders, [5](#)
 - NScAPIWrapper, [4](#)
- getCustomerDetails
 - apisamplecode::NScAPIWrapper, [4](#)
- getShippingAndTax
 - apisamplecode::NScAPIWrapper, [4](#)
- getShippingOptions
 - apisamplecode::NScAPIWrapper, [5](#)
- getTaxForAnOrder
 - apisamplecode::NScAPIWrapper, [5](#)
- getUserID
 - apisamplecode::NScAPIWrapper, [5](#)
- insertWebOrders
 - apisamplecode::NScAPIWrapper, [5](#)
- main
 - apisamplecode::APISampleCode, [3](#)
- NScAPIWrapper
 - apisamplecode::NScAPIWrapper, [4](#)