HDOC DAY-74

1. Create an enumeration for months and print how many days each month has.
    a. Input: FEB
    b. Output: 28 or 29 days
2. Define an enumeration with SUCCESS, FAILURE, and TIMEOUT, and print messages accordingly.
    a. Input: FAILURE
    b. Output: Operation Failed

Algorithm

1. Start.
2. Define an enumeration Month containing JAN to DEC.
3. Declare a variable month of type enum Month.
4. Assign FEB to month.
5. Use a switch statement to check the month.
6. For January, March, May, July, August, October, and December, print 31 days.
7. For April, June, September, and November, print 30 days.
8. For February, print 28 or 29 days.
9. Stop.

- # C Program:

```
#include <stdio.h>

enum Month {
    JAN, FEB, MAR, APR, MAY, JUN,
    JUL, AUG, SEP, OCT, NOV, DEC
};

int main() {
    enum Month month = FEB;

    switch (month) {
```

```
        case JAN:
        case MAR:
        case MAY:
        case JUL:
        case AUG:
        case OCT:
        case DEC:
          printf("31 days");
          break;

        case APR:
        case JUN:
        case SEP:
        case NOV:
          printf("30 days");
          break;

        case FEB:
          printf("28 or 29 days");
          break;
    }

    return 0;
}
```

Test Cases:

Input	Expected Output
JAN	31 Days
FEB	28 or 29 Days
APR	30 Days
JUL	31 Days
NOV	30 Days
DEC	31 Days

Compilation and Execution:

The Following test cases has been compiled and executed successfully.



- **Algorithm**
  1. Start.
  2. Define an enumeration Status containing SUCCESS, FAILURE, and TIMEOUT.
  3. Declare a variable status of type enum Status.
  4. Assign FAILURE to status.
  5. Use a switch statement to check the status.
  6. If SUCCESS, print Operation Successful.
  7. If FAILURE, print Operation Failed.
  8. If TIMEOUT, print Operation Timed Out.
  9. Stop.

- **C Program:**

```
#include <stdio.h>

enum Status {
    SUCCESS,
    FAILURE,
    TIMEOUT
};

int main() {
    enum Status status = FAILURE;

    switch (status) {
        case SUCCESS:
            printf("Operation Successful");
            break;

        case FAILURE:
            printf("Operation Failed");
            break;

```

```
        case TIMEOUT:
            printf("Operation Timed Out");
            break;
    }

    return 0;
}
```

Test Cases:

Input	Expected Output
SUCCESS	Operation Successful
FAILURE	Operation Failed
TIMEOUT	Operation Timed Out

Compilation and Execution:

The following test case has been compiled and executed successfully.

