

Hybrid Camera Pose Estimation

Wenjie Niu

July 2nd, 2018

Abstract

This paper aims to solve the pose estimation problem of calibrated pinhole and generalized cameras w.r.t. a Structure-from-Motion (SfM) model by leveraging both 2D-3D correspondences as well as 2D-2D correspondences. While traditional approaches either focus on the use of 2D-3D matches, known as structure-based pose estimation or solely on 2D-2D matches (structure-less pose estimation).




Figure 1. Visualization of 2D-2D matches (pink) and 2D-3D matches (blue) used by one of our hybrid pose solvers. The query camera is represented in red and SfM cameras in green.[1]

1. Introduction

Camera pose estimation, *i.e.*, estimating the position and orientation of a given image, is a central step in 3D computer vision approaches such as SfM [6], Simultaneous Localization and Mapping (SLAM) [3], and visual localization [2]. In addition, camera pose estimation plays an important role in applications such as selfdriving cars [4] and augmented reality [5].

The availability of both structure-based and structureless camera pose estimation techniques leads to a set of interesting questions: Are they mutually exclusive, *i.e.*, is one always preferable over the other, or is there value in using both 2D-3D and 2D-2D matches for pose estimation? Is it

best to use pure solvers, *i.e.*, solvers that use either 2D-3D or 2D-2D correspondences, or do hybrid solvers (*c.f.* Fig. 1) using both type of matches improve pose estimation performance? Should one decide prior to RANSAC which solver to use, or is it best to select solvers in a data-driven way during RANSAC-based pose estimation?

2. Hybrid RANSAC for Pose Estimation

RANSAC variant stops when at least one solver s has been chosen K_s times, as this means that a good solution for the current inlier ratios has been found with probability P .

3. Conclusions

This paper have posed the question whether camera pose estimation can be improved by using both 2D-2D and 2D-3D matches. To answer this, we have developed a novel framework for camera pose estimation that jointly uses different minimal solvers within a new Hybrid RANSAC scheme.

Acknowledgements. This research was funded by Google.

References

- [1] F. Camposeco, A. Cohen, M. Pollefeys, and T. Sattler. Hybrid camera pose estimation. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2018. 1
- [2] F. Camposeco, T. Sattler, A. Cohen, A. Geiger, and M. Pollefeys. Toroidal constraints for two-point localization under high outlier ratios. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2017. 1
- [3] A. J. Davison, I. D. Reid, N. D. Molton, and O. Stasse. Monoslam: Real-time single camera SLAM. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 29(6):1052–1067, 2007. 1
- [4] C. Hne, L. Heng, G. H. Lee, F. Fraundorfer, P. Furgale, T. Sattler, and M. Pollefeys. 3D visual perception for self-driving cars using a multi-camera system: Calibration, mapping, localization, and obstacle detection. *Image and Vision Computing*, 68:14 – 27, 2017. 1

- [5] S. Middelberg, T. Sattler, O. Untzelmann, and L. Kobbelt. Scalable 6-dof localization on mobile devices. In *European Conference on Computer Vision*, 2014. [1](#)
- [6] A. Sameer, S. Noah, S. Ian, M. S. Steven, and R. Szeliski. Building rome in a day. In *IEEE International Conference on Computer Vision*, 2009. [1](#)