

● JANUARY 2026 SERIES

FROM GO BUILD TO GO RUN

GOLANG 2026 - NIV RAVE

#22

ERROR HANDLING - WRAPPING & CONTEXT

DON'T JUST RETURN THE ERROR; ADD VALUE TO IT





The %w Verb

Preserving the Chain

Since Go 1.13, we use *fmt.Errorf* with the %w verb to wrap an error. This adds context while preserving the original error for inspection.



```
func LoadConfig(path string) error {  
    file, err := os.Open(path)  
    if err != nil {  
        // %w wraps the error, allowing callers to unwrap it later  
        return fmt.Errorf("config: open %s: %w", path, err)  
    }  
    defer file.Close()  
    return nil  
}
```

Wrapping creates a "Logical Stack Trace." It tells a story: "Config failed" because "Open failed" because "Permission denied."





Checking the Chain (*errors.Is*)

Detecting Specific Sentinels

Never use `==` to check a wrapped error. It will fail. Use *errors.Is*, which recursively unwraps the chain to find a match.



```
err := LoadConfig("config.yaml")

// errors.Is looks deep into the wrapping layers
if errors.Is(err, os.ErrNotExist) {
    // We can handle 'missing file' differently than 'permission denied'
    return createDefaultConfig()
}
```



Retrieving Types (*errors.As*)

Extracting Detailed Context

If you need to access fields on a custom error struct hidden inside a chain, use *errors.As*.

```
var perr *os.PathError
if errors.As(err, &perr) {
    // Now we have access to the Path, Op, and Err fields of PathError
    fmt.Printf("Operation %s failed on path %s", perr.Op, perr.Path)
}
```

Golden Rule: Use *As* when you need the "Why" (metadata), and *Is* when you only need the "What" (identity).



The "Handle or Return" Rule

Stop Double-Logging

A common junior mistake is logging an error and then returning it. This leads to 5 identical log entries for one single failure.

The Senior Strategy:

- **Option A:** Handle the error (log it and stop the process).
- **Option B:** Wrap it and return it (add context for the next guy).

ONE FAILURE = ONE LOG ENTRY





Multi-Errors (*errors.Join*)

Handling Multiple Failures (Go 1.20+)

Sometimes you run multiple operations (like closing 3 different resources) and want to collect all errors instead of just the first one.



```
var errs error
errs = errors.Join(closeDB(), closeRedis(), closeFile())

if errs != nil {
    return errs // Contains all non-nil errors formatted together
}
```

Benefit: *errors.Is* and *errors.As* work on joined errors too! They will search through every error in the collection.





Concurrent Errors (*errgroup*)

Concurrency-Safe Error Handling

When running goroutines in parallel, *sync.WaitGroup* isn't enough because it doesn't handle errors. Use golang.org/x/sync/errgroup.



```
g, ctx := errgroup.WithContext(mainCtx)

for _, url := range urls {
    url := url // avoid closure capture bug
    g.Go(func() error {
        return fetch(ctx, url)
    })
}

// Wait() returns the first error encountered by any goroutine
if err := g.Wait(); err != nil {
    return err
}
```



Privacy in Error Design

Error Sanitization (Internal vs External)



A database connection string or a SQL syntax error should never be sent to a client. It's a security risk.

The Pattern: Wrap internally for your logs, but use a "Sanitizer" at the API edge.

We would:

- Internal: `fmt.Errorf("db update failed for user %d: %w", id, queryErr)`
External: `{"error": "Update failed. Please try again."}`

Error Flow: From Database to Sanitized API Response



Summary:

- Use %w for history, ls/As for inspection.
- Use errors.Join and errgroup for complex flows.
- Add context at every layer, log only once at the top.
-

Have an errorless day :)

