

● JANUARY 2026 SERIES

# FROM GO BUILD TO GO RUN

GOLANG 2026 - NIV RAVE

## #23

# TESTING PHILOSOPHY - THE "GO" WAY

HIGH COVERAGE != HIGH QUALITY





# Package-Level Testing

## The *\_test.go* Contract

Go's file naming isn't just a convention; it's an Encapsulation Strategy. You decide the visibility of your test suite based on the package declaration:

- **Internal** (*package service*): Tests have "God Mode" access to unexported types and private logic. Use this for deep unit testing of complex internal algorithms.
- **External** (*package service\_test*): Tests only the public API. This is the Gold Standard for black-box testing.

### The Senior Take:

- **Minimize Brittleness:** 80% of your tests should be *package\_test*. Testing internals makes refactoring a nightmare; testing the public contract allows internal change without breaking the suite.
- **API Ergonomics:** If a feature is hard to test from a *\_test* package, your API is likely poorly designed. Use external tests as a "First Customer" feedback loop.
- **No Circular Imports:** External tests are compiled separately, making them the perfect place to test integrations without triggering import cycles.





# Table-Driven Tests

## Scaling Your Assertions

Don't write ten different test functions for one logic branch. Use a slice of anonymous structs to run "Table-Driven Tests."

```
func TestSplit(t *testing.T) {
    tests := []struct {
        name  string
        input string
        sep   string
        want  []string
    }{
        {"simple", "a/b/c", "/", []string{"a", "b", "c"}}, // 1st entry
        {"no sep", "abc", "/", []string{"abc"}},          // 2nd entry
        {"trailing", "a/", "/", []string{"a", ""}},        // 3rd entry
    }

    for _, tt := range tests {
        t.Run(tt.name, func(t *testing.T) {
            got := Split(tt.input, tt.sep)
            if !reflect.DeepEqual(got, tt.want) {
                t.Errorf("Split() = %v, want %v", got, tt.want)
            }
        })
    }
}
```







# Subtests and *t.Run*

## Granular Execution Control

Don't let one failure hide ten successes. Using *t.Run* creates hierarchical tests that offer better reporting and flexible execution.

- **Isolation:** Each subtest has its own setup/teardown logic and failure state.
- **Surgical Runs:** Run specific cases from the CLI without re-running the whole suite: `go test -run TestSplit/simple_case`
- **Parallelism:** Call *t.Parallel()* inside *t.Run* to speed up CPU-bound logic across all subtests.

### Failure Locality:

- Without subtests, a single panic in a loop kills the entire test function. With *t.Run*, you get a precise line number for the specific data set that failed.

### Dynamic Test Names:

- Use meaningful strings for subtest names (e.g., `fmt.Sprintf("input_%d", i)`) to make your CI logs searchable and readable for the whole team.

### Race Detection:

- Combining *t.Parallel()* with the `-race` flag is the fastest way to flush out concurrency bugs in complex logic.





# Orchestrating the Environment

## Lifecycle & *TestMain*

Unit tests should be stateless, but Integration Tests often require heavy lifting. *TestMain* is your package-level hook to manage expensive resources (DB containers, Mock Servers) once per suite, not once per test.

```
func TestMain(m *testing.M) {  
    // 1. Setup: Start Docker/Migrations  
    db := setupIntegrationEnv()  
  
    code := m.Run() // 2. Execute all TestXxx in package  
  
    // 3. Teardown: Clean up resources  
    db.Close()  
    os.Exit(code)  
}
```

**The "Flaky Test" Killer:** Use *TestMain* to ensure your local environment exactly matches your CI environment.

**Avoid Global Leakage:** If you use *TestMain*, ensure you aren't leaking state between individual tests. Use *t.Cleanup()* within specific tests for fine-grained resource disposal.





# Reducing Signal-to-Noise Ratio

## Assertion Helpers & *t.Helper()*

When a test fails at 3:00 AM, the log should point to the problem, not the utility. Using *t.Helper()* marks a function as an assertion wrapper, effectively "hiding" it from the failure stack trace.



```
func assertDeepEqual(t *testing.T, got, want any) {  
    t.Helper() // Shifts failure location to the caller's line  
    if !reflect.DeepEqual(got, want) {  
        t.Errorf("\nGot:  %v\nWant: %v", got, want)  
    }  
}
```

- **Actionable Failures:** A Senior focuses on the diff. Your helpers should output clean, formatted comparisons (using *go-cmp* or similar) so the dev can see exactly what changed in a complex struct.
- **DRY vs. Readability:** Don't over-abstract. If an assertion helper is used in only one place, it's probably better off as inline code to keep the test readable.







# Designing for Testability

## Architectural Decoupling

Testable code isn't a result of "writing more tests" – it's a result of Dependency Injection. If your logic instantiates its own database client, it's untestable.

### The Senior Shift:

- **Program to Interfaces:** Accept an *interface* (e.g., *Storer*), not a concrete struct (*\*sql.DB*).
- **Constructor Injection:** Pass dependencies in your *NewService* constructor. This allows you to inject "Mocks" or "Stubs" during testing with zero friction.





# The "Stability" Toolbox

## The CI/CD Defense Suite

*go test* is just the beginning. Use specific flags to ensure code is "Production Grade" before it even hits a PR review.

### The Power Commands:

- **-race**: Your most important tool. It instruments binaries to detect unsynchronized memory access. Non-negotiable for CI.
- **-count=1**: Bypasses the test cache. Use this when debugging flaky tests or hardware-dependent logic.
- **-v -failfast**: Stops the suite at the first failure. Perfect for local development to keep your "Red-Green-Refactor" loop tight.

### A key take:

**Total Coverage is a Lie**: 100% coverage often means you're testing the language, not the business logic. Focus on Branch Coverage for critical paths and Boundary Conditions.







# Tests are Code, too.

## The Cheat Sheet:

- *go test -v*: Verbose output.
- *go test -cover*: Quick coverage check.
- *go test -race*: Crucial. Detects data races (run this in CI!).
- *go test -count=1*: Bypass the test cache (force a fresh run).

**Tonight we go beyond unit tests:  
Benchmarks, Fuzzing, and Mocks.**

