



nivass@localhost:~



```
[nivass@localhost ~]$ ls
'\'
```

a	Desktop	four.sh	pc.c	rev.sh	Templates
ab	Documents	frogprog.c	Pictures	script.awk	third.sh
ab.awkl	Downloads	frokprog.c	program	scripts	val.awk
ab.c	emp.awk	id.awk	program.c	sec.awk	Videos
a.out	emp.txt	marks.awk	Public	second.sh	vj.awk
av.awk	fibo.sh	marks.txt	reader	sender	write
awk	fifth.sh	Music	reader.c	sender.c	writer
b	file.txt	opendir	rec	shell	writer.c
c	first.csv	opendir.c	receiver	shellscrp	
	fork	pari	receiver.c	shell.sh	
data.txt	fork.c	pc	reversenum	sixth.sh	

```
[nivass@localhost ~]$ vi format_program.c
[nivass@localhost ~]$ gcc format_program.c -o format_program
[nivass@localhost ~]$ ./format_program
This line executed twice
```



nivass@localhost:~



--- Parent Process ---

Parent Process Id (PID): 3996

Parent's parent process Id (PPID): 3832

It can be executed twice

This line executed twice

--- Child Process ---

Child process Id (PID): 3997

Parent process ID (PPID): 2587

Executing 'ls' command using execlp()

```
[nivass@localhost ~]$ '\'
```

	Desktop	format_program	parl	r	
receiver.c	shell.sh				
a	Documents	format_program.c	pc	reversenum	sixth.sh
ab	Downloads	four.sh	pc.c	rev.sh	Templates
ab.awk	emp.awk	frogprog.c	Pictures	script.awk	third.sh
ab.c	emp.txt	frokprog.c	program	scripts	val.awk
a.out	fibo.sh	id.awk	program.c	sec.awk	Videos
av.awk	fifth.sh	marks.awk	Public	second.sh	vj.awk
awk	file.txt	marks.txt	reader	sender	write
b	first.csv	Music	reader.c	sender.c	writer
c	fork	opendir	rec	shell	writer.c
data.txt	fork.c	opendir.c	receiver	shellscrp	



```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

int main() {
    int pid;

    pid = fork();

    printf("This line executed twice\n");

    if(pid == -1) {
        printf("Child process not created\n");
        exit(0);
    }
    else if(pid == 0) {
        printf("\n--- Child Process ---\n");
        printf("Child process Id (PID): %d\n", getpid());
        printf("Parent process ID (PPID): %d\n", getppid());
        printf("Executing 'ls' command using execlp()\n");

        execlp("ls", "ls", NULL);
    }
}
```

```
    execlp("ls", "ls", NULL);
}
else {
    printf("\n--- Parent Process ---\n");
    printf("Parent Process Id (PID): %d\n", getpid());
    printf("Parent's parent process Id (PPID): %d\n", getppid());
}

printf("It can be executed twice\n");

return 0;
```

```
}
```

```
-- INSERT --
```

33,1

Bot