

Rajalakshmi Engineering College

Name: Nivedhitha K
Email: 240701371@rajalakshmi.edu.in
Roll no: 240701371
Phone: 9790413580
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_CY

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

John is working on a project to manage and analyze the data from various sensors in a manufacturing plant. Each sensor provides a sequence of integer readings, and John needs to process this data to get some insights. He wants to implement a queue to handle these sensor readings efficiently. The requirements are as follows:

Enqueue Operations: Each sensor reading needs to be added to the circular queue. Average Calculation: Calculate and print the average of every pair of consecutive sensor readings. Sum Calculation: Compute the sum of all sensor readings. Even and Odd Count: Count and print the number of even and odd sensor readings.

Assist John in implementing the program.

Input Format

The first input line contains an integer n , which represents the number of sensor readings.

The second line contains n space-separated integers, each representing a sensor reading.

Output Format

The first line should print "Averages of pairs:" followed by the averages of every pair of consecutive sensor readings, separated by spaces.

The second line should print "Sum of all elements: " followed by the sum of all sensor readings.

The third line should print "Number of even elements: " followed by the count of even sensor readings.

The fourth line should print "Number of odd elements: " followed by the count of odd sensor readings.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

1 2 3 4 5

Output: Averages of pairs:

1.5 2.5 3.5 4.5 3.0

Sum of all elements: 15

Number of even elements: 2

Number of odd elements: 3

Answer

```
// You are using GCC
#include<stdio.h>
int main()
{
    int n;
    scanf("%d",&n);
```

```

int queue[n];
int sum=0,evenCount=0,oddCount=0;
for(int i=0;i<n;i++)
{
    scanf("%d",&queue[i]);
    sum+=queue[i];
    if(queue[i]%2==0)
        evenCount++;
    else
        oddCount++;
}
printf("Averages of pairs: ");
for (int i=0;i<n;i++)
{
    int next =(i+1)%n;
    float avg=(queue[i] + queue[next]) / 2.0;
    printf("%.1f ",avg);
}
printf("\n");
printf("sum of all elements: %d\n",sum);
printf("Number of even elements: %d\n",evenCount);
printf("Number of odd elements: %d\n",oddCount);
return 0;
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Saran is developing a simulation for a theme park where people wait in a queue for a popular ride.

Each person has a unique ticket number, and he needs to manage the queue using a linked list implementation.

Your task is to write a program for Saran that reads the number of people in the queue and their respective ticket numbers, enqueue them, and then calculate the sum of all ticket numbers to determine the total ticket value present in the queue.

Input Format

The first line of input consists of an integer N, representing the number of people in the queue.

The second line consists of N space-separated integers, representing the ticket numbers.

Output Format

The output prints an integer representing the sum of all ticket numbers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

2 4 6 7 5

Output: 24

Answer

```
// You are using GCC
#include<stdio.h>
int main()
{
    int n;
    scanf("%d",&n);
    int ticket,sum=0;
    for(int i=0;i<n;i++)
    {
        scanf("%d",&ticket);
        sum+=ticket;
    }
    printf("%d\n",sum);
    return 0;
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Manoj is learning data structures and practising queues using linked lists. His professor gave him a problem to solve. Manoj started solving the program but could not finish it. So, he is seeking your assistance in solving it.

The problem is as follows: Implement a queue with a function to find the Kth element from the end of the queue.

Help Manoj with the program.

Input Format

The first line of input consists of an integer N, representing the number of elements in the queue.

The second line consists of N space-separated integers, representing the queue elements.

The third line consists of an integer K.

Output Format

The output prints an integer representing the Kth element from the end of the queue.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
2 4 6 7 5
3

Output: 6

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct Node{
    int data;
```

```

    struct Node*next;
}
struct Node*createNode(int data)
{
    struct Node*newNode=(struct Node*)malloc(sizeof(struct Node));
    newNode->data=data;
    newNode->next=NULL;
    return newNode;
}
int main()
{
    int n;
    scanf("%d",&n);
    struct Node *front=NULL,*rear=NULL;
    for(int i=0;i<n;i++)
    {
        int value;
        scanf("%d",&value);
        struct Node*newNode =createNode(value);
        if (rear==NULL)
            front=rear=newNode;
        else
        {
            rear->next=newNode;
            rear=newNode;
        }
    }
    int k;
    scanf("%d",&k);
    int targetIndex=n-k;
    struct Node* temp=front;
    for(int i=0;i<targetIndex;i++)
        temp=temp->next;
    printf("%d\n",temp->data);
    return 0;
}

```

Status : Correct

Marks : 10/10