Task 3:

1) Define a function greet () to print "Hello!" and call it from main()

```
#include <stdio.h>
Void greet (){
    printf("Hello! \n");

}
int main (){
    greet ();
    return 0;

}
```

output:

Hello!

2) write a function add() that takes two integer as parameters and prints their sum

```
#include <stdio.h>
Void add (int a, int b){
    printf("Sum: %d\n", a+b);
}
int main (){
    int x, y;
    printf("Enter two integers: ");
    scanf("%d %d", &x, &y);
    add (x, y);
    return 0;
}
```

output:

Enter two integer:
57

Sum: 12

3) Create a function multiply() that returns the product of two numbers

```
#include <stdio.h>
int multiply (int a, int b) {
    return a * b;
}

int main () {
    int x, y, result;
    printf("Enter two integers : ");
    scanf("%d %d", &x, &y);
    result = multiply (x, y);
    printf ("product : %d\n", result);
    return 0;
}
```

output :

```
Enter two integers: 4 0
Product : 24
```

4) Implement a recursive function to calculate the factorial of a number

```
#include <stdio.h>
int factorial (int n) {
    if (n == 0 || n == 1)
        return 1;
    else
        return n * factorial (n-1);
}
int main () {
    int n;
```

```
printf("Enter a number:");
scanf("%d", &n);
printf("Factorial of %d is %d\n", n,
                       factorial(n));
return 0;
}
```

output:

```
Enter a number: 5
Factorial of 5 is 120
```

5) Program with two function: one to square a number and another to display it.

```
# include <stdio.h>
int square (int n){
    return n* n;
}
void display (int n){
    printf("Result: %d \n", n);
}
int main (){
    int num;
    printf("Enter a number to square:");
    scanf("%d", &num);
    int sq = square (num);
    display (sq);
    return 0;
}
```

output:

```
Enter a number to square: 9
Result: 81
```