

Semantic Similarity Report

Generated on: 2025-12-08 10:11:28

SPATIO-TEMPORAL TRANSFORMER TO SUPPORT AUTOMATIC SIGN LANGUAGE

Sign Language Translation (SLT) systems support hearing-impaired people communication by finding equivalences between signed and spoken languages. [Similarity: 78%]

This task is however challenging due to multiple sign variations, complexity in language and inherent richness of expressions. [Similarity: 64%]

Computational approaches have evidenced capabilities to support SLT. [Similarity: 36%]

Nonetheless, these approaches remain limited to cover gestures variability and support long sequence translations. [Similarity: 56%]

This paper introduces a Transformer-based architecture that encodes spatio-temporal motion gestures, preserving both local and long-range spatial information through the use of multiple convolutional and attention mechanisms. [Similarity: 54%]

The proposed approach was validated on the Colombian Sign Language Translation Dataset (CoL-SLTD) outperforming baseline approaches, and achieving a BLEU4 of 46.84%. [Similarity: 59%]

Additionally, the proposed approach was validated on the RWTH-PHOENIX-Weather-2014T (PHOENIX14T), achieving a BLEU4 score of 30.77%, demonstrating its robustness and effectiveness in handling real-world variations. [Similarity: 40%]

Index Terms— sign language translation, encoder-decoder, convolutional feature maps, transformer. [Similarity: 64%]

1. [Similarity: 25%]

INTRODUCTION Sign language is the main alternative of communication for approximately 466 million hearing-impaired individuals worldwide [1]. [Similarity: 68%]

However, effective communication even among deaf people can be challenging due to the various cultural, regional, and socio-linguistic differences in sign language. [Similarity: 79%]

Moreover, communication with the rest of society is severely limited due to the lack of knowledge of sign languages, creating a significant obstacle to full immersion of deaf people in daily activities. [Similarity: 71%]

Hence, translation support alternatives are crucial to facilitate communication among hearing-impaired individuals and the rest of society [2]. [Similarity: 55%]

Sign languages are complex visual languages that involve spatio-temporal parameters present in the articulation of signs such as motion, position, hand-shape and orientation as well as non-manual components corresponding to mouth and eyebrow shapes [3]. [Similarity: 67%]

As a consequence, modeling, characterizing, and developing computational methods that can handle a continuous sign language translation remains a challenging task. [Similarity: 69%]

Currently, state-of-the-art approaches for sign language translation are mostly based on sequence-to-sequence models with encoder-decoder architectures [4]. [Similarity: 62%]

These approaches are typically built on recurrent neural networks (RNN), which can limit the network's ability to identify long-range spatial dependencies inherent in sign language [5, 6]. [Similarity: 65%]

To address these challenges, more advanced approaches such as Transformers have been proposed to capture long temporal dependencies in sign language translation, considering multiple attention mechanism to weight importance to key gestures in a communication [7]. [Similarity: 66%]

Current SLT Transformers, however, lose spatio-temporal information given by sign gestures, as they typically use flattened input representations, which may result in the loss of significant information in sign communication. [Similarity: 55%]

Also, during language communication, motion information is relevant to bring additional contextual information, and therefore, new schemes require the exploitation of spatio-temporal gestural pose estimation, as well as motion kinematic primitives. [Similarity: 55%]

Semantic Similarity Report

Generated on: 2025-12-08 10:11:29

The main contribution of this work is a Transformer-based architecture that takes in a more suitable spatial representation of sign gestures to encode both local and long range spatial dependencies. [Similarity: 59%]

To achieve this, we enhance the encoding strategy by creating a better input representation which consists of first taking optical-flow images which helps the network focus on motion kinematic patterns and extract from these two-dimensional (2D) representations of convolutional feature maps in order to preserve relevant local spatial information present in gestures. [Similarity: 59%]

We explore the application of 2D positional encodings to handle 2D data. [Similarity: 39%]

Additionally, we include a 2D self-attention mechanism that takes the previously extracted feature maps and calculates a pixel-wise attention to better highlight long range dependencies while acting as a complement to convolutions. [Similarity: 42%]

Our proposed approach has therefore the capability to detect variations related to both manual and non-manual articulators while trained using a sequence-to-sequence scheme. [Similarity: 38%]

arXiv:2502.02587v1 [cs.CL] 4 Feb 2025 [Similarity: 16%]

Sources of Similar Content

V-STaR: Benchmarking Video-LLMs on Video Spatio-Temporal Reasoning
(Source: <https://arxiv.org/pdf/2503.11495v1>)

Scaling up Multimodal Pre-training for Sign Language Understanding
(Source: <https://arxiv.org/pdf/2408.08544v1>)

ASTER: Adaptive Spatio-Temporal Early Decision Model for Dynamic Resource Allocation
(Source: <https://arxiv.org/pdf/2506.17929v1>)

3D-LEX v1.0: 3D Lexicons for American Sign Language and Sign Language of the Netherlands
(Source: <https://arxiv.org/pdf/2409.01901v1>)