ROUTING Report

Last run: 05 Nov 2026, 06:58:54 pm
Generated: 05 Nov 2026, 07:01:33 pm

Project: Asynchronous_FIFO PDK: sky130A

Run Time: 2m 7s | CPU Time: 3m 55s | Peak Memory: 1.05 GB | Threads: 2

AREA METRICS

Total area of buffer cells	Total area of timing buffer cells	Total area of inverter cells	Total area of clock inverter cells	Total area of sequential cells
4115 µm²	1232 µm²	8 µm²	653 µm²	17347 µm²

Total area of combinational cells	Total area of tap cells	Total placed standard-cell area
4244 µm²	1755 µm²	106903 µm²

DESIGN AREA UTILIZATION

Core area	Core utilization
27599 µm²	26 %

DESIGN CELL COUNTS

Number of clock buffer cells	Number of timing repair buffer cells	Number of inverter cells	Number of clock inverter cells	Number of sequential cells
167	126	2	102	584

Number of combinational cells	Number of tap cells	Total number of cells
259	1403	13,025

PHYSICAL CELL COUNTS

Number of tap cells
1403

POWER

Sequential power	Combinational power	Clock power	Macro power	Pad power
3.88 W	2.25 W	5.85 W	0.00 W	0.00 W

Total power
12.00 W

ROUTING CONGESTION

Total routing overflow	Worst layer usage (%)
0	19.54 %

ROUTING MEMORY

Memory used (MB)	Peak memory used (MB)
1074 MB	1073 MB

ROUTING VIAS

Total vias
10,292

ROUTING WIRE LENGTH

Total wire length
51,634 µm

TIMING

Max slack	Min slack
4.410 ns	0.560 ns

COMPCARTA