

AIPP LAB 17

Name: MOHAMMED NIZAMUDDIN

Hall Ticket No.: 2503B05144

Date: 04/12/2025 (Week 6)

Completed this Assignment using Google Colab – Gemini AI Integration.

Task 1:

Social Media Data Cleaning

Clean raw social media posts dataset.

Instructions:

- Remove stopwords, punctuation, and special symbols from post text.**
- Handle missing values in likes and shares columns.**
- Convert timestamp to datetime and extract features (hour, weekday).**
- Detect and remove spam/duplicate posts.**

CODE:



```
# =====  
# NAME: MOHAMMED NIZAMUDDIN  
# HALL TICKET NO. 2503B05144  
# DATE: 04/12/2025  
  
# LAB 17 - AI FOR DATA PROCESSING: CLEANING & PREPROCESSING  
# =====  
  
# -----  
# INSTALLATION  
# -----  
!pip install nltk pandas numpy scikit-learn beautifulsoup4 --quiet  
  
import pandas as pd  
import numpy as np  
import nltk  
import re  
from bs4 import BeautifulSoup  
from sklearn.feature_extraction.text import TfidfVectorizer  
from sklearn.preprocessing import StandardScaler, LabelEncoder  
  
nltk.download("stopwords")  
from nltk.corpus import stopwords  
stop_words = set(stopwords.words("english"))
```

```
... [nltk_data] Downloading package stopwords to /root/nltk_data...  
[nltk_data] Package stopwords is already up-to-date!
```



```
# =====
# ----- TASK 1 -----
# SOCIAL MEDIA DATA CLEANING
# =====

print("\n===== TASK 1: SOCIAL MEDIA CLEANING =====")

# Upload dataset in Google Colab
from google.colab import files
uploaded = files.upload()

social_df = pd.read_csv("social_media.csv")

# ----- BEFORE SUMMARY -----
print("\n--- BEFORE CLEANING ---")
print(social_df.head())

# ----- REMOVE PUNCTUATION, STOPWORDS, SPECIAL SYMBOLS -----
def clean_text(text):
    if pd.isna(text):
        return ""
    text = text.lower()
    text = re.sub(r"[^a-zA-Z\s]", "", text)          # remove punctuation/symbols
    words = [w for w in text.split() if w not in stop_words]
    return " ".join(words)

social_df["clean_post"] = social_df["post_text"].apply(clean_text)

# ----- HANDLE MISSING VALUES IN likes & shares -----
social_df["likes"] = social_df["likes"].fillna(social_df["likes"].median())
social_df["shares"] = social_df["shares"].fillna(0)

# ----- TIMESTAMP PROCESSING -----
social_df["timestamp"] = pd.to_datetime(social_df["timestamp"])
social_df["hour"] = social_df["timestamp"].dt.hour
social_df["weekday"] = social_df["timestamp"].dt.day_name()

# ----- REMOVE DUPLICATE / SPAM -----
social_df.drop_duplicates(subset="clean_post", inplace=True)

# ----- AFTER SUMMARY -----
print("\n--- AFTER CLEANING ---")
print(social_df.head())

# ----- TEST CASES -----
assert social_df["clean_post"].isna().sum() == 0
assert social_df["likes"].isna().sum() == 0
assert "hour" in social_df.columns

print("\nTask 1 Passed All Tests ✓")
```

OUTPUT:

```

===== TASK 1: SOCIAL MEDIA CLEANING =====
...  No file chosen Upload widget is only available when the cell has
Saving social_media.csv to social_media (2).csv

--- BEFORE CLEANING ---
post_id    user    post_text    likes    shares    \
0          1  user_1    This is a sample POST!!! #fun    20.0    1.0
1          2  user_2    <html>Great Day!</html>    20.0    3.0
2          3  user_3    This is a sample POST!!! #fun    20.0    1.0
3          4  user_4    <html>Great Day!</html>    100.0    NaN
4          5  user_5    This is a sample POST!!! #fun    20.0    5.0

timestamp
0  2025-01-01 00:00:00
1  2025-01-01 06:00:00
2  2025-01-01 12:00:00
3  2025-01-01 18:00:00
4  2025-01-02 00:00:00

--- AFTER CLEANING ---
post_id    user    post_text    likes    shares    \
0          1  user_1    This is a sample POST!!! #fun    20.0    1.0
1          2  user_2    <html>Great Day!</html>    20.0    3.0

timestamp    clean_post    hour    weekday
0  2025-01-01 00:00:00    sample post fun    0    Wednesday
1  2025-01-01 06:00:00    htmlgreat dayhtml    6    Wednesday

Task 1 Passed All Tests ✓

```

Task 2:

Financial Data Preprocessing

Preprocess a stock market dataset.

Instructions:

- Handle missing values in closing_price and volume.
- Create lag features (1-day, 7-day returns).
- Normalize volume column using log-scaling.
- Detect outliers in closing_price using IQR method.

CODE:

```

# =====
# ----- TASK 2 -----
# FINANCIAL DATA PREPROCESSING
# =====

print("\n===== TASK 2: FINANCIAL DATA =====")

financial_df = pd.read_csv("financial_data.csv")

# BEFORE SUMMARY
print("\n--- BEFORE ---")
print(financial_df.head())

# Missing values
financial_df["closing_price"] = financial_df["closing_price"].fillna(method="ffill")
financial_df["volume"] = financial_df["volume"].fillna(financial_df["volume"].median())

# Lag features
financial_df["return_1d"] = financial_df["closing_price"].pct_change()
financial_df["return_7d"] = financial_df["closing_price"].pct_change(periods=7)

# Log normalize volume
financial_df["volume_log"] = np.log1p(financial_df["volume"])

# Outlier detection (IQR)
Q1 = financial_df["closing_price"].quantile(0.25)
Q3 = financial_df["closing_price"].quantile(0.75)
IQR = Q3 - Q1

lower = Q1 - 1.5 * IQR
upper = Q3 + 1.5 * IQR

financial_df = financial_df[(financial_df["closing_price"] >= lower) &
                           (financial_df["closing_price"] <= upper)]

# AFTER SUMMARY
print("\n--- AFTER ---")
print(financial_df.head())

# TESTS
assert financial_df["volume"].isna().sum() == 0
assert "return_1d" in financial_df.columns
assert financial_df["volume_log"].min() >= 0

print("\nTask 2 Passed All Tests ✓")

```

OUTPUT:

```

...
===== TASK 2: FINANCIAL DATA =====

--- BEFORE ---
   date  closing_price  volume
0 2025-01-01         NaN  5000.0
1 2025-01-02        131.04  2000.0
2 2025-01-03        138.26  2000.0
3 2025-01-04        164.68     NaN
4 2025-01-05        165.06  5000.0

--- AFTER ---
   date  closing_price  volume  return_1d  return_7d  volume_log
1 2025-01-02        131.04  2000.0         NaN         NaN       7.601402
2 2025-01-03        138.26  2000.0    0.055098         NaN       7.601402
3 2025-01-04        164.68  2000.0    0.191089         NaN       7.601402
4 2025-01-05        165.06  5000.0    0.002308         NaN       8.517393
5 2025-01-06        137.99  1500.0   -0.164001         NaN       7.313887

Task 2 Passed All Tests ✓
/tmp/ipython-input-1164313261.py:15: FutureWarning: Series.fillna with 'method'
  financial_df["closing_price"] = financial_df["closing_price"].fillna(method='

```

Task 3:

IoT Sensor Data Preparation

Clean and preprocess IoT temperature and humidity logs.

Instructions:

- Handle missing values using forward fill.
- Remove sensor drift (apply rolling mean).
- Normalize readings using standard scaling.
- Encode categorical sensor IDs.

CODE:

```
▶ # =====
# ----- TASK 3 -----
# IOT SENSOR DATA
# =====

print("\n===== TASK 3: IOT SENSOR =====")

iot_df = pd.read_csv("iot_sensor.csv")

print("\n--- BEFORE ---")
print(iot_df.head())

# Handle missing → Forward fill
iot_df["temperature"] = iot_df["temperature"].fillna(method="ffill")
iot_df["humidity"] = iot_df["humidity"].fillna(method="ffill")

# Remove drift → Rolling mean
iot_df["temp_smooth"] = iot_df["temperature"].rolling(5, min_periods=1).mean()
iot_df["humidity_smooth"] = iot_df["humidity"].rolling(5, min_periods=1).mean()

# Normalize using standard scaling
scaler = StandardScaler()
iot_df["temp_scaled"] = scaler.fit_transform(iot_df[["temp_smooth"]])
iot_df["humidity_scaled"] = scaler.fit_transform(iot_df[["humidity_smooth"]])

# Encode sensor ID
encoder = LabelEncoder()
iot_df["sensor_encoded"] = encoder.fit_transform(iot_df["sensor_id"])

print("\n--- AFTER ---")
print(iot_df.head())

# TESTS
assert iot_df["temperature"].isna().sum() == 0
assert "temp_scaled" in iot_df.columns
assert iot_df["sensor_encoded"].nunique() > 0

print("\nTask 3 Passed All Tests ✓")
```

OUTPUT:

```
===== TASK 3: IOT SENSOR =====

*** --- BEFORE ---
      timestamp sensor_id temperature humidity
0  2025-02-01 00:00:00      S2       24.0      40.0
1  2025-02-01 01:00:00      S3       30.0      NaN
2  2025-02-01 02:00:00      S1       24.0      50.0
3  2025-02-01 03:00:00      S2       24.0      NaN
4  2025-02-01 04:00:00      S3       23.0      42.0

--- AFTER ---
      timestamp sensor_id temperature humidity temp_smooth \
0  2025-02-01 00:00:00      S2       24.0      40.0        24.0
1  2025-02-01 01:00:00      S3       30.0      40.0        27.0
2  2025-02-01 02:00:00      S1       24.0      50.0        26.0
3  2025-02-01 03:00:00      S2       24.0      50.0        25.5
4  2025-02-01 04:00:00      S3       23.0      42.0        25.0

      humidity_smooth temp_scaled humidity_scaled sensor_encoded
0          40.000000    -0.031984     -1.922355             1
1          40.000000     2.493079     -1.922355             2
2          43.333333     1.651391     -0.377054             0
3          45.000000     1.230547      0.395597             1
4          44.400000     0.809703      0.117443             2

Task 3 Passed All Tests ✓
/tmp/ipython-input-91793892.py:14: FutureWarning: Series.fillna with 'me
iot_df["temperature"] = iot_df["temperature"].fillna(method="ffill")
/tmp/ipython-input-91793892.py:15: FutureWarning: Series.fillna with 'me
iot_df["humidity"] = iot_df["humidity"].fillna(method="ffill")
```

Task 4:

Real-Time Application: Movie Reviews Data Cleaning

A streaming platform wants to analyze customer reviews.

Instructions:

- Standardize text (lowercase, remove HTML tags).
- Tokenize and encode reviews using AI-assisted methods (TF-IDF or embeddings).
- Handle missing ratings (fill with median).
- Normalize ratings (0–10 → 0–1 scale).
- Generate a before vs after summary report.

CODE:

```

# =====
# ----- TASK 4 -----
# MOVIE REVIEWS
# =====

print("\n===== TASK 4: MOVIE REVIEWS CLEANING =====")

movie_df = pd.read_csv("movie_reviews-1.csv")

print("\n--- BEFORE ---")
print(movie_df.head())

# Clean HTML + lowercase
def clean_review(text):
    if pd.isna(text):
        return ""
    text = BeautifulSoup(text, "html.parser").get_text()
    return text.lower()

movie_df["clean_review"] = movie_df["review_text"].apply(clean_review)

# Tokenize + TF-IDF
tfidf = TfidfVectorizer(stop_words="english", max_features=500)
tfidf_matrix = tfidf.fit_transform(movie_df["clean_review"])

# Rating -> fill missing
movie_df["rating"] = movie_df["rating"].fillna(movie_df["rating"].median())

# Normalize 0-10 -> 0-1

# Normalize 0-10 -> 0-1
movie_df["rating_norm"] = movie_df["rating"] / 10

print("\n--- AFTER ---")
print(movie_df.head())

# TESTS
assert movie_df["clean_review"].isna().sum() == 0
assert movie_df["rating_norm"].max() <= 1
assert tfidf_matrix.shape[0] == len(movie_df)

print("\nTask 4 Passed All Tests ✓")

print("\n===== ALL TASKS COMPLETED SUCCESSFULLY =====\n")

```

OUTPUT:

```

...
===== TASK 4: MOVIE REVIEWS CLEANING =====

--- BEFORE ---
  review_id  review_text  rating
0         1  <p>Amazing movie!</p>    8.0
1         2  Terrible acting & plot!!!    2.0
2         3  <p>Amazing movie!</p>    NaN
3         4  Terrible acting & plot!!!    8.0
4         5  <p>Amazing movie!</p>    5.0

--- AFTER ---
  review_id  review_text  rating  clean_review \
0         1  <p>Amazing movie!</p>    8.0    amazing movie!
1         2  Terrible acting & plot!!!    2.0  terrible acting & plot!!!
2         3  <p>Amazing movie!</p>    8.0    amazing movie!
3         4  Terrible acting & plot!!!    8.0  terrible acting & plot!!!
4         5  <p>Amazing movie!</p>    5.0    amazing movie!

  rating_norm
0         0.8
1         0.2
2         0.8
3         0.8
4         0.5

Task 4 Passed All Tests ✓

===== ALL TASKS COMPLETED SUCCESSFULLY =====

```


