

Partitioning Mutate, Example 3

John Mount, Win-Vector LLC

2017-12-28

This third article shows our second example being processed by the rquery big data scale relational data operator system (currently in development).

We will repeat the steps from Partitioning Mutate, Example 2, using only the rquery package and DBI/sparklyr (no dplyr).

```
library("wrapr")
library("rquery")

class(sc)

## [1] "spark_connection"
## [2] "spark_shell_connection"
## [3] "DBIConnection"

class(d)

## [1] "relop_table_source" "relop"

d %>%
  to_sql(., sc) %>%
  DBI::dbGetQuery(sc, .) %>%
  knitr::kable(.)
```

rowNum	a_1	a_2	b_1	b_2	c_1	c_2	d_1	d_2	e_1	e_2
1	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
2	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
3	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
4	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
5	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

```
dQ <- d %>%
  extend_se(.,
    if_else_block(
      testexpr =
        "rand()>=0.5",
      thenexprs = qae(
        a_1 := 'treatment',
        a_2 := 'control'),
      elseexprs = qae(
        a_1 := 'control',
```

```

        a_2 := 'treatment')))) %.>%
select_columns(., c("rowNum", "a_1", "a_2"))

cat(format(dQ))

table('d') %.>%
  extend(.,
    ifebtest_1 := rand() >= 0.5) %.>%
  extend(.,
    a_1 := ifelse(ifebtest_1,"treatment",a_1),
    a_2 := ifelse(ifebtest_1,"control",a_2)) %.>%
  extend(.,
    a_1 := ifelse(! ( ifebtest_1 ),"control",a_1),
    a_2 := ifelse(! ( ifebtest_1 ),"treatment",a_2)) %.>%
  select_columns(., rowNum, a_1, a_2)

sql <- to_sql(dQ, sc)
cat(sql)

SELECT
  `rowNum`,
  `a_1`,
  `a_2`
FROM (
  SELECT
    `ifebtest_1`,
    `rowNum`,
    ( CASE WHEN ( ( NOT ( `ifebtest_1` ) ) ) THEN ( "control" ) ELSE ( `a_1` ) END ) AS `a_1`,
    ( CASE WHEN ( ( NOT ( `ifebtest_1` ) ) ) THEN ( "treatment" ) ELSE ( `a_2` ) END ) AS `a_2`
  FROM (
    SELECT
      `ifebtest_1`,
      `rowNum`,
      ( CASE WHEN ( `ifebtest_1` ) THEN ( "treatment" ) ELSE ( `a_1` ) END ) AS `a_1`,
      ( CASE WHEN ( `ifebtest_1` ) THEN ( "control" ) ELSE ( `a_2` ) END ) AS `a_2`
    FROM (
      SELECT
        `rowNum`,
        `a_1`,
        `a_2`,
        rand ( ) >= 0.5 AS `ifebtest_1`
      FROM (
        SELECT
          `d`.`rowNum`,
          `d`.`a_1`,

```

```

    `d`.`a_2`
FROM
    `d`
  ) tsq1_0000
  ) tsq1_0001
  ) tsq1_0002
  ) tsq1_0003

DBI::dbGetQuery(sc, sql) %>%
  knitr::kable(.)

```

rowNum	a_1	a_2
1	treatment	control
2	treatment	control
3	control	treatment
4	control	treatment
5	treatment	control

Links

Win-Vector LLC supplies a number of open-source R packages for working effectively with big data. These include:

- **wrapr**: supplies code re-writing tools that make coding *over* “non standard evaluation” interfaces (such as **dplyr**) *much* easier.
- **cdata**: supplies pivot/un-pivot functionality at big data scale.
- **rquery**: (in development) big data scale relational data operators.
- **seplyr**: supplies improved interfaces for many data manipulation tasks.
- **replyr**: supplies tools and patches for using **dplyr** on big data.

Partitioning mutate articles:

- **Partitioning Mutate**: basic example.
- **Partitioning Mutate, Example 2**: **ifelse** example.
- **Partitioning Mutate, Example 3** **rquery** example.

Topics such as the above are often discussed on the Win-Vector blog.