

Double Nibble Detect

Marc Defossez Sr. Staff Applications Engineer

Created: Modified: March 30, 2011

July 29, 2011

DISCLAIMER:

© Copyright 2009 - 2009, Xilinx, Inc. All rights reserved.

This file contains confidential and proprietary information of Xilinx, Inc. and is protected under U.S. and international copyright and other intellectual property laws.

Disclaimer:

This disclaimer is not a license and does not grant any rights to the materials distributed herewith. Except as otherwise provided in a valid license issued to you by Xilinx, and to the maximum extent permitted by applicable law: (1) THESE MATERIALS ARE MADE AVAILABLE "AS IS" AND WITH ALL FAULTS, AND XILINX HEREBY DISCLAIMS ALL WARRANTIES AND CONDITIONS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE; and (2) Xilinx shall not be liable (whether in contract or tort, including negligence, or under any other theory of liability) for any loss or damage of any kind or nature related to, arising under or in connection with these materials, including for any direct, or any indirect, special, incidental, or consequential loss or damage (including loss of data, profits, goodwill, or any type of loss or damage suffered as a result of any action brought by a third party) even if such damage or loss was reasonably foreseeable or Xilinx had been advised of the possibility of the same.

CRITICAL APPLICATIONS

Xilinx products are not designed or intended to be fail-safe, or for use in any application requiring fail-safe performance, such as life-support or safety devices or systems, Class III medical devices, nuclear facilities, applications related to the deployment of airbags, or any other applications that could lead to death, personal injury, or severe property or environmental damage (individually and collectively, "Critical Applications"). Customer assumes the sole risk and liability of any use of Xilinx products in Critical Applications, subject only to applicable laws and regulations governing limitations on product liability.

THIS COPYRIGHT NOTICE AND DISCLAIMER MUST BE RETAINED AS PART OF THIS FILE AT ALL TIMES.


Contact: e-mail hotline@xilinx.com phone + 1 800 255 7778



This page is intentionally left blank.




Symbol






Datapath






Counters & SRL Control



Rst Control



When RstIn is applied, made high, the last two FFs will be set and immediately filled back with zero at the rate of Clock (rising edge). IntRstIn_d will thus go high for two Clock periods.

When IntRstSet is made high for a Clock cycle all FFs will turn high and then back filled with zero at the rate of Clock. IntRstIn_d will be high for eight Clock cycles.

