KatalogKu Stage B

PocketBase microservices | Submission report | 8 November 2026

Client / Postman HTTP API requests	**Nginx gateway** localhost:18081	**Product service** PocketBase + SQLite	**Account service** PocketBase + SQLite
		products | host 8091 volume: product_data	users + favorites | host 8092 volume: account_data

Architecture and configuration

The deployment runs exactly three containers. Product and account data use separate SQLite databases in named Docker volumes. PocketBase imports its exported collection schema through startup migrations. Nginx routes product requests to product-service and auth/favorites requests to account-service.

Container	Responsibilities	Host endpoint / storage
product-service	Public product list/details; superuser-only writes	8091 | product_data
account-service	User registration/login; owner-scoped favorites	8092 | account_data
gateway	Nginx API routing and health response	18081 (8080 unavailable)

API and access rules

GET /api/health and product list/details are public. Product create/update/delete rules are locked to superusers. Users can register and authenticate at /api/auth/records and /api/auth/auth-with-password. Favorites require an authenticated owner for writes and are filtered by user ID for reads; a unique (user, product_id) index rejects duplicates.

Verification results

PASS	Health, public product list and detail through Nginx
PASS	Five example products seeded as product superuser; products persist after rebuild
PASS	Anonymous product writes denied; user registration and login succeeded
PASS	Favorites: owner list/create/delete; duplicate rejected; another user cannot read or delete

Superuser passwords are randomly generated and stored in the ignored local .env file. The submission ZIP contains only .env.example and no live databases or credentials.