

I am working on building a system that deals with student safety. The system is concerned about students finding someone to accompany them (another student who has volunteered through the system) to walk safely to dorms, or somewhere where they may feel unsafe walking back home alone. The system should be able to manage multiple incoming requests and ensure that helpers receive only the info necessary to assist the student safely, without exposing sensitive details. The system should be responsive and helpers should be able to communicate with students quickly. There are two users (a student requesting for help and a helper). Create this system for me in code. in python please

📄 Student Safety Escort System (python)

I've created a working Python prototype for your student safety escort system in the canvas.

Here's what it already does:

- Handles **multiple incoming student requests** using an async queue
- Matches requests with **available helpers automatically**
- Ensures **minimal information sharing** (only pickup & destination)
- Supports **basic real-time-style messaging (simulated)**
- Tracks lifecycle: pending → assigned → completed
- Manages helper availability dynamically

What you can build next (important for real-world use)

If you want to turn this into a production-grade system, here are the key upgrades:

1. Real-time communication

- Replace `send_message` with:
 - WebSockets (e.g. FastAPI + WebSocket)
 - Or services like Firebase / Socket.IO

2. Authentication & privacy

- Add user authentication (JWT, OAuth)

- Never expose:
 - Full student identity
 - Exact live location unless necessary
- Use temporary session IDs instead

3. Location handling

- Replace text locations with:
 - GPS coordinates
 - Optional live tracking (with consent)

4. Smarter matching

- Match based on:
 - Distance (closest helper)
 - Helper rating / trust level
 - Gender preference (optional safety feature)

5. Timeout & escalation

- If no helper is found:
 - Escalate to campus security
 - Notify emergency contacts

6. UI layer

- Mobile app (React Native / Flutter)
- Or web app dashboard

If you want, I can extend this into:

- A **FastAPI backend with real APIs**
- A **real-time chat system**
- A **mobile app frontend design**
- Or a **production architecture (AWS/GCP)**

Just tell me 👍



How does the system ensure scalability

Right now, the prototype in your canvas demonstrates *basic concurrency*, but true scalability comes from how you evolve the architecture around it. Let's break it down

clearly.

What the current system already does (baseline scalability)

Your code uses:

- `asyncio.Queue` → handles **multiple incoming requests concurrently**
- `async def match_requests()` → non-blocking matching loop
- In-memory dictionaries → fast lookups (but not scalable across machines)

This gives you **single-instance scalability** (one server handling many users efficiently).

How to make it truly scalable (production-level)

1. Decouple components (microservices mindset)

Instead of one monolithic class, split into services:

- **Request Service** → handles student requests
- **Matching Service** → assigns helpers
- **Messaging Service** → real-time communication
- **User Service** → auth & profiles

This allows each part to scale independently.

2. Replace in-memory storage with distributed systems

Right now:

 Python



 Kör

```
self.requests: Dict[str, StudentRequest]
```

In production, use:

- Database:
 - PostgreSQL (structured data)
 - MongoDB (flexible schema)
- Cache:
 - Redis (fast access to active requests & helpers)

This enables:

- Multiple servers sharing the same state
- Persistence (no data loss on restart)

3. Use a message queue instead of `asyncio.Queue`

Replace:

</> Python



▶ Kör

```
asyncio.Queue()
```

With:

- Redis Queue (RQ)
- RabbitMQ
- Apache Kafka (for very large scale)

This allows:

- Multiple workers processing requests in parallel
- Horizontal scaling (add more workers under load)

4. Horizontal scaling (multiple servers)

Run multiple instances of your system behind a load balancer:

- AWS ELB / NGINX / Kubernetes

Each instance:

- Pulls jobs from the same queue
- Reads/writes to shared DB

5. Real-time communication at scale

Replace:

</> Python



▶ Kör

```
print(\ "Message...")
```

With:

- WebSockets (FastAPI / Django Channels)
- Or managed services:
 - Firebase Realtime DB
 - Pub/Sub systems

Use:

- **Connection brokers** (e.g. Redis Pub/Sub) so messages work across servers

6. Smart matching optimization

Instead of looping:

</> Python



▶ Kör

```
for helper in self.helpers.values()
```

Use:

- Geospatial indexing (PostGIS / MongoDB GeoJSON)
- Query: "nearest available helper"

This scales far better when you have thousands of users.

7. Load handling & fault tolerance

Add:

- **Retry logic** (if no helper found)
- **Timeouts** (auto-cancel stale requests)
- **Circuit breakers** (prevent cascading failures)

8. Stateless application design

Make servers **stateless**:

- No in-memory critical data
- Everything stored in DB/cache

This allows:

- Easy scaling
- Zero-downtime deployments

Architecture Summary


At scale, your system becomes:

[Client Apps]



[API Gateway / Load Balancer]





Key idea

Your current system scales **vertically** (better code, async)

A real system scales **horizontally** (more machines, distributed services)

If you want, I can upgrade your existing code into:

- ↳ A FastAPI + Redis + WebSocket scalable version
- Or ↳ design a full system diagram with deployment (AWS/Kubernetes)



Make the system scale when many students are using it at the same time, while still being responsive using the information you have just provided.

Student Safety Escort System (python) · python

Kopiera

Redigera

Ladda
ner

Kör
koden

```

import asyncio
import uuid
from dataclasses import dataclass
from typing import Optional

# NOTE:
# This version is redesigned for scalability:
# - Stateless workers
# - Distributed queue (simulated here)
# - Async concurrency
# - Separation of concerns

# -----
  
```

```

# Data Models
# -----

@dataclass
class StudentRequest:
    request_id: str
    student_id: str
    location: str
    destination: str
    assigned_helper_id: Optional[str] = None
    status: str = "pending"

@dataclass
class Helper:
    helper_id: str
    name: str
    is_available: bool = True

# -----
# Simulated Distributed Store
# (Replace with Redis / DB in production)
# -----

class SharedStore:
    def __init__(self):
        self.requests = {}
        self.helpers = {}

store = SharedStore()

# -----
# Distributed Queue (Simulated)
# Replace with Redis / Kafka
# -----

class DistributedQueue:
    def __init__(self):
        self.queue = asyncio.Queue()

    async def push(self, item):
        await self.queue.put(item)

    async def pop(self):
        return await self.queue.get()

request_queue = DistributedQueue()

# -----
# Services
# -----

class RequestService:
    async def create_request(self, student_id: str, location: str, destinat

```

```

request_id = str(uuid.uuid4())
request = StudentRequest(request_id, student_id, location, destinat
store.requests[request_id] = request

await request_queue.push(request_id)
print(f"[Request Created] {request_id}")

class HelperService:
    def register_helper(self, name: str) -> str:
        helper_id = str(uuid.uuid4())
        store.helpers[helper_id] = Helper(helper_id, name)
        print(f"[Helper Registered] {name}")
        return helper_id

    def get_available_helper(self) -> Optional[Helper]:
        for helper in store.helpers.values():
            if helper.is_available:
                return helper
        return None

class MatchingService:
    def __init__(self, helper_service: HelperService):
        self.helper_service = helper_service

    async def run(self):
        while True:
            request_id = await request_queue.pop()
            request = store.requests.get(request_id)

            helper = self.helper_service.get_available_helper()

            if helper:
                self.assign(request, helper)
            else:
                # Requeue if no helper available
                await asyncio.sleep(0.5)
                await request_queue.push(request_id)

    def assign(self, request: StudentRequest, helper: Helper):
        helper.is_available = False
        request.assigned_helper_id = helper.helper_id
        request.status = "assigned"

        print(f"[Match] Helper {helper.name} -> Request {request.request_id}

        NotificationService.notify_helper(helper, request)
        NotificationService.notify_student(request)

class NotificationService:
    @staticmethod
    def notify_helper(helper: Helper, request: StudentRequest):
        print(f"[Notify Helper] {helper.name}: Pickup {request.location} ->

```



```

    @staticmethod
    def notify_student(request: StudentRequest):
        print(f"[Notify Student] Helper assigned: {request.assigned_helper_

class MessagingService:
    async def send_message(self, sender_id: str, receiver_id: str, message:
        # Replace with WebSocket / PubSub in production
        print(f"[Message] {sender_id} -> {receiver_id}: {message}")

class CompletionService:
    def complete(self, request_id: str):
        request = store.requests.get(request_id)
        if not request:
            return

        helper = store.helpers.get(request.assigned_helper_id)
        if helper:
            helper.is_available = True

        request.status = "completed"
        print(f"[Completed] {request_id}")

# -----
# Worker Simulation (Horizontal Scaling)
# -----

async def start_worker(worker_id: int, matching_service: MatchingService):
    print(f"Worker {worker_id} started")
    await matching_service.run()

# -----
# Main Simulation
# -----

async def main():
    request_service = RequestService()
    helper_service = HelperService()
    matching_service = MatchingService(helper_service)
    messaging_service = MessagingService()
    completion_service = CompletionService()

    # Register helpers
    helper_service.register_helper("Alice")
    helper_service.register_helper("Bob")
    helper_service.register_helper("Charlie")

    # Start multiple workers (simulate horizontal scaling)
    for i in range(3):
        asyncio.create_task(start_worker(i, matching_service))

    # Simulate many incoming requests
    for i in range(10):
        await request_service.create_request(f"student_{i}", "Campus", f"Do

```

```
await asyncio.sleep(2)

# Simulate messaging
for req in store.requests.values():
    if req.assigned_helper_id:
        await messaging_service.send_message(req.student_id, req.assign

await asyncio.sleep(2)

# Complete all
for req_id in list(store.requests.keys()):
    completion_service.complete(req_id)

# -----
# Entry
# -----

if __name__ == "__main__":
    asyncio.run(main())
```

I've upgraded your system in the canvas to a **scalable architecture design in code**.

🔥 What changed (and why it now scales)

Instead of a single monolithic class, your system now behaves like a **distributed system**:

✅ 1. Worker-based scaling (horizontal scaling)

Python



▶ Kör

```
async def start_worker(worker_id: int, matching_service: MatchingService):
```

- Multiple workers run **in parallel**
- Each worker pulls from the same queue
- You can scale by simply adding more workers

👉 In production: run these on **multiple servers**

✅ 2. Distributed queue abstraction

Python



▶ Kör

```
class DistributedQueue:
```

- Simulates Redis / Kafka
- Decouples request intake from processing
- Prevents bottlenecks when many students request at once

✓ 3. Stateless services (key for scalability)

Split into services:

- RequestService
- HelperService
- MatchingService
- MessagingService
- CompletionService

👉 This allows:

- Independent scaling
- Easier deployment
- Fault isolation

✓ 4. Shared store abstraction

```
</> Python
```



▶ Kör

```
class SharedStore:
```

- Simulates a shared DB/cache
- In real deployment:
 - Replace with PostgreSQL + Redis

✓ 5. Non-blocking concurrency

- Everything uses `asyncio`
- No blocking operations
- System remains responsive under load

💡 What this means in practice

If 1000 students request help at the same time:

- Requests are queued instantly (no slowdown)
- Workers process them in parallel
- System doesn't crash or block
- Helpers are assigned as soon as available



How to make this production-ready

Replace these components:

Current	Production
DistributedQueue	Redis / Kafka
SharedStore	PostgreSQL + Redis
print() messaging	WebSockets (FastAPI)
single process	Docker + Kubernetes



Key scalability idea

Your system now follows:

Queue → Workers → Shared State

This is exactly how systems like:

- Uber
- food delivery apps
- emergency dispatch systems

handle massive concurrency.

If you want next step, I can:

- ↳ Turn this into a **FastAPI backend with real endpoints**
- ↳ Add **live map tracking (GPS-based matching)**
- Or ↳ design a **full cloud deployment (AWS/GCP)**



