

Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	A multimedia company experienced an internal network outage lasting two hours due to a Denial of Service (DoS) attack. A malicious actor exploited an unconfigured firewall to launch an ICMP ping flood, overwhelming the internal network and preventing access to all network resources. The incident management team successfully mitigated the attack and restored services by blocking the incoming ICMP packets.
Identify	The cybersecurity team identified a DoS attack utilizing a massive flood of ICMP pings. The attack severely impacted the company's internal network, causing all network services to suddenly stop responding and preventing normal internal traffic from functioning. The root vulnerability was an unconfigured firewall that allowed external, malicious ICMP traffic to enter the network unchecked.
Protect	To safeguard internal assets from future volumetric attacks, the security team implemented several network hardening measures. These include creating a new firewall rule to strictly limit the rate of incoming ICMP packets, and enabling source IP address verification on the firewall to drop spoofed packets. Additionally, an IDS/IPS system was deployed to actively filter out ICMP traffic based on suspicious characteristics.

Detect	To improve continuous monitoring capabilities, the organization deployed dedicated network monitoring software configured to detect abnormal traffic patterns and sudden spikes in ICMP requests. Integrating these logs with a SIEM tool will ensure the security team is alerted immediately if a similar anomaly occurs.
Respond	During the active attack, the incident management team effectively contained the threat by manually blocking all incoming ICMP packets at the firewall level. To preserve system integrity, non-critical network services were temporarily taken offline, allowing the team to focus on stabilizing and restoring critical network services first.
Recover	The affected network systems were fully recovered and returned to normal operation within two hours. Moving forward, recovery processes will include continuously monitoring the newly implemented firewall rules and IDS/IPS filters to ensure that legitimate network traffic is completely restored and not inadvertently blocked by the new security measures.

Reflections/Notes: