



ForzaTM

BOND | A FORCE TO BE RECKONED WITH

Transportation

TC456

Contact Adhesive



ForzaBOND® TC456 is a Low VOC, CA Compliant, multi-purpose web spray canister adhesive.

Benefits

- Excellent bonding to porous substrates
- Aggressive - bonds to nearly any surface
- Good head resistance (up to 180°F/82°C)
- High-strength, long-term bond
- Low VOC & California Compliant (SCAQMD Rule 1168)

Product Application

- Designed as a portable, self-contained spray system for field or shop applications.
- Be sure all surfaces are clean and free of grease, dirt, duct, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 1 day.

Applications

ForzaBOND® TC456 is specifically designed for a multi-purpose, low VOC contact adhesive specifically designed to bond and fixture foams, fabrics, and carpeting materials.

- Bonding foam in wrapped panels in buses, RVs, commercial, and emergency vehicles
- Fixturing insulation in cargo trailers, buses, RVs, livestock trailers, and commercial vehicles
- Foam bonding in upholstery applications

Technical Data

Solids:	32 - 38%
VOC Content:	52 g/L
Appearance:	Clear or Red
Shelf Life:	12 months from manufacture date
Dry Time:	2-4 Minutes
Open Time:	Long

Sizes

13 oz Aerosol Can	22L Disposable Canister
	108L Returnable Canister

Recommended Equipment

- FK20 Spray Gun
- FK30 Hose
- Use 6501B Spray Tip

Recommended Cleanup

- FC-CAR (citrus cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501