



ForzaTM

BOND | A FORCE TO BE RECKONED WITH

Construction

C-R560

Two-Part Epoxy



ForzaBOND® C-R560 is a two-part, reactive adhesive with a very fast cure and a wide range of uses.

Benefits

- 1:1 ratio, easy mixing or dispensing
- 3 minute work life, 8 minute handling strength
- -60° to 250°F service temperature
- Resistant to water, salt, vehicle fuels and fluids, and many other substances

Product Application

- A two part 1:1 mix ratio
- Ensure flow from both sides of cartridge is possible, attach static mixer and gun out material.
- Apply mixed adhesive to one surface to be bonded then mate second surface.
- Surfaces should be clean and dry free of dust and debris in most cases no abrasion or solvent wipe is necessary.

Applications

ForzaBOND® C-R560 provides a tenacious bond to wood, concrete, fiberglass, and most thermoset plastics, including:

- Carpet tack strip to concrete, metal, wood, and various other floor surfaces (carpet may be stretched as soon as 20 minutes after application)
- Bonding metal balusters in wood handrails
- Quickly adhering tread materials in high-traffic areas
- Bonding various materials to ceramic tile without the need for drilling or fasteners

Technical Data

Appearance:	Clear or Blue
Handling Time:	20 min
Mix Ratio:	15-21 %
Solids:	Flammable
VOC:	569 g/L

Sizes

300ml Dual Cartridge	280ml Coaxial

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501