



Pressure Sensitive Contact Adhesive

ForzaBOND IC947[®] is a high solids, very fast drying pressure sensitive adhesive.

Benefits

- · Polystyrene safe will not dissolve
- Aggressive Adheres to nearly any surface
- Repositionable High tack Excellent coverage
- Web spray
- Fast drying with long open time
- Excellent green strength and higher heat resistance
- No ODS (Ozone Depleting Substances)
- Temporary fixturing single-sided applications

Application Instructions

- ForzaBOND® IC947 is designed as a portable, self-contained spray system for field or shop applications.
- Apply adhesive to one or both surfaces to be mated, at 80% to 100% coverage.
 Spraying both surfaces will result in a stronger, more permanent bond.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical. Normal coverage required with web spray pattern is approximately 80% however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.

Applications

ForzaBOND® IC947 is a web spray adhesive designed for use in applications using:

- Polystyrene
- Foam of all types
- Flooring product
- Carpeting
- Vinyls (backed)
- Insulation
- Wood
- Fabrics
- · Acoustic materials

Technical Data

| Total Solids: | 25 - 30% |
|-----------------|----------------|
| VOC Content: | 465 g/L |
| Appearance: | Clear or Green |
| Shelf Life: | 12 Months |
| Dry Time: | 2-4 mins* |
| Open Time: | Long |
| Solvent System: | Flammable |
| Spray Pattern: | Web |

Sizes

22L Disposable Canister

108L Returnable Canister

*dependent on temp & humidity

Recommended Equipment

- FK20 Spray Gun
- FK30 Hose
- Use M201, 6501, Spray Tip

Recommended Clean Up

- ForzaCLEAN FC-CAR (citrus cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM



