



Insulation

R-A2000



Insulation Laminating Adhesive



ForzaBOND® R-21000 is a medium viscosity high-tack water based adhesive formulated to bond facing materials and fibrous substrates.

Benefits

- UL 723 Certification
- Non-Wrinkling
- Fast drying
- Excellent fiber-tearing bonds
- Excellent coverage - 600 sq ft per gallon

Product Application

- May be applied by extrusion or roller.
- 600 sq ft per gallon is recommended coverage.
- Adhesive should be allowed to completely dry before shipping.
- Film cleans up in warm soapy water, or a mixture of acetone and water.

Applications

ForzaBOND® R-A2000 engineered for bonding facing materials to fiberglass and mineral wood in roll coating insulation applications. It features high initial green-strength, effectively addressing the challenge of wrinkling across various facing materials.

Technical Data

Appearance:	White
Shelf Life:	3-6 months
Solids:	45-50%
Viscosity:	25-30cps

Sizes

5 Gallon Pail	Tote
55 Gallon Drum	

Recommended Cleanup

- Soapy Water

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300
info@forzabuilt.com
www.forzabuilt.com



3211 Nebraska Ave, Suite 300
Council Bluffs, Iowa 51501