

**ForzaBOND® CC503** is a Low VOC, CA Compliant, multi-purpose web spray canister adhesive.

### **Benefits**

- Excellent bonding to porous substrates
- · Aggressive bonds to nearly any surface
- Good head resistance (up to 180°F/82°C)
- High-strength, long-term bond
- Low VOC & California Compliant (SCAQMD Rule 1168)

## **Product Application**

- Designed as a portable, self-contained spray system for field or shop applications.
- Be sure all surfaces are clean and free of grease, dirt, duct, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 1 day.

# **Applications**

**ForzaBOND® CC503** is a low-VOC, California-compliant, multi-purpose web spray canister adhesive, specifically designed for various bonding and fixturing applications in construction, including:

- Carpet Installations
- Acoustical panel manufacturing
- Adhering vapor barriers
- Woodworking applications
- Corner bead applications in drywall
- Temporary securing of reveal strips in tilt-up concrete

#### **Technical Data**

Solids:	32 - 38%
VOC Content:	<50 g/L
Appearance:	Clear or Red
Shelf Life:	12 months from manufacture date
Dry Time:	2-4 Minutes
Open Time:	Long
Sizes	

13 oz Aerosol Can	22L Disposable Canister
	108L Returnable Canister

#### **Recommended Equipment**

- FK20 Spray Gun
- FK30 Hose
- Use 6501B Spray Tip

#### **Recommended Cleanup**

- FC-CAR (citrus cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

