

ForzaSEAL® OA29 is a high performance, trowelable advanced polymer adhesive specifically formulated to be used for most types of paneling installations.

## **Benefits**

- Trowelable Adhesive
- **Universal Application**
- Can be adhered immediately
- Will not soften drywall joints
- Environmentally safe
- Fast strength development
- Nonflammable
- Moisture, mold & mildew resistant
- Strong, fast grab
- Water-resistant bond
- Odorless
- **VOC-Compliant**

## **Product Application**

- Keep clean and free of adhesive build-up to ensure proper application
- Place panel against surface and press firmly over entire surface, working from the edge of the panel where molding is installed outwards to the open edge.
- Using a roller over the entire installed wall panel is recommended.
- Bracing may be required if walls and panels
- Panels used in conjunction with channel moldings should NOT fit tightly into the
- Leave a small area in the molding for expansion and follow panel manufacturer's recommendations.
- Any holes drilled through the panels for fasteners, pipes, or conduits should be oversized to allow for natural movement of the panel.
- Spread no more adhesive than can be installed in 20 minutes or less.

## **Applications**

Specifically designed for installing fiber reinforced plastic, plastic laminate, wainscoting, and other wall coverings over many common porous and non-porous surfaces. Compatible with wood, foam board, plastic, laminate, plywood, tub surrounds, metal, concrete vinyl, and non-porous building materials

## **Technical Data**

Skin Time:	95 minutes
Elongation at Break:	113%
Shore A Hardness:	46
Color:	White
Viscosity:	200,000 cps
ApplicationTemperature Range:	40 - 140°F
Shelf Life:	12 Months
Lap Shear Strength:	125 Psi
Sag:	Non-Sagging
Packaging	
1 Gallon	3.5 Gallon
5 Gallon	
	·

**Recommended Cleanup** 

Water Alcohol

Council Bluffs, Iowa 51501

