



ForzaBOND® OS24 hybrid polymer, moisture cure, single part structural adhesive.

#### **Benefits**

- Retains strong bond through impact, peel, flex, and changing temperatures
- Contains no solvents or iscyanates
- Easily applied by extrusion or trowel
- Non-yellowing Exposed to UV
- Does not form bubbles, shrink or crack when curing
- Highly resistant to water, salt water, oil, grease, fuel, and mild chemicals
- Paintable even when wet
- High tack holds parts until cured
- **UV** stable
- Non Hazardous

## **Product Application**

- Generally applied by extrusion, and trowel.
- Surfaces should be clean and free of dust, oil, and grease. When bonding metals, applying OSA Surface Activator to area to be bonded is recommended for best results.
- Apply between 34°F 150°F, in damp or dry conditions. The majority of its strength is developed in the first 24 hours.
- Minimum cure time is overnight, but several days may be required for maximum performance, however cure time may be accelerated at higher temperatures (do not exceed 150°F for accelerated cure).
- Most parts do not require fixturing, although heavy parts may require temporary fixturing to ensure desire positioning.

Bead Widths (inch)	Adhesive Yield (FT) / oz
1/8	12.2 ft
1/4	3.05 ft
3/8	1.35 ft
1/2	9.2 in
5/8	5.88 in
3/5	4.08 in
3/5	4.08 in

# **Applications**

ForzaBOND® OS24 is a permanent structural bond for interior and exterior application. This product bonds a large variety of materials:

All Metals

Wood

- Painted Steel
- **Fiberglass**
- Glass
- Rubber
- Granite
- Polystyrene Foam

**Most Plastics** 

### **Technical Data**

Skin Time:	Less than 30 min @ 68°F/65% RH
Tack Free Time:	Less than 1 hour @ 68°F/65% RH
Elongation at Break:	300-500%
Shore A Hardness:	50-55 +/-
Color:	White & Gray
Viscosity:	787,000 cps
Temperature Range:	-75° - 200°F
Shelf Life:	12 Months
Lap Shear Strength:	700 psi
Sag:	Non-Sagging
Staining:	Non-Staining

## **Packaging**

10.1oz Cartridge	20oz Sausage
5 Gallon Pail	52 Gallion Drum

**Recommended Cleanup** When Wet

Water Alcohol

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM

402.731.9300 info@forzabuilt.com www.forzabuilt.com

