

**ForzaBOND® CC513** is a non-flammable, non-methylene chloride contact adhesive.

### **Benefits**

- Non-Flammable
- Non-Methylene Chloride/N-Propyl Bromide
- High Heat Resistance
- · High Strength Aggressive Bond
- Quick Tack
- Fast Dry Time
- Lower VOC Formulation
- Fully Portable System
- HAPs Free

# **Application Instructions**

- Be sure all surfaces are clean and free of grease, dirt, dust, etc.
- Hold applicator perpendicular to substrate, 6-10 inches away.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 24 hours.

# **Applications**

**ForzaBOND**® **CC513** is a non-flammable, non-methylene chloride-based contact adhesive designed to bond a wide range of substrates, including:

- Carpet Installations
- Acoustic panel manufacturing and installation
- Backed roof membrane materials
- Prefabricated home and building manufacturing applications

## **Technical Data**

Total Solids:	34-36%
VOC Content:	~322 g/L
Appearance:	Clear or Blue
Shelf Life:	12 Months
Dry Time*:	2-4 Minutes
Open Time:	Long
Solvent System:	Non-Flam
Spray Pattern:	Web

#### Sizes

22L Disposable Canister

108L Returnable Canister

\*dependent on temp & humidity

### **Recommended Equipment**

- FK18 Gun
- FK80 Hose
- 11001B Tip

#### **Recommended Cleanup**

- FC-CAR (citrus cleaner)
- Organic Solvents



