

Non-Flammable
Contact Adhesive

ForzaBOND® MC722 is a non-flammable, Contact Adhesive.

Benefits

- Non-Flammable
- Non-Methylene Chloride/N-Propyl Bromide
- High Strength
- High Heat Resistance
- Quick Tack
- Fast Dry Time
- Lower VOC Formulation
- Fully Portable System
- HAPs Free

Application Instructions

- Be sure all surfaces are clean and free of grease, dirt, dust, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding. Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80% however, porous surfaces may need a second coat.
- Initial bond is a strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.

Applications

ForzaBOND® MC722 is specifically designed to bond:

- Marine carpeting including metal, wood, and composites
- Headliner to interiors
- Foam in upholstery and seating
- Plastic laminate in wood working
- Porous and insulation materials

Technical Data

Total Solids:	34-36%
VOC Content:	~322 g/L
Appearance:	Clear or Blue
Shelf Life:	12 Months
Dry Time*:	2-4 Minutes
Open Time:	Long
Solvent System:	Non-Flammable
Spray Pattern:	Web
Dry Time*: Open Time: Solvent System:	2-4 Minutes Long Non-Flammable

Sizes

22L Disposable Canister

108L Returnable Canister

*Dependent on temp & humidity

Recommended Equipment

- FK18 Spray Gun
- FK80 Hose
- 11001B Tip
- FK300 Valve Splitter

Recommended Cleanup

- FC-CAR (Citrus Cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM



