



**Double-Coated PET** 

ForzaTAPE® C-T5100 is a double-coated hybrid rubber based tape that bonds exceptionally well in cold, and wet condition

### **Benefits**

- Works exceptionally well in cold weather
- Provides strong bond to cold or damp surfaces
- · Performs well on LSE materials
- · Good cohesive strength
- High Initial tack
- Excellent peel and shear
- Bonds a wide variety of substrates

## **Product Application**

- Apply to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- Surfaces should be clean and free of dirt, oil, frost, etc. Stated temperatures are a range and products may be applied at higher or lower temperatures.
- Remove the release liner and apply with care to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- Apply with reccommended application pressure of 15 pounds per inch of tape width.
- At the point of final assembly or lamination, remove the release liner and apply with care to avoid wrinkles or trapped air.
- It is recommended that end sure test for suitability in their environement.

# **Applications**

**ForzaBOND® C-T5100** is used for bonding and mounting applications, including:

- Peel and stick applications for signage and display
- Attaching decorative and protective cladding in both interior and exterior applications

#### **Technical Data**

1.5 mils
1.5 mils
2.4 mils
5.9 mils
6.5 lbs/in 104oz/in
75+ hours to fail @ 72°F
Above -10°F (-23°C)
-65°F to 150°F (-54°C to 65.5°C)
6.2 lbs/in 99oz/in
12 months

### Size in Inches

3/4in x 180ft	60in x 1080ft
1-1/2in x 180ft	60in x 400ft
1-1/2in x 1080ft	11/2 x 1800

CREATING INDUSTRIAL ADHESIVE, TAPE AND SEALANT SOLUTIONS THAT OUTPERFORM

