

**ForzaBOND**° **C-C551** is a non-flammable high performance spray contact adhesive

### **Benefits**

- Non-flammable
- High coverage
- Over 220°F (105°C) temperature resistant
- 80% of final strength achieved immediately; full strength achieved in 24 hours
- · Fast drying with long open time
- No ODS (Ozone Depleting Substances)
- VOC free
- Qualifies for LEED\*-NC & CI EQ Credit 4.4: laminating adhesives shall contain no urea formaldehyde resins

## **Product Application**

- Be sure all surfaces are clean and free of grease, dirt, dust, etc. Apply to both surfaces to be bonded.
- Adhesive should be applied to each surface, allowed to dry (until non transferable to finger), then bonded under pressure.
- When brushing, multiple coats may be required on porous surfaces.
- When spraying, use of DeVilbiss JGA with FX tip and needle or Binks 2001 or 95 gun and 63B tip 2nd needle or similar equipment is satisfactory.
- Adhesive should be applied at a minimum of 2.0 dry grams per square foot. Apply pressure with a hand laminate roller or nip roller.
- Normal coverage required with web spray pattern is approximately 80%. Initial bond is strong enough to allow cutting or trimming immediately although ultimate strength is achieved in approximately 24 hours.
- Store away from heat, flames or other sources of ignition. If spray tip clogs unscrew the spray tip from the gun and clean with a solvent such as lacquer thinner or acetone.
- Do not use a pin on the spray tip orifice.

# **Applications**

ForzaBOND° C-C551 is a non-flammable, high-performance spray contact adhesive specifically designed for:

- Wall coverings
- Countertop bonding in cabinet manufacturing

#### **Technical Data**

Appearance:	Amber
Shelf Life:	12 months
Solids:	22-28 %
Solvent:	Non-Flammable
CONTONIC.	TOTT TTUTTITIALITY
voc:	0 g/L
voc.	09/L
Dataleaging	

## **Packaging**

1 Gallon Can	5 Gallon Pail
55 Gallon Drum	



