



CA Compliant Contact Adhesive

ForzaBOND® MC723 is a Low VOC, CA Compliant, Multi-Purpose, Contact Adhesive.

Benefits

- Low VOC
- Multi-Purpose
- Excellent bonding to porous substrates
- Aggressive bonds to nearly any surface
- Good heat resistance (up to 180°F/82°C)
- High-strength, long-term bond
- Low VOC & California Compliant (SCAQMD Rule 1168)

Application Instructions

- Be sure all surfaces are clean and free of grease, dirt, dust, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat.
- Initial bond is a strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.

Applications

ForzaBOND® MC723 is specifically designed to bond:

Marine carpeting including metal, wood, and composites

Forzo

- Head liner to interiors
- Foam in upholstery and seating
- Plastic laminate in wood working

Technical Data

Total Solids:	32-38%
VOC Content*:	< 45 g/L
Appearance:	Clear or Red
Shelf Life:	12 Months
Dry Time**:	2 - 4 Minutes
Open Time:	Long
Solvent System:	Flammable
Spray Pattern:	Web

Sizes

13oz Aerosol Can	108L Returnable Canister
22L Disposable Canister	55 Gallon Drum
	5 Gallon Pail

*Drum: ~77.66 g/L **dependent on temp & humidity

Recommended Equipment

- FK20 Gun
- FK30 Hose
- 9501 Tip
- FK300

Recommended Cleanup

- FC-CAR (citrus cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM



