



**Pressure Sensitive Adhesive** 

**ForzaBOND® MC724** is an aggressive and fast-drying pressure sensitive adhesive designed to bond a vast range of substrates.

## **Benefits**

- Polystyrene safe will not dissolve
- High Heat Resistance
- Aggressive Adheres to nearly any surface
- · Repositionable High tack Excellent coverage
- Web spray
- 80% of final strength achieved immediately
- Full strength achieved in 24 hours
- · Fast drying with long open time
- Excellent green strength and high heat resistance
- No ODS (Ozone Depleting Substances)
- OTC Compliant
- · Temporary fixturing single-sided applications

# **Product Application**

- Be sure all surfaces are clean and free of grease, dirt, dust, etc.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding. Parts should be mated with as much pressure as practical
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may be a second coat.
- Initial bond is a strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in approximately 24 hours.

## **Applications**

**ForzaBOND® MC724** is a pressure sensitive adhesive designed for use in applications using:

- Polystyrene
- · Foam of all types
- Flooring product
- Carpeting
- Vinyls (backed)
- Insulation
- Wood
- Fabrics
- Acoustic materials

### **Technical Data**

Total Solids:	26 - 32%
VOC Content:	< 469g/L
Appearance:	Clear or Green
Shelf Life:	12 months
Dry Time:	2-4 Minutes
Open Time:	Long
Solvent System:	Flammable
Spray Pattern:	Web

#### Sizes

13 oz Aerosol Can	22L Disposable Canister
	108L Returnable Canister

#### **Recommended Equipment**

- FK20 Spray Gun
- FK30 Hose
- Use 6501B Spray Tip
- FK300 Splitter Valve

#### **Recommended Clean Up**

- ForzaCLEAN FC-CAR (Citrus Cleaner)
- Organic Solvents

CREATING INDUSTRIAL ADHESIVE, TAPE, AND SEALANT SOLUTIONS THAT OUTPERFORM



