



**ForzaTAPE® C-T731** is a high performance and versatile double-sided PET Hybrid Rubber based tape.

## **Benefits**

- Works exceptionally well in cold weather
- Excellent holding power
- UV resistant

## **Product Application**

- Apply to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- Surfaces should be clean and free of dirt, oil, frost, etc. Stated temperatures are a range and products may be applied at higher or lower temperatures.
- Remove the release liner and apply with care to the part to be bonded, ensuring that no air is trapped between the tape and the substrate.
- Apply with reccommended application pressure of 15 pounds per inch of tape width.
- At the point of final assembly or lamination, remove the release liner and apply with care to avoid wrinkles or trapped air.
- It is recommended that end sure test for suitability in their environement.

## **Applications**

ForzaBOND® C-T731 is used for bonding and mounting applications, including:

- Peel and stick applications for signage and display
- Attaching decorative and protective cladding in both interior and exterior applications

## **Technical Data**

Application Temperature:	0°F (-17°C) to 125°F (51°C)
Service Temp:	-22°F to 248°F(-30°C to 120°F)
Shelf Life:	12 Months
Total Thickness:	3.6 mils

Size	
1 1/2 x 180	11/2 x 1080
2 x 180	
	custom sizes available

CREATING INDUSTRIAL ADHESIVE, TAPE AND SEALANT SOLUTIONS THAT OUTPERFORM